

PARTICULARS OF LONGITUDINAL FRAMING.

| FRAMING. | AMIDSHIPS. | | | ENDS. | | | AMIDSHIPS. | | | ENDS. | | | RIVETING. | | | | | |
|--|------------------------|-------------------------------------|--------|-------------|------------|--------|--------------------------|--------|-------|--------------------------|-------|---------|--|---|----------------------------------|----------------------|-----|-----|
| | In Ship. | | | In Ship. | | | Per Rule or as approved. | | | Per Rule or as approved. | | | Rivets in Longitudinal Frames. Diam. Speng. | Spacing of Rivets on each side of Transverses and Bulkheads. Inches. | Rivets in Brackets to Bulkheads. | | | |
| | Ins. | Ins. | Ins. | Ins. | Ins. | Ins. | Ins. | Ins. | Ins. | Ins. | Ins. | Number. | | | Diameter. Inches. | | | |
| Framing of Σ , L & C | | | | | | | | | | | | | | | | | | |
| Frames in Bridge 'tween Decks ... | | | | | | | | | | | | | | | | | | |
| Frames from Uppermost Continuous Deck | | | | | | | | | | | | | | | | | | |
| Framing from Awning, Shelter or Upper Deck to Margin Plate. | No. 1 | 7 | 3 1/2 | 40 | 6 1/2 | 3 1/2 | 42 | 7 | 3 1/2 | 40 | 7 | 3 1/2 | 36 | 7/8 | 5/4 | 5 1/4 | 4 | 7/8 |
| | " 2 | " | " | " | " | " | " | " | " | " | " | " | " | " | " | " | " | " |
| | " 3 | 8 | 3 1/2 | 42 | 8 | 3 1/2 | 40 | 8 | 3 1/2 | 40 | 7 1/2 | 3 1/2 | 42 | " | " | " | 8 | 7/8 |
| | " 4 | 8 | 3 1/2 | 54 | 8 | 3 1/2 | 44 | 8 | 3 1/2 | 54 | 8 | 3 1/2 | 44 | " | " | " | " | " |
| | " 5 | 9 | 3 1/2 | 44 | 8 | 3 1/2 | 54 | 9 | 3 1/2 | 44 | 8 1/2 | 3 1/2 | 44 | " | " | 3 15/16 for 9 rivets | " | " |
| | " 6 | 9 | 3 1/2 | 54 | 9 | 3 1/2 | 44 | 9 | 3 1/2 | 54 | 9 | 3 1/2 | 44 | " | " | " | " | " |
| | " 7 | 10 | 3 1/2 | 46 | 9 | 3 1/2 | 54 | 10 | 3 1/2 | 46 | 9 1/2 | 3 1/2 | 46 | " | " | " | " | " |
| | " 8 | 10 | 3 1/2 | 50 | 9 | 3 1/2 | 58 | 10 | 3 1/2 | 50 | 10 | 3 1/2 | 46 | " | " | 3 | 10 | " |
| | " 9 | 10 | 3 1/2 | 54 | 10 | 3 1/2 | 50 | 10 | 3 1/2 | 54 | 10 | 3 1/2 | 50 | " | " | " | " | " |
| | " 10 | 10 | 3 1/2 | 60 | 10 | 3 1/2 | 60 | 10 | 3 1/2 | 60 | 10 | 3 1/2 | 56 | " | " | " | " | " |
| | " 11 | 12 x 4 x 4 | 56 | 58 | 12 x 4 x 4 | 60 | 12 3/4 x 3 3/4 | 60 | - | - | - | - | - | 3 15/16 | " | " | 16 | " |
| | " 12 | 12 x 4 x 4 | 62 1/2 | 62 1/2 | 12 x 4 x 4 | 62 | 12 x 4 x 4 | 62 1/2 | - | - | - | " | " | " | " | " | " | " |
| | " 13 | 12 x 4 x 4 | 64 | 62 1/2 | 12 x 4 x 4 | 62 1/2 | 12 x 4 x 4 | 62 1/2 | - | - | - | " | " | " | " | " | 12 | " |
| | " 14 | Nos 14 to 22 inclusive as per No 13 | | | | | | | | | | | | | | | | |
| | " 15 | | | | | | | | | | | | | | | | | |
| | " 16 | | | | | | | | | | | | | | | | | |
| Spacing of Longitudinal Frames | Amidships | | | At Ends | | | | | | | | | | | | | | |
| | 30 | | | 27 | | | | | | | | | | | | | | |
| Double Bottoms | Tank Top Longitudinals | | | Bottom | | | DOUBLE BOTTOM AFT | | | UNDER | | | ENGINES & BOILERS | | | | | |
| Σ , L or E | 7 | 3 1/2 | 50 | 7 | 3 1/2 | 50 | | | | | | | 7/8 | 5/4 | 3 1/2 for 4 rivets | 6 | 7/8 | |
| Spacing of Longitudinals | Amidships | | | At Ends... | | | | | | | | | | | | | | |
| | 30 | | | 30 | | | | | | | | | | | | | | |
| Transverses. | | | | | | | | | | | | | | | | | | |
| In Bridge 'tween Decks | Depth and Thickness | | | Face Angles | | | Lugs to Shell* | | | Rivets in Lugs to Shell | | | | | | | | |
| | TRANSVERSE FRAMING | | | | | | | | | | | | | | | | | |
| In Awning, Shelter or Upper 'tween Decks. | Depth and Thickness | | | Face Angles | | | Lugs to Shell* | | | Rivets in Lugs to Shell | | | | | | | | |
| | 18 | 40 | ✓ | ✓ | - | - | 18 | 40 | ✓ | ✓ | ✓ | 7/8 | 3 15/16 | | | | | |
| | 4 | 3 1/2 | 44 | ✓ | - | - | 4 | 3 1/2 | 44 | ✓ | ✓ | | | | | | | |
| | 3 1/2 | 3 1/2 | 40 | - | - | - | 3 1/2 | 3 1/2 | 40 | - | - | " | " | | | | | |
| In Hold. | Depth and Thickness | | | Face Angles | | | Lugs to Shell* | | | Rivets in Lugs to Shell | | | | | | | | |
| | 34 | 46 | - | - | - | - | 34 | 46 | - | - | - | " | " | | | | | |
| | 6 1/2 | 3 1/2 | 75 | - | - | - | 6 1/2 | 4 | 70 | - | - | | | | | | | |
| | 6 | 6 | 46 | - | - | - | 6 | 6 | 46 | - | - | 7/8 | 3 15/16 | 2 ROWS | | | | |
| | 40 | - | - | - | - | - | 40 | - | - | - | - | - | - | | | | | |
| Spacing of Transverse Frames | 9'-2" | | | 9'-2" | | | | | | | | | | | | | | |
| * State if joggled or liners. | | | | | | | | | | | | | | | | | | |
| Longitudinal Beams of L , L or C | Roof Bridge Deck | 6 | 3 | 36 | - | - | - | 6 | 3 | 36 | 30 | | | | | | | |
| | Awg. or Shldr. Dk. | 6 | 3 | 50 | - | - | - | - | - | - | - | | | | | | | |
| | Upper | 7 | 3 | 38 | - | - | - | 7 | 3 | 38 | 29 | | | | | | | |
| | Second | 7 1/2 | 3 | 40 | - | - | - | 7 1/2 | 3 | 40 | 29 | | | | | | | |
| Third | 8 | 3 | 40 | - | - | - | - | - | - | - | | | | | | | | |
| In Ships: Plate. Angles. As approved. Plate. Angles. 10 x 38 4 x 3 1/2 40 10 x 38 4 x 3 1/2 40 18 x 40 5 flanges 18 x 40 5 flanges 11 x 40 4 x 3 1/2 40 11 x 40 4 x 3 1/2 40 20 x 40 6 1/2 x 3 1/2 75 20 x 40 6 1/2 x 4 x 70 | | | | | | | | | | | | | | | | | | |

The particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.