

ST EXPANSION

2ND

Below the reaction blades	80 ¹ / ₁₆ in.	1460 ¹ / ₁₆ in.	5.
	100 ¹ / ₁₆ in.	1500 ¹ / ₁₆ in.	8
		1600 ¹ / ₁₆ in.	7

S. S. "EMPRESS of AUSTRALIA"

Adjusting Washers of Safety Valves.

Forward Boilers.

	Centre Boilers.			Stb. Boilers.		Port. Boilers.	
No	1.	2.	3.	2.	3.	2.	3.
Stb.	9 ¹ / ₁₆ in.	11 ¹ / ₁₆ in.	13 ¹ / ₁₆ in.	15 ¹ / ₁₆ in.	11 ¹ / ₁₆ in.	12 ¹ / ₁₆ in.	10 ¹ / ₁₆ in.
Port.	13 ¹ / ₁₆ in.	10 ¹ / ₁₆ in.	12 ¹ / ₁₆ in.	10 ¹ / ₁₆ in.	11 ¹ / ₁₆ in.	11 ¹ / ₁₆ in.	6 ¹ / ₁₆ in.

After Boilers.

Stb.	30 ¹ / ₁₆ in.	31.5 ¹ / ₁₆ in.	27.5 ¹ / ₁₆ in.	31.5 ¹ / ₁₆ in.	28.5 ¹ / ₁₆ in.	29 ¹ / ₁₆ in.	29 ¹ / ₁₆ in.
Port.	29 ¹ / ₁₆ in.	30.5 ¹ / ₁₆ in.	31.5 ¹ / ₁₆ in.	33 ¹ / ₁₆ in.	37 ¹ / ₁₆ in.	30 ¹ / ₁₆ in.	31 ¹ / ₁₆ in.

Are the Bilge Suction Pipes, Cocks, and Valves arranged so as to prevent any communication between the sea and the bilges yes

Are the Screw Shaft Tunnel watertight yes Are they fitted with watertight doors yes worked from bridge & deck.

2010-9801M

