

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 18.5 ft., R.Q.D. ☒ ft., Bridge ☒ ft., Forecastle 19.0 ft.
(in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ☒

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 1st (Steel) wood sheathed

Official No. 135727 ; Signal Letters

State if Machinery is fitted aft

yes.

How are the surfaces preserved from oxidation? Inside

Paint & Cement

Outside

Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,			Fore peak tank,		
Double bottom, under Engines and Boilers,			After peak tank,		17 1/2
Double bottom, if under Engines only,			Deep tank, aft,	✓	15
Double bottom, if under Boilers only,			Deep tank, forward,	✓	
Double bottom, forward,			Other tanks, if fitted,	✓	
Total capacity of double bottom			(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules

yes.

Order for Special Survey No. 4827

Date 4.5.14

No. 260 in builder's yard.

DATES of Surveys held while building

1914 Apr. 10. May 5. 8. 21. 26 June 2. 3. 5. 9. 11. 19. 23. 25 July 1. 8. 9. 10. 12. 15. 28. 30 Aug 3. 5. 6. 11. 14. 18. 24. 27 Sept. 1. 3. 8. 15. 16. 21. 24. 25. 30 Oct. 6. 7. 9. 13. 16. 20. 21. 23. 26. 27. 29 Nov. 2 Dec. 1. 2. 4. 7. 9. 11. 15. 16. 17. 18. Dec. 21. 23

Total No. of Visits 63

Surveyor's Signature

Harry G. Farrar

Lloyd's Register Foundation