

Diameter of screw shaft as fitted 222 mm ✓ Diameter of thrust shaft as fitted 222 mm ✓
Diameter of screw shaft as per Rule 7 3/16" ✓ Is the screw shaft fitted with a continuous liner the whole length of the stern tube ✓
as fitted 7 3/16" x 1/2" = 190 mm ✓

M. S. "Virginia"

Cpn. 6244.

It is submitted that
this vessel is eligible for
THE RECORD.

✓ L. M. C. - 11.21. (Annual Survey)
Oil Engines 4 S.C.S.A. 6 Cy. 14 9/16", 22 7/16"
75 N.H.P. C.L.

A/S Aaleby Dieselmotorfabrik, Aaleby.

L.L.
30/11/21.

It is concluded that the following
articles of spare gear are included,
but this should be confirmed :-


2 connecting rod top end bolts & nuts
for main & auxiliary engines. none (trunks)

2 main bearing bolts & nuts for main
& auxiliary engines. ✓

~~1 set coupling bolts for thrust shaft.~~

1 set of valves for daily fuel supply
pump. (hand pump)

L.L.
2/12/21



© 2020

Lloyd's Register
Foundation

ed with a safety valve as per Rule. ✓ Can the internal surfaces of the receivers be examined. ✓ What means

er surfaces man hole fitted to routine air receiver. Is there a drain arrangement fitted at the lowest part of each receiver.