

OUTFIT AND SPARE GEAR. To be supplied with engine, as follows:--

Lamp Burner.....	1	for	each	engine.
Piston Rings.....	4	for	each	cylinder.
Injection Mouth Piece.....	2	for	each	cylinder.
Delivery Valve for Fuel Pump....	1	for	each	cylinder.
Suction Valve for Fuel Pump.....	1	for	each	cylinder.
Valve Balls.....	3	"	"	"
Valve Springs.....	6	"	"	"
Oil Valve for Lubricating Pump..	1	"	"	"
Oil Valve for Spindles for Lubricating Pump.....	3	"	"	"
Spiral Springs for Fuel Pump....	1	"	"	"
Spiral Springs for Reverse Pump.	1	"	"	"
Speed Regulator Springs.....	2	"	"	"
Air Valve Springs.....	3	"	"	"
Ebonite plate to govenor.....	1	"	"	"

EXTRA SPARE GEAR. To Lloyd's requirements, to be supplied with engine as follows:--

- 2. Bolts for Crank pin basses.
- 2. Bolts for Gudgeon pin brasses.
- 1. Suction Valve for Bilge pump.
- 1. Discharge Valve for Bilge pump.
- 1. Suction Valve for Circulating water pump.
- 1. Discharge Valve for Circulating water pump.
- 3. Studs for Cylinder cover.
- 1. Stud for Cylinder.
- 1. Stud for Thrust bearing.
- 1. Stud for Lubricator.
- 2. Studs for Main bearings.
- 1. Bolt for Eccentric Rod.
- 1. Bolt for rocking arm.
- 1. Bolt for regulator weight.

TOOLS. To be supplied with engine as follows:--

- 1. Oil Can.
- 1. Spirit Can.
- 1. Gauge for Fuel Pump.
- 4. Wrenches.
- 1. Shifting Spanner.
- 1. Key for Circulation Pump.
- 1. Key for Oil Valves.
- 1. Hook for Piston.
- 2. Keys for Fuel Pump.
- 2. Valve Keys.
- 1. Screw-driver.
- 1. Screw-driver for Valves.
- 1. Key for coupling.
- 1. Wrought Iron Turning Bar.



© 2020

Lloyd's Register  
Foundation

11114 0086