

ank shaft, dia. of journals as per rule 13.9 14.17 Crank pin dia. 14 7/8 No. of Cyllinders 3 Mid. length breadth 22.5 No. of Cranks 3 Thickness parallel to axis 9.25 Crank webs Mid. length thickness 10.775 Thunk Thickness around eye-hole 8

SIR W. G. ARMSTRONG, WHITWORTH & CO'S NO 1012. WILLIS-0066
NEWCASTLE-ON-TYNE, No. 80370
PARTICULARS OF LONGITUDINAL FRAMING.

FRAMING.			AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.					
			In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames.		Spacing of Rivets on each side of Transverses and Bulkheads.		Rivets in Brackets to Bulkheads.	
			Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Diam.	Speng.	Inches.	Number.	Diameter.	
ing of L, L & E			Transverse.																	
es in Bridge 'tween Decks			No. 1																	
es from Uppermost Continuous Deck			6 1/2	3 1/2	38	6	3 1/2	38	6 1/2	3 1/2	38	6	3 1/2	34	7/8	5/4		7	7/8	
Framing from Awning, Shelter or Upper Deck to Margin Plate.			" 2																	
			" 3	7 1/2	3 1/2	37	6 1/2	3 1/2	38	7	3 1/2	38	6	3 1/2	36			4" for 9 rivets		
			" 4	8	3 1/2	40				7 1/2	3 1/2	37							8	
			" 5							8	3 1/2	38								
			" 6	8 1/2	3 1/2	40	7	3 1/2	38	8	3 1/2	46	6	3 1/2	38					
			" 7	8 1/2	3 1/2	46				8 1/2	3 1/2	45	6 1/2	3 1/2	38			3"		
			" 8	9	3 1/2	41	7 1/2	3 1/2	42	9	3 1/2	41	7	3 1/2	42					
			" 9	9 1/2	3 1/2	41				9 1/2	3 1/2	41	7 1/2	3 1/2	42					
			" 10	9 1/2	3 1/2	46	8	3 1/2	42	9 1/2	3 1/2	46	8	3 1/2	38					
			" 11	10	3 1/2	50	8 1/2	3 1/2	44	10	3 1/2	50	8 1/2	3 1/2	42				10	
			" 12				8 1/2	3 1/2	48				8 1/2	3 1/2	48				11	
			" 13				9	3 1/2	46				9	3 1/2	44					
" 14				9 1/2	3 1/2	43				9 1/2	3 1/2	42								
" 15				9 1/2	3 1/2	48				9 1/2	3 1/2	48								
" 16																				
ing of			30"			24"			30"			24"								
adinal			for 7-11 plates																	
es																				
Tank Top Longitudinals			7	3 1/2	41	10	Same			7	3	37	Same			7/8				
Bottom			"	"	"	40				7	3 1/2	41				"	3 1/2" for 4 rivets			
of Longitudinals			30						30											
Transverses.			Rivets in Lugs to Shell Diam. Speng.																	
dge																				
Decks																				
ing,																				
or																				
ween																				
s.																				
if																				
ld.																				
Brackets																				
of Transverse Frames																				
Wa																				
ate if joggled or liners.																				
Bridge Deck																				
Awg.or Shltr.Dk.																				
Upper																				
Second																				
Third																				
inal																				
of																				
E																				
Transverse																				
Beams.																				

Particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.

29.30

12.14

S. Thomson

Manufacturer.

Lloyd's Register Foundation