

Length from fore part of stem to after part of stern post on summer L.W.L. See Sec. 3 (1a) **L** 474.0
 Breadth (greatest moulded) **B** 64.0
 Builders **A.B. Sötaaviken**

F.E.

Issued by Chief Ship Surveyor _____ Received from Chief Ship Surveyor _____
 VESSEL'S NAME St. Lw. Sc. M/V "BARFONN" Rpt. Got. No. 8324

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92).

1st Long. Transverse No. 17656 Depth "d" ✓
 Framing: Table No. _____ Description Bult. angles as approved.
 Longitudinal No. 47992
 Proportions $\frac{\text{Length}}{\text{Depth}} = \frac{12.72}{1}$


Deck Sheerstrake

Revised Rules

A length of chain cable requires to be supplied.

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed

✱ 100 A1 (Steel). Carrying Petroleum in bulk.
 1 D^K (Steel). Subject to a length of chain cable being supplied.
 Cell DB u E 71' 30" t, DT f 33' 6" 22 t FPT 196 t, APT 310 t.
 FK, 10 BH, pt cem. Lloyds A&CP.
 P 103'. B 35'. F 39'.
 Machy aft.


 29.5.31

© 2021
 Lloyd's Register Foundation
 W1123-0244

Depth & thickness of Intercoastal Plate...	1600 x 12.5	280 90 12.5	150 150 13	single app. 140 x 140 x 14
Top Bult Angles				
Angles to Shell				

Poop Deck, Angle, E or F ✓
 Spacing...
 230 90 12
 230 90 12
 200 75