

Percentage of strength of circ. end seams { rivets 48.5  
plate 85.7  
Percentage of strength of longitudinal joint { rivets 91  
combined 89.7

Percentage of strength of circ. intermediate rivets  
Working pressure of shell by Rules 183 lbs./sq.

Boiler No. 9705- Made by Hawtorn, Leslie & Co.

For Capt. Raimondi dell' Admiration, May 1899

Report No. 91672

a copy of  
It is submitted that this Report be returned to  
the British Surveyors for their guidance and  
for completion.

L. G.

Date 24/8/34.

5c.12.30.

Copy to 28/8/34



© 2021

Lloyd's Register  
Foundation

Working Pressure 200 lbs./sq.

Main stays: Material Steel

Tensile strength 28

Diameter { At body of stay, 3"  
or  
Over threads

No. of threads per inch 6

Area supported by each stay

Working pressure by Rules 181 lbs./sq.

Screw stays: Material Steel

Tensile strength 28

W1123-0298



(State quality of workmanship, opinions as to class, &c.)

*Mr Porter has been com*

Percentage of

Thickness of

Material

Length of p

Dimensions

nd plates

low are sta

ube plates

lean pitch

holders to

t centre

each

tensile stre

itch of stag

Working pr

Thickness

itch of sta

Working p

Diameter {

Working pr

*Mr Cooke*



© 2021

Lloyd's Register  
Foundation

TUE. 4 JUN 1935

*Engineer Surveyor to Lloyd's Register* Shipping.