

- 4 AUG 1937

(Received at London Office.....)

No. **908** Place **Schiedam** Date **2nd August 19 37**

We request that the Committee of Lloyd's Register will instruct the Society's Surveyors to Specially Survey during Construction the Hull, Engines and Boilers of the Vessel No. **663** building by Messrs.

Wilton-Fyenoord for Messrs. **Holland Amerika Lyn.**

of **10.000** Tons. Length **475'** Breadth **64'**, Depth **40'**
intended to be Classed **100 D1**

We undertake to arrange for every facility to be given to the Surveyors to carry out the duty in question, and we agree to pay the fees for the Surveyors' services, in addition to the actual travelling and other expenses incurred by the Surveyors in connection therewith.

This request is made upon the terms of the Rules and Regulations of Lloyd's Register of Shipping, which provide that:—

"While the Committees of the Society use their best endeavours to ensure that the functions of the Society are properly executed, it is to be understood that neither the Society nor any Member of any of its Committees is under any circumstances whatever to be held responsible for any inaccuracy in any report or certificate issued by the Society or its Surveyors, or in any entry in the Register Book or other publication of the Society, or for any error of judgment, default or negligence of any of its Committees or any Member thereof, or the Surveyors, or other Officers or Agents of the Society."

Auth'd

H.B. 4/8/37

Engine Makers

Boiler Makers

Signature

To the Secretary,

Lloyd's Register of Shipping,

71, Fenchurch Street, London, E.C.3.

WILTON - FIJENOORD.
(N.V. WILTON'S Machinefabriek en Scheepswerk)
(WILTON'S Engineering & Shipway Co.)
Maatschappij voor Scheeps- en Werktuigbouw
"FIJENOORD" N.V.)

Lloyd's Register
Foundation
W1134-0133

Forecastle Deck.

Stringer Plate breadth and thickness..... *915 x 92 mm* ✓

L PL

URE FROM
PLANS
OTED.

21 JUL. 1937

BETREFT:

GEZIEN DOOR:

BEANTWOORD:



© 2020

Lloyd's Register
Foundation

KEEL, Bar

Housmate keelplate

STEM

Plate 22-16 mm stiffness as approved ✓