

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office 13 SEP 1933

Date of writing Report 19 When handed in at Local Office 9/9/1933 Port of Leith
 No. in Survey held at Burntisland Date, First Survey 27/7/33 Last Survey 7/9/1933
 Reg. Book. Number of Visits 7
 A1057 on the S/S PUL BOROUGH Tons Gross 960.14
 Built at Burntisland By whom built Burntisland S.B.C.L. Yard No. When built 1933
 Owners Stephenson Clarke & Co. Ltd Port belonging to London
 Electric Light Installation fitted by The Burntisland S.B.C.L. Contract No. 178 When fitted 1933
 Is the Vessel fitted for carrying Petroleum in bulk No


System of Distribution Two wire lead & return
 Pressure of supply for Lighting 110 volts, Heating ✓ volts, Power ✓ volts.
 Direct or Alternating Current, Lighting Direct Power ✓
 If alternating current system, state frequency of periods per second ✓
 Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off Yes
 Generators, do they comply with the requirements regarding rating Yes , are they compound wound Yes
 are they over compounded 5 per cent. Yes , if not compound wound state distance between each generator ✓
 Where more than one generator is fitted are they arranged to run in parallel ✓ , is an adjustable regulating resistance fitted in series with each shunt field Yes
 Are all terminals accessible, clearly marked, and furnished with sockets Yes , are they so spaced or shielded that they cannot be accidentally earthed, short circuited, or touched Yes Are the lubricating arrangements of the generators as per Rule Yes
 Position of Generators Engine room S.B.C.L. side
 Is the ventilation in way of the generators satisfactory Yes , are they clear of all inflammable material Yes
 If situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators none and none , are the generators protected from mechanical injury and damage from water, steam or oil Yes
 are their axes of rotation fore and aft Yes
 Earthing, are the bedplates and frames of the generating plant efficiently earthed bolted direct to earth are the prime movers and their respective generators in metallic contact Yes
 Main Switch Boards, where placed Engine room S.B.C.L. side
 If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard same compartment Yes
 Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes Yes
 are they protected from mechanical injury and damage from water, steam or oil Yes , if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards no woodwork
 are they constructed wholly of durable, non-ignitable non-absorbent materials Yes , is all insulation of high dielectric strength and of permanently high insulation resistance Yes , if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework ✓
 and is the frame effectively earthed Bolted direct to earth. Are the fittings as per Rule regarding:— spacing or shielding of live parts Yes
 , accessibility of all parts Yes , absence of fuses on back of board Yes , proportion of omnibus bars Yes , individual fuses to voltmeter, pilot or earth lamp Yes , connections of switches Yes
 Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches Double Pole
 Main Switch Knife Type, & Single Pole Knife Type Switches for outgoing circuits

Instruments on main switchboard one ammeters one voltmeter's — synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system Two Earth Lamps

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules Yes

Joint Boxes Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule Yes



© 2020

Lloyd's Register
Foundation

Cables: Single, twin, concentric, or multicore	<i>No</i>	are the cables insulated and protected as per Tables IV or V of the Rules	<i>Yes</i>
Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load	<i>3 Volts</i>		
Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets	<i>No</i>		
Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound	<i>not as yet</i>		
Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage	<i>No</i>		
Support and Protection of Cables, state how the cables are supported and protected	<i>Cables on lead covered and Galvanised Clips on wire armoured cable</i>		
If cables are run in wood casings, are the casings and caps secured by screws	<i>✓</i>	, are the cap screws of brass	<i>✓</i>
separate grooves	<i>✓</i>	If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII	<i>Yes</i>
Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements	<i>✓</i>		
Joints in Cables, state if any, and how made, insulated, and protected	<i>✓</i>		
Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands	<i>Yes</i>		
Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed	<i>Yes</i>	state the material of which the bushes are made	<i>Lead</i>
Earthing Connections, state what earthing connections are fitted and their respective sectional areas	<i>Switchboard frame & Dynamo Baseplate bolted strict to earth.</i>		
, are their connections made as per Rule			
Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule	<i>Yes</i>		
Emergency Supply, state position and method of control of the emergency supply and how the generator is driven	<i>✓</i>		
Navigation Lamps, are these separately wired	<i>Yes</i>	, controlled by separate switch and separate fuses	<i>Yes</i>
are the switches and fuses grouped in a position accessible only to the officers on watch	<i>Yes</i>		
has each navigation lamp an automatic indicator as per Rule	<i>Yes</i>		
Secondary Batteries, are they constructed and fitted as per Rule	<i>✓</i>		
Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight	<i>Yes</i>		
are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected	<i>none</i>		
are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected	<i>none</i>		
, how are the cables led			
where are the controlling switches situated			
Searchlight Lamps, No. of		, whether fixed or portable	
are their fittings as per Rule			
Arc Lamps, other than searchlight lamps, No. of		, are their live parts insulated from the frame or case	
are their fittings as per Rule			
Motors, are their working parts readily accessible		, are the coils self-contained and readily removable for replacement	
are the brushes, brush holders, terminals and lubricating arrangements as per Rule		, are the motors placed in well-ventilated compartments in which	
inflammable gases cannot accumulate and clear of all inflammable material			
are they protected from mechanical injury and damage from water, steam or oil		, are their axes of rotation fore and aft	
if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type			
, if not of this type, state distance of the combustible material horizontally or vertically above the motors		and	
Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule			
Lightning Conductors, where lightning conductors are required, are these fitted as per Rule			
Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings			
If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office			

PARTICULARS OF GENERATING PLANT.							
DESCRIPTION OF GENERATOR.	No. of	RATED AT			DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.		Fuel Used.	Flash Point of Fuel.
MAIN	one	3	110	27	350	Open Type Engine	
AUXILIARY							
EMERGENCY							
ROTARY TRANSFORMER							
GENERATOR, LIGHTING AND HEATING CONDUCTORS.							
DESCRIPTION.	CONDUCTORS.	COMPOSITION OF STRAND.	TOTAL MAXIMUM CURRENT AMPERES.	Approximate Length, (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.	
	No. per Pole.	Total Effective Area per Pole Sq. Ins.	No. Diameter.	In Circuit.	Rule.	Rubber	L.C. and W.A.
MAIN GENERATOR	1	.0115	7	.064	21	38.5	10 feet
EQUALISER CONNECTIONS							
AUXILIARY GENERATOR							
EMERGENCY GENERATOR							
ROTARY TRANSFORMER	{ MOTOR GENERATOR						
ENGINE ROOM	1	.0030	3	.036	7	12	6 feet
BOILER ROOM							
AUXILIARY SWITCHBOARDS							
Navigational	1	.0030	3	.036	3.5	12	268
ACCOMMODATION	Scallop	1	.0030	3	.036	5	12
	Engines	1	.0045	7	.029	5.5	12
WIRELESS							
SEARCHLIGHT							
MASTHEAD LIGHT	1	.0020	3	.029	.36	7.8	270
SIDE LIGHTS	1	.0020	3	.029	.36	7.8	40
COMPASS LIGHTS	1	.0020	3	.029	.36	7.8	24
POOP LIGHTS							
CARGO LIGHTS							
ARC LAMPS							
HEATERS							
MOTOR CONDUCTORS:							
DESCRIPTION.	No. of Motors.	CONDUCTORS.	COMPOSITION OF STRAND.	TOTAL MAXIMUM CURRENT AMPERES.	Approximate Length, (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Effective Area per Pole Sq. Ins.	No. Diameter.	In Circuit.	Rule.		
BALLAST PUMP							
MAIN BILGE LINE PUMPS							
GENERAL SERVICE PUMP							
EMERGENCY BILGE PUMP							
SANITARY PUMP							
CIRC. SEA WATER PUMPS							
CIRC. FRESH WATER PUMPS							
AIR COMPRESSOR							
FRESH WATER PUMP							
ENGINE TURNING GEAR							
ENGINE REVERSING GEAR							
LUBRICATING OIL PUMPS							
OIL FUEL TRANSFER PUMP							
WINDLASS							
WINCHES, FORWARD							
WINCHES, AFT							
STEERING GEAR—							
(a) MOTOR GENERATOR							
(b) MAIN MOTOR							
WORKSHOP MOTOR							
VENTILATING FANS							

All Conductors are of annealed copper conforming to British Standard Specification No. 7.

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

FOR THE BURNTISLAND SHIPBUILDING COMPANY LTD.

W. J. Ayre

MANAGING DIRECTOR
W. J. Ayre

Electrical Engineers.

Date

8/9/33

COMPASSES.

Distance between electric generators or motors and standard compass

107'

Distance between electric generators or motors and steering compass

102'

The nearest cables to the compasses are as follows :—

A cable carrying .5 Ampères 7" feet from standard compass 7" feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power. Yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted. Yes

The maximum deviation due to electric currents was found to be Nil degrees on any course in the case of the standard compass, and degrees on course in the case of the steering compass.

FOR THE BURNTISLAND SHIPBUILDING COMPANY LTD.

W. J. Ayre

MANAGING DIRECTOR
W. J. Ayre

Builder's Signature.

Date 8/9/33

Is this installation a duplicate of a previous case No If so, state name of vessel ✓

General Remarks (State quality of workmanship, opinions as to class, &c.) This installation has been

efficiently fitted on board in accordance with the rules.

The materials & workmanship are sound & good & the installation was found satisfactory under full load & working conditions.

It is submitted that
this vessel is eligible for
THE RECORD.

Electric light

BB
13/9/33

Total Capacity of Generators 3 Kilowatts.

The amount of Fee ... £ 5 : 0 0 When applied for,
8-9-1933

Travelling Expenses (if any) £ *✓* When received,
30-9-1933

Chas. R. Rowcliffe
Surveyor to Lloyd's Register of Shipping.

(The Surveyors are requested not to write on or below the space for Committee's Minute.)

Committee's Minute

Assigned

© 2020



Lloyd's Register
Foundation