

Rpt. 1*.

PARTICULARS OF LONGITUDINAL FRAMING.

FRAMING.			AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.						
			In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames.		Spacing of Rivets on each side of Transverses and Bulkheads.		Rivets in Brackets to Bulkheads.		
			Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Diam.	Speng.	Inches.	Number.	Diameter.	
Framing of L or D			Shelter Deck						8 3 1/2 375						7/8 5/4		5 1/4		9 7/8		
Frames in Bridge 'tween Decks ...															7/8 5/4		5 1/4		9 7/8		
Frames from Uppermost Continuous Deck															7/8 5/4		5 1/4		9 7/8		
Framing from Awning, Shelter or Upper Deck to Margin Plate.			No. 1																		
			" 2																		
			" 3																		
			" 4																		
			" 5														4 3/8 for 10 Rivets		5 1/4 elsewhere		
			" 6						8 3 1/2 40												
			" 7						8 3 1/2 46												
			" 8						9 3 1/2 44												
			" 9						9 3 1/2 48												
			" 10						8 3 1/2 375			1/5 Amidships			5/4		3 1/2 for 4 Rivets				
" 11						8 3 1/2 375						5/4		3 1/2 - 4 "							
" 12																					
" 13																					
" 14																					
" 15																					
" 16																					
Spacing of longitudinal Frames			Amidships			27			26			27			26						
			At Ends			26						26									
Tank Top Longitudinals									8 3 1/2 375						7/8 5/4		4 3/8 for 4 Rivets		Note! In plates 34 to 48		
Bottom									8 3 1/2 375						7/8 5/4		3 1/2 - 4 -		3/4 Rivets 3 1/4 Pitch		
Framing of Longitudinals			Amidships			28													Plates 48 to 66 7/8 Rivets		
			At Ends...									21							4 3/8 pitch		
Transverses.															Rivets in Lugs to Shell						
Bridge			Depth and Thickness																		
'tween Decks			Face Angles																		
			Lugs to Shell*																		
Awning, Shelter or 'tween Decks.			Depth and Thickness			23 12 x 40			13 12 x 40												
			Face Angles			3 1/2 3 1/2 44															
			Lugs to Shell*			3 1/2 3 1/2 375						7/8 4 3/8			Joggled in places						
n Hold.			Depth and Thickness			23 1/2 x 46			28 15												
			Face Angles			6 6 3/4															
			Lugs to Shell*			6 6 46						7/8 4 3/8			Double for 4 Spaces above Tank Top and in fore hold to upper deck.						
			Brackets			44															
Framing of Transverse Frames						11 1 1/2			7 10 12 ft.								From 73 forward 4 ft Spaces and from 16 aft 1' 10" to 2' 0" Joggled amidships, Lined elsewhere.				
			* State if joggled or liners.																		
Longitudinal Beams of L or D			Bridge Deck												Spacing Varying from 30" to 37"		In Ships Plate 16 Angles 7		As approved Plate Angles		
			Awg. or Shltr. Dk.			7 3 1/2 34											Transverse 11 x 38 8 x 3 1/2 46		11 x 7/8 8 x 3 1/2 46		
			Upper			7 3 1/2 34									34 to 37		Beams 14 x 40 8 x 3 1/2 38		14 x 40 8 x 3 1/2 38		
			Second																		
			Third																		

The particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.