

TUE. 18 JUL. 1922

REPORT ON ELECTRIC LIGHTING INSTALLATION. No. 28362

Port of NEWCASTLE ON TYNE Date of First Survey May 2 Date of Last Survey 17 July 22 No. of Visits 4
 No. in on the Iron or Steel S.N.A.-7 Port belonging to House
 Reg. Book Built at Dublin & Limerick By whom Messrs. Gibson & Graham & Co. When built 1922
 Owners Soc. Nationale d'Affrètements Owners' Address House
 Yard No. 245 Electric Light Installation fitted by Messrs. Charles Chapman & Co. Ltd. When fitted 1922

DESCRIPTION OF DYNAMO, ENGINE, ETC.

One enclosed type vertical engine direct coupled to a continuous current compound wound dynamo

Capacity of Dynamo 85 Amperes at 100 Volts, whether continuous or alternating current continuous

Where is Dynamo fixed In Engine Room Whether single or double wire system is used Single

Position of Main Switch Board Near Dynamo having switches to groups A.B.C.D.E. of lights, &c., as below

Positions of auxiliary switch boards and numbers of switches on each Each light & group of lights provided with switches as required

If fuses are fitted on main switch board to the cables of main circuit Yes and on each auxiliary switch board to the cables of auxiliary circuits Yes and at each position where a cable is branched or reduced in size Yes and to each lamp circuit Yes

If vessel is wired on the double wire system are fuses fitted to both flow and return wires or cables of all circuits including lamp circuits Yes

Are the fuses of non-oxidizable metal Yes and constructed to fuse at an excess of 50 per cent over the normal current

Are all fuses fitted in easily accessible positions Yes Are the fuses of standard dimensions Yes If wire fuses are used

are permanent instructions fitted on or near each switch board giving particulars of proper size of fuse for each circuit Yes

Are all switches and fuses constructed of incombustible materials and fitted on incombustible bases Yes slate & porcelain

Total number of lights provided for 128 arranged in the following groups:-

A. Deck Round	50 lights each of	16	candle power requiring a total current of	28.0	Amperes
B. Engine Room	45 lights each of	16	candle power requiring a total current of	25.2	Amperes
C. Engine Room	33 lights each of	16	candle power requiring a total current of	18.5	Amperes
D. Wireless	lights each of	.	candle power requiring a total current of	25	Amperes
E. Spare	lights each of	.	candle power requiring a total current of	.	Amperes
2 Mast head light with	1 lamp each of	32	candle power requiring a total current of	2.2	Amperes
2 Side light with	1 lamp each of	32	candle power requiring a total current of	2.2	Amperes
Cargo lights of	.	.	candle power, whether incandescent or arc lights	.	.

If arc lights, what protection is provided against fire, sparks, &c.

Where are the switches controlling the masthead and side lights placed In Wheel House

DESCRIPTION OF CABLES.

Main cable carrying	85 Amperes, comprised of	19 wires, each	14 S.W.G. diameter, .094	square inches total sectional area
Branch cables carrying	28 Amperes, comprised of	7 wires, each	17 S.W.G. diameter, .017	square inches total sectional area
Branch cables carrying	18.5 Amperes, comprised of	7 wires, each	18 S.W.G. diameter, .0125	square inches total sectional area
Leads to lamps carrying	1.6 Amperes, comprised of	1 wires, each	19 S.W.G. diameter, .0018	square inches total sectional area
Cargo light cables carrying	1.1 Amperes, comprised of	3 wires, each	22 S.W.G. diameter, .0018	square inches total sectional area

DESCRIPTION OF INSULATION, PROTECTION, ETC.


Vulcanized india rubber taped & braided & lead covered where exposed steel armored cable

Joints in cables, how made, insulated, and protected No joints except mechanical ones

Are all the joints of cables thoroughly soldered, and the flux used not containing acids or other corrosive substances Yes Are all joints in accessible positions, none being made in bunkers, cargo spaces, or spaces which may at any time be used for carrying cargo, stores, or baggage Yes

Are there any joints in or branches from the cable leading from dynamo to main switch board No

How are the cables led through the ship, and how protected Lead & armored cables run through bulkheads & clipped to underside of deck with strong galvanized iron clips



© 2020

Lloyd's Register Foundation

W1155-0046

DESCRIPTION OF INSULATION, PROTECTION, ETC.—continued.

Are they in places always accessible *No*What special protection has been provided for the cables in open alleyways or where exposed to weather or moisture *Lead & steel
armoured vessel cables*What special protection has been provided for the cables near galleys or oil lamps or other sources of heat *Lead & armoured cables*What special protection has been provided for the cables near boiler casings *" " "*What special protection has been provided for the cables in engine room *" " "*How are cables carried through beams *In lead bushes* through bulkheads, &c. in *HT glands*How are cables carried through decks *In galvanised iron deck tiles*Are any cables run through coal bunkers *Yes* or cargo spaces *Yes* or spaces which may be used for carrying cargo, stores, or baggage *Yes*If so, how are they protected *Lead & armoured cables*Are any lamps fitted in coal bunkers or spaces which may at times be used for cargo, coals, or baggage *No*If so, how are the lamp fittings and cable terminals specially protected *.*Where are the main switches and fuses for these lights fitted *.*If in the spaces, how are they specially protected *.*Are any switches or fuses fitted in bunkers *No*Cargo light cables, whether portable or permanently fixed *.*How fixed *.*In vessels fitted on the single wire system, how is the dynamo terminal fixed to the hull of vessel *Double wire system*How are the returns from the lamps connected to the hull *.*Are all the joints with the hull in accessible positions *.*Is the installation supplied with a voltmeter *Yes*, and with an amperemeter *Yes*, fixed *in switchboard*

VESSELS BUILT FOR CARRYING PETROLEUM.

In vessels built for carrying petroleum, are all switches and fuses fitted in positions not liable to the accumulation of petroleum vapour or gas *.*Are any switches, fuses, or joints of cables fitted in the pump room or companion *.*How are the lamps specially protected in places liable to the accumulation of vapour or gas *.*

The copper used is guaranteed to have a conductivity of not less than that of the Engineering Standards Committee's standard, and the wires are protected by tinning from the sulphur compounds present in the insulating material.

Insulation of cables is guaranteed to have a resistance of not less than *600* megohms per statute mile at 60° Fahrenheit after 24 hours' immersion in water, the test being made after one minute's electrification at not less than 500 volts and while the cable is still immersed.

The foregoing statements are a correct description of the Electric Light installation fitted by us on this vessel and we declare that it is at this date in good order and safe working condition.

W. H. Morrison

Director.

Electrical Engineers

Date *July 12th 1922*

COMPASSES.

Distance between dynamo or electric motors and standard compass *66 ft*Distance between dynamo or electric motors and steering compass *60 "*

The nearest cables to the compasses are as follows:—

A cable carrying *1.1* Amperes *12* feet from standard compass *6* feet from steering compassA cable carrying *1.1* Amperes *6* feet from standard compass *12* feet from steering compassA cable carrying *.* Amperes *.* feet from standard compass *.* feet from steering compassHave the compasses been adjusted with and without the electric installation at work at full power *Yes*The maximum deviation due to electric currents, etc., was found to be *Nil* degrees on *all* course in the case of thestandard compass and *Nil* degrees on *all* course in the case of the steering compass.

OSBOURNE GRAHAM & CO., LIMITED.

*A. H. Thomson*Builder's Signature. Date *14th July '22*

GENERAL REMARKS.

*The above installation is in accordance with the Society's Rules. The vessel is eligible in my opinion for notation elec light, wireless**It is submitted that
this vessel is eligible for
THE RECORD.**Elec. Light.**See L 9.0.0**Applied for 26/6/22
Paid 28/7/22**Now**L. J. 19/7/22**L. J. Davis & W. T. Badger*

Surveyor to Lloyd's Register of Shipping.

Committee's Minute

THE SURVEYORS ARE REQUESTED NOT TO WRITE ACROSS THIS MARGIN.