

425.6

Framing Depth "d," at middle of length. See
 Sec. 3 (1d) }
 Proportions—Depth to Length—Uppermost con-
 tinuous deck to top of keel }

11-04

Port of Registry London

at, or in dry

dry dock

COPY.

Rpt. 12.

FREEBOARD VERIFICATION FORM FOR STEAMERS.

When received in London Office

Port Sunderland.

Vessel's Name "SILVERBEECH".

Official No.

No. in Reg. Book 90861

Port of Registry (For Foreign Vessels)

Iron or Steel Steel State whether Classed by Lloyd's Register Contemp.

Name of Owners

Date of Verification 26. 7. 26.

I have to report that the Freeboard from the centre of disc to the top of the statutory deck line, and the lines in connection therewith, as given below, assigned by the Committee to this vessel, have been correctly marked on the vessel's sides, in accordance with the printed instructions:—

From centre of disc to top of statutory deck line 3 ft. 10 ins.

From centre of disc to top of statutory deck line } --- ft. --- ins.
 at awning or part-awning deck . . . }Fresh Water line above centre of disc . . . 6 $\frac{3}{4}$ ins.

Indian Summer line above centre of disc . . . 6 ins.

Winter line below centre of disc . . . 6 ins.

Winter North Atlantic line below centre of disc --- ins.

Distance between the top of statutory deck line on vessel's side and the intersection of the continuation of upper side of ~~wood~~ steel deck with the vessel's side } at main-spar or upper dk. 1 ins.
 } at awning or pt.-awning dk. --- ins.

NOTE.—It should be clearly shown whether the statutory deck line is set off from a wood or steel deck.

Maximum Summer Draught corresponding to the freeboard assigned as shown on the Builders' Displacement Scales:—

(Signed) T. SHAW. Surveyor.

(To be filled up in London Office.)

Statement No. Date of Committee's Minute 15. 7. 26.

Particulars for Record in Register Book. { Moulded Depth . . . 29 ft. 0 ins.
 { Freeboard . . . 3 ft. 10 ins.
 { Corresponding Draught 25 ft. 5 $\frac{3}{4}$ ins.

Freeboards compared and found correct by Date

Is fee paid?

Form for Certificate

Instructions

Date

Certificate written

Noted for posting

2m, 12, 24.

Condition of Class.
Tonnage Opening Fitted.

Bracket Floors, breadth and thickness at middle line.....

33

42

breadth and thickness at

39

42

Forecastle Deck, Axx B A C [.....

8


3

42

Spacing

24

and 27



© 2020

Lloyd's Register Foundation

W1157-0032