

Rpt. 12.

FREEBOARD VERIFICATION FORM FOR STEAMERS.

Port

(When received in London Office 24.2.19

Vessel's Name

Official No.

No. in Reg. Book

Port of Registry (For Foreign Vessels)

Iron or Steel

State whether Classed by Lloyd's Register

Name of Owners

Date of Verification 21.2.19

I have to report that the Freeboard from the centre of disc to the top of the statutory deck line, and the lines in connection therewith, as given below, assigned by the Committee to this vessel, have been correctly marked on the vessel's sides, in accordance with the printed instructions :—

From centre of disc to top of statutory deck line 9 ft. 5 ins.

From centre of disc to top of statutory deck line } at awning or part-awning deck . . . } ft. ins.

Fresh water line above centre of disc . . . 6 1/2 ins.

Indian Summer line above centre of disc . . . 5 1/2 ins.

Winter line below centre of disc . . . 5 1/2 ins.

Winter North Atlantic line below centre of disc . . . ins.

Distance between the top of statutory deck line on vessel's side and the intersection of the continuation of upper side of wood or iron deck with the vessel's side } at main, spar or upper dk. 1 3/4 ins.

steel } at awning or pt.-awning dk. ins.

NOTE.—It should be clearly shown whether the statutory deck line is set off from a wood or iron deck

S. Henshall Surveyor.

(To be filled up in London Office.)

Statement No 25342 Date of Committee's Minute 14.2.19

Particulars for Record in Register Book. { Moulded Depth . . . 34 ft. 0 ins. { Freeboard . . . 9 ft. 5 ins. { Corresponding Draught 24 ft. 11 ins.

Freeboards compared and found correct by date

Is fee paid? Form for Certificate

Instructions date

Certificate written Noted for posting

2m 3.18.—T.

Angles on upper edge

Spacing

BEAMS, Forecastle Deck, Angle, Bulb Angle,

Forecastle Deck Stringer Plate, b'dth & th'kns

W116-0116

Condition of class



© 2019

Lloyd's Register Foundation