

7/14/10

Doorloopt vlamvrijheid: B.V. = 1:5

Verwarmend oppervlak.

pijpen	1855 □'
vuurgangen	170 "
vlamkasten	205 "
<u>Totaal</u>	<u>2230 □' = 207 m²</u>

Constructuend volgens Lloyd's regels.

Omschrijving	Totaal <i>1. 1902</i>		minimum tek in %	Soort materiaal
	41. per %	26. per %		
Rimpelkassengroff	41. 47	26. 30	24	S. va. W. v. j. z. j. z.
Rosken	38. 44	24. 1-27. 9	26	" "
Wankass-platen	34-40	21.6-25.4	26	" "
Vuur-gangen	34-40	21.6-25.4	26	" "
Wooftakken	42-48	26.6-30.4	20	" "
Daadstakken	34-40	21.6-25.4	25	" "
Nagels	41. 47	26. 30	25	" "
Steenhouwen in vloer	42-48	26.6-30.4	20	" "
Vloeren in steenhouwen	35	22. 7	12	W. v. j. z. j. z.

de voorring [↖]bestaat
uit 2 platen van
gelijke lengte.

vingang afdraaien
front vixoren

ORDER N° 9526 A° 1910
TEKENING N° 1.

7/4/10

© 2020
Lloyd's Register
Foundation

Ned fabriek van Werk & Spoor Mat.


2 Single Ended Boilers

S.S. No 108.



Koninkrijk der Nederlanden

Class. 4888



W1203 - 0122



© 2020

Lloyd's Register
Foundation