

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ☒ ft., R.Q.D. ☐ ft., Bridge ☒ ft., Forecastle ☒ ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ☒

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) 2 DKS: STEEL Weather deck part covered with wood. 2 tiers of Beams.
 Official No. _____; Signal Letters _____ State if Machinery is fitted aft Yes.
 How are the surfaces preserved from oxidation? Inside Paint & Cement wash. No Cement in d.b. tanks except under Boilers. Outside Paint & anti-souling combination

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cellular System

Where Fitted.	*Length. metres. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. metres. Feet.	Water Capacity. Tons.
Double bottom, <u>etc.</u>	237.11	72.20 / 1062	Fore peak tank,	6.40	150
Double bottom, under Engines and Boilers,	67.51	20.60 / 100	After peak tank,	5.00	150
Double bottom, if under Engines only,	309.5	—	Deep tank, aft, <u>(Nafta) oil</u>	7.60	1070
Double bottom, if under Boilers only,	—	—	Deep tank, forward, <u>Topside Beam tanks</u>	14.80	180
Double bottom, <u>forward</u> ,	—	—	Other tanks, if fitted, <u>aft.</u>	14.48	140
Total capacity of double bottom		1162	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks. State whether the above have been tested as required by the Rules. All tested except Nafta tanks & Topside Beam tanks

Order for Special Survey No. ☒ Date 1922. Nov. 28 Dec. 8, 9, 11. 1923. Apr 19, 20, 26, 30 May 3, 4, 5, 8, 9.

No. 232 in builder's yard. DATES of Surveys held while building

Surveyor's Signature Colin Bartlett

Total No. of Visits 13

