

# With or Without Disconnected Erections.

## STEEL STEAMER.

MON. 19 NOV. 1923

Received at London Office

Date of completion of report 30 October 1923 Port of New York  
Survey held at Newark N.J. Date, First Survey 27 Sept Last Survey 26 October 1923

On the (State if Single, Twin, or Triple Screw) single screw s/s ATLANTIC ex WEST CATANACE Rig 2 masts  
(37027 R.B.)

TONNAGE under 5058 CLASS 100A1

Do. between Tonnage Dk. and 3rd and 4th Dk. 5058 11

Total under Upper Dk. 5058 11

Do. of Poop 143 41

Do. of R.Q.Dk. 14 42

Do. of Bridge House 19 83

Do. of Houses on Dk. 168 30

Do. of excess of Hatchways 50 60

Do. above Crown of Engine Room 69 64

Gross Tonnage 5524

Less Crew Space 208 06

Less above Crown of Engine Room 176 77

Less Navigation Spaces 93 26

Register Tonnage 3455

Destined Voyage Baltimore

If Surveyed while Building, Afloat, or in Dry Dock afloat & in dry dock

Length on Deck as per Rule 410 5 1/2

Breadth Moulded 54 0

Depth, Actual—Top of Floors to top of Upper Dk. Beams 27 2 1/2

Do. Second Dk. Beams 17 7

No. of Decks with flat laid 2

No. of Tiers of Beams

Dimensions of Ship per Register, Length 410 5 breadth 54 0 depth 27 2

Moulded depth, ft. 38 ins. 3 To Bridge Dk. Round of Upper 13 1/2 ins.

Moulded depth, ft. 29 ins. 9 To Upper Dk. Dk. Beam, Actual

FRAMING.

FRAME, Angles or Bars amidships 10 3 7/8 50 10 3 7/8 50

Do. in peaks 6 3 1/2 38 6 3 1/2 38

Do. in way of Double Bottoms at Solid Floors 3 1/2 3 1/2 44 3 1/2 3 1/2 44

at intermdt. Bkts. 27 27

Spacing of Frames from centre to centre amidships 24 24

length to Collision bulkhead 3 1/2 3 1/2 38 3 1/2 3 1/2 38

in peaks 3 3 44 3 3 44

REVERSED FRAME, Angles, in peaks 3 1/2 3 1/2 38 3 1/2 3 1/2 38

Do. in way of Double Bottoms at Solid Floors 3 3 44 3 3 44

at intermdt. Bkts. 10 10

FRAMING, depth of girder 44 36 44 36

FLOORS, depth and thickness of Floor Plate at mid-line for length amidships 44 36 44 36

in way of Engine and Boiler Spaces 44 36 44 36

thickness at the ends of vessel 44 36 44 36

depth at 1/2 the half breadth, as per Rule 44 36 44 36

height extended at the Bilges 44 36 44 36

FLOORS in Cell. Double Bottoms 44 36 44 36

state if flanged (top & bottom) 20 20

Spacing of Solid floors 27 27

CENTRE GIRDER, in Dbl. bottom, dpth. & thicknss. 44 52 44 52

Angles, Top 3 1/2 3 1/2 44 3 1/2 3 1/2 44

Bottom 4 4 50 4 4 50

Floors 3 1/2 3 1/2 44 3 1/2 3 1/2 44

Brackets at intermdt. frmg. width & thknss 1 36 1 36

SIDE GIRDERS, number on each side & thickness 1 36 1 36

state if flanged (top and bottom) 20 20

Angles (top and bottom) 3 1/2 3 1/2 44 3 1/2 3 1/2 44

to Floors 44 50 44 50

MARGIN PLATE, depth (exclusive of flange) and thickness 4 4 50 4 4 50

Angle to Outside Plating 3 1/2 3 1/2 44 3 1/2 3 1/2 44

Floors 3 1/2 3 1/2 44 3 1/2 3 1/2 44

Brackets at intermdt. frmg. width & thknss 59 40 59 40

Height of Outside Brackets above at bilge 44 52 44 52

INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake 44 52 44 52

in Engine and Boiler space 56 56

Remainder in Holds 42 42

BEAMS, Upper Deck, Single Angle, Bulb 7 3 44 35 7 3 44 35

Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

In way of Long Bridge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Second Deck, Single Angle, Bulb 12 3 1/2 50 12 3 1/2 50

Angle, Plate, Tee Bulb, or Channel 12 3 1/2 50 12 3 1/2 50

Spacing 54 54

BEAMS, Third and Fourth Deck, Single Angle, Bulb 7 3 44 35 7 3 44 35

Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Forecastle Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35

Angles on upper edge 7 3 44 35 7 3 44 35

Spacing 27 27

BEAMS, Poop Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 8 3 41 38 8 3 41 38

Angles on upper edge 8 3 41 38 8 3 41 38

Spacing 54 54

BEAMS, Bridge Deck, Angle, Bulb, Angle, Plate, Tee Bulb, or Channel 7 3 44 35 7 3 44 35







PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 43 ft., R.Q.D. ✓ ft., Bridge 115 ft., Forecastle 47 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) 2 DKS (STL) / Official No. 217709 ; Signal Letters LQGP State if Machinery is fitted aft no / How are the surfaces preserved from oxidation? Inside Pt. Cam Outside Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors. Cellular

Where Fitted.	Length. Feet.	Water Capacity. Tons.	Where Fitted.	Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	132'-9"	409	Fore peak tank,	21'-6"	135
Double bottom, under Engines and Boilers,	45	196	After peak tank,	24	226
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,	20'-3"	667
Double bottom, forward,	175'-6"	657	Other tanks, if fitted,		
	Total capacity of double bottom	1262	(If necessary, furnish further information by sketch.)		

\* The wells are not to be included in the lengths of the tanks. 353-3

State whether the above have been tested as required by the Rules. yes

Order for Special Survey No. ✓

Date ✓

No. 3 in builder's yard.

DATES of Surveys held while building

Surveyor's Signature

© 2021

Total No. of Visits

Lloyd's Register Foundation