

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ✓ ft., R.Q.D. $14\frac{1}{4}$ ft., Bridge $58\frac{3}{4}$ ft., Forecastle 3 (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ✓

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given should appear in the Register Book) 1 *DN (Stl)*. 1 *tr B*. *Two decks (Stl) forward.*

Official No. 18657; Signal Letters NVKW. State if Machinery is fitted aft No

How are the surfaces preserved from oxidation? Inside Cement + paint Outside Paint.

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors.

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	47	71.47	Fore peak tank,		41.6
Double bottom, under Engines and Boilers,	35.25	81.20	After peak tank,		37.1
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,	123.4	236.76	Other tanks, if fitted,		
	Total capacity of double bottom	389.43	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules. *Yes*

Order for Special Survey No.

Date


No. 386 in builder's yard.

DATES of Surveys held while building

17th May to 3rd December 1915

Continuous attendance

Surveyor's Signature



© 2020

Lloyd's Register Foundation