

"GIULIA" PEIRCE

The Ship

Approved in plan: or Rule

ties at hatches

850 x 14 ✓? Dumbly

1700 x 13% Doubling

plating

 $10.44 \frac{m}{m}$

at Sides $\rightarrow 12.5\mu \vee 10.5\mu$

Ends N^{os} 28, 48, 76 & 106 ✓

9^{my} - 6^{my} ✓

9.5% - 6.5%

u u u u u

Stani box 6007 1/2 ✓

deduced the frame space = 620^u_m

van Bulkhead V-136

9.5-7⁴_h

[illegible]

10-7.

Spacing of Stiffs

625 $\frac{1}{2}$ - 760 $\frac{1}{2}$

arranged that
begin he felt in
for hold as complete
steps for reduction
days

610 2m

Two bullheads Shufflers

$$[178 \times 88 \times 11.4 \text{ m}]$$

[203, 88-9, 10, 12.

ing of rivets in Shell Leams ✓

$(4\frac{1}{2})$ dia. Adal. mostly to be fitted in
seams when too wide

14 Dec

Butto ✓

3 - 4 1/2 hrs ✓

3 1/2 Ans. ✓

Heurstrake butt Strafe R

21⁴/₂

257

aths of Prop Bully & 46 Sides R

Single Riv

Double Row

ms of Bricks Lids plating

Single ✓

Double at break

Tests of Steel Wires and Weight of Chain Cable Not reported

© 2020

Lloyd's Register
Foundation
W1265-0024

W1265-0024