

F.E.

by Chief Ship Surveyor

Received from Chief Ship Surveyor

EL'S NAME *Steel S.S. "EIKOKU MARU"*Rpt. *Kbe*No. *3100*

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/22.)

Transverse No. *70.0*Depth "d" *-*Framing: Table No. *-*Description *Longitudinal framing*Longitudinal No. *24150*Proportions  $\frac{\text{Length}}{\text{Depth}} =$ 

*Deck Sheerstrake and other scantlings as approved for vessels built on the longitudinal system*

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed *✱ 100. A-1. (Steel) "Shelter Dk"* with freeboard," as recommended. The Summer freeboard of *4'-10 1/2"* from centre of disc to top of statutory deck line at *Shelter* deck, now marked on the vessel's sides, to be inserted in the classification certificate, and recorded in the Register Book, and further, the remaining freeboards, as shown on the accompanying verification form to be inserted in the certificate of classification.

*1 Dk (Steel) v Shelter Dk (Steel) & Webframes v Longitudinal framing*

*Cell DB 29 1/2' 1120t, ITa 32' 690t, FPT 114t, APT 29t*

*FK, Collision BH to Shelter Dk, 5 BH to upper Dk, pt Cen, pt asp. Av CP*

*P 30', B 99', F 34 on Shelter Dk*

*It is concluded a hand pump is fitted to the fire peaks as in other vessels but the Surveyor should be requested to state if this is so.*

W1283-0257