

Awning or Shelter Deck, STEEL STEAMER.

or Pt. Awning Deck.

No. 2576

State if Report is also sent on the Machinery of the Vessel

Yes

Port of Kobe Date of completion of Report

Received at London Office

Survey held at Osaka Date, First Survey

Last Survey

On the (State if Single, Twin, or Triple Screw)

Steel Ship Sec. Stmr. "Heindan maru" Rig

TONNAGE under

CLASS +100 A1 Awning Dk.

FEET.

Master

Do. between Tonnage Dk. and

Breadth (greatest moulded)

49.83

Year of Appointment

(1) As Master in service of
(2) As Master of this vessel

3rd, 4th, or Awning Dk.

Depth, at middle of length from top of keel to top of

28.17

Total under Upper Dk.

begins at side of uppermost Continuous Deck

20.17

Do. of Poop

Deduct height of 'tween deck when this does not exceed 8ft.

20.17

Do. of R. Qr. Dk.

Transverse Number

40.00

Do. of Forecastle

Length on deck from fore part of stem to after part of

345.00

Do. of Houses on Deck

Longitudinal Number

24150

Do. of excess of Hatchways

Depth "d" at middle of length. See Secs. 2 & 13

12.25

Do. above Crown of

Proportions, Depths to Length, Uppermost Continuous

12.25

age

Deck at side to top of keel

9.54

ace

Destined Voyage

If Surveyed while Building, Afloat, or in Dry Dock

on Rule	Ft.	Ins.	BREADTH	Ft.	Ins.	DEPTH, ACTUAL	Top of Floors to top of Awn. or Shelter Dk. Beams	Ft.	Ins.	No. of Decks with flat laid
345	0		Moulded	49	10	Do.	do.	28	17	2
length	345.0		breadth	49.83		depth	19.17	Upper Deck.	Moulded depth, ft. 19 ins. 2	To Upper Dk.

FRAMING.	Inches in Ship.	Inches in Ship.	Inches in Ship.	Inches per Rule Or as Approved.	Inches per Rule Or as Approved.	PILLARS.	Inches. Size in Ship.	Inches. Spacing in Ship.	Inches. per Rule. Or as Approved.	Inches. per Rule. Or as Approved.
Angles, or \square or \angle Bars, amidships						PILLARS, In 'tween Deck, size and spacing	8-3 1/2-3 1/2-50	8-3 1/2-3 1/2-60		
Peaks						" " Hold	7-3 1/2-3 1/2-40	6-3 1/2-3 1/2-40		
Way of Double Bottoms at Solid Floors						" Quarter, 'tween Dks.,	14-60 10-50	Spaces 22 ft		
" at intermdt. Bkts.						" in Hold	12-54 10-44	as approved		
Frames from centre to centre amidships						KEELSONS AND STRINGERS.				
Length to collision bulkhead						CENTRE LINE KEELSON, Vertical Plate above				
Frames from centre to centre in peaks						" floors, Through Plate, or Intercoastal Plate				
ED FRAME, Angles						" Rider Plate				
Way of Double bottoms at Solid Floors						" Flat Keel Plate Angles				
" at intermdt. Bkts.						" Horizontal Plates on Floors				
G, depth of girder						" Angles or Bulb Angles				
depth and thickness of Floor Plate						SIDE KEELSONS, Number				
mid-line for 1/2 length amidships						" Angles or Bulb Angles				
Way of Engine and Boiler spaces						" Plate above floors, for	length			
Thickness at the ends of vessel						" Intercoastal Plate, for	length			
Depth at 1/2 the half-bdth. as per Rule						" Attached to outside plating with Angle				
Height extended at the Bilges						BILGE KEELSON, Angles				
in Cell Double Bottoms	50 in BS	40-34	40-34			" Intercoastal Plate, for	length			
state if flanged (top and bottom)	No	No	No			" Attached to outside plating with Angle				
spacing of Solid	5 ft. 5 1/2 ft. 6 ft.	36 58 40 54 24				SIDE STRINGERS, Number				
GIRDER, in Dbl. bottom, dpth. & thknss	40	48-38	40	48-38		" Angle				
" Angles, Top	3 1/2	3 1/2 46	3 1/2	3 1/2 46		" Intercoastal Plate, for	lng.			
" Bottom	4	4 58	4	4 58		" Attached to outside plating with Angle				
" to Floors	5	5 44	5	5 44		Awning or Shelter Deck Stringer Plates,				
Brackets at intermdt. frmg., width & thknss						" breadth and thickness	52-32 56-40	52-32 56-40		
ORDERS, number and thickness	One	36-34	One	36-34		" Angle on ditto	5-5-60	5-5-60		
" state if flanged (top & bottom)	No	No	No			" Tie Plates, fore and aft, outside Hatchways	3 1/2-3 1/2 44	3 1/2-3 1/2 44		
Angles	3 1/2	3 1/2 36	3 1/2	3 1/2 36		" Deck * Iron or Steel, for	whole lng.	34 +	34 +	
PLATE, depth (exclusive of flange)	Level top	42	42			" Wood Deck. Material & thickness				
and thickness	3 1/2	3 1/2 42	3 1/2	3 1/2 42		Upper Deck Stringer Plate, breadth and	4 dec	34	34	
Angles to outside plating	3 1/2	3 1/2 42	3 1/2	3 1/2 42		" thickness	3 1/2-3 1/2 40	3 1/2-3 1/2 40		
" to floors	6	3 1/2 44	6	3 1/2 44		" Angles on ditto, No.	1			
Brackets at intermdt. frmg., width & thknss	36	40 36	40			" Tie Plates, outside Hatchways				
Height of Brackets above at bilge						" Deck * Iron or Steel, for	whole lng.	34	34	
BOTTOM PLATING, breadth and	40	46-38	40	46-38		" Wood Deck. Material & thickness				
thickness of Middle Line Strake	E 46	B 54	E 46	B 54		Second Deck Stringer Plates, br'dth & thkn's				
" thickness in Engine and Boiler space	38-34	38-34				" Angles on ditto, No.				
" Remainder in Holds						" Tie Plates, outside Hatchways				
Awng or Shltr Dk, Single Angle,						" Deck * Material and thickness				
Bulb Angle, Plate, Tee Bulb or Channel						Third, Fourth & Fifth Deck Stringer Plate,				
ing						" breadth and thickness				
Upper Deck, Single Angle, Bulb Angle,						" Angles on ditto, No.				
Plate, Tee Bulb or Channel						" Tie Plates, outside Hatchways				
ing						" Deck. Material and thickness				
Second, Third & Fourth Deck, Single						Poop Deck Stringer Plate, breadth & thickness	9 dec	30	30	
le, Bulb Angle, Plate, Tee Bulb or Channel						" Angles on ditto	3-3-32	3-3-32		
" Angles on upper edge						" Tie Plates	30	30		
" Spacing						" Deck. Material and thickness				
BEAMS, Poop Deck, Angle, Bulb Angle, Plate,						Bridge Deck Stringer Plate, br'dth & thickness	46	50	46	50
" Tee Bulb or Channel						" Angle on ditto	5-5	54	5-5	54
" Angles on upper edge						" Tie Plates	30	30		
" Spacing						" Deck. Material and thickness				
BEAMS, Bridge Deck, Angle, Bulb Angle, Plate,						Forecastle Deck Stringer Plate, br'dth & th'kns	32	32	32	32
" Tee Bulb or Channel						" Angle on ditto	3-3	32	3-3	32
" Angles on upper edge						" Tie Plates	24	24		
" Spacing						" Deck. Material and thickness	2 1/2 O.P.	2 1/2 O.P.		

Date of writing
 No. in
 Reg. Book
 Master
 Engines
 Boilers
 Registers
 Nom. Horse Power
 ENGINE
 Dia. of
 Is the sc
 in the p
 between
 liners and
 Dia. of T
 collars
 No. of
 No. of
 No. of
 In Eng
 No. of B
 Are all t
 Are all
 Are they
 Are they
 What p
 Are all
 Are the
 Is the
 BOILER
 Total I
 Worki
 Can ea
 each bo
 Smaller
 Thickne
 long. s
 Per cen
 Size of
 Length
 Worki
 Pitch
 Mater
 Mater
 Area
 Thickn
 Diamo
 Pitch
 thickne
 Work
 Diamo
 Pitch
 SUPP
 Date
 Dis

2