

Received by Chief Ship Surveyor

Received from Chief Ship Surveyor

VESSEL'S NAME STEEL S.S. "HEIJIN MARU" Rpt. Kobe No. 2416

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92.)

Transverse No. 70 Depth "d" 15.16

Framing: Table No. - Description Longitudinal Framing

Longitudinal No. 24150

Proportions $\frac{\text{Length}}{\text{Depth}} =$ 9.54

Bridge Deck Sheerstrake as approved

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed 100 A.1. (Steel) Shelter Deck with freeboard, as recommended. The Summer freeboard of 4'-10 1/2" from centre of disc to top of statutory deck line at Shelter deck, now marked on the vessel's sides, to be inserted in the classification certificate, and recorded in the Register Book, and further, the remaining freeboards, as shown on the accompanying verification form to be inserted in the certificate of classification.

1 Dk (Steel) & Shelter Dk (Steel) & Webframes. Longitudinal Framing.

Cell DB 294' 10975. DT 2 32' 690t. FPT 115t. APT 29t.

FK. 1 BH to Shelter Dk. 5 BH to upper dk. Cons. A. & C.P.

P 30', B 38', F 34' on Shelter Dk 10-7-10

W1503-0025

Lloyd's Register Foundation

Angles on
Spacing
BEAMS, Forecast