

No. 15098.

State if Report is also sent on the Machinery of the Vessel Yes: Gls.

Received at London Office.....TUES 11 JUN 1907

Date of completion of Report 1ST JUNE 1907

Port of GREENOCK

Date, First Survey 8th January 1907 Last Survey 31st MAY

194

AYESTRUZ" (YARD N° 284)

Rig ONE MAST.

Survey held at GREENOCK
On the STEEL SCREW TURN

ONE ~~OR TWO~~ DECKED VESSEL.

Master H. B. KEARNEY

Year of appointment	{	(1) As master in service of	
		owner of present vessel:—	190
		(2) As master of this	
		vessel	190

Built at GREENOCK

When built 1907 Launched 3rd May 1907.

By whom built GRANGEMOUTH & GREENOCK DOCKYARD C=

Owners COMPANIA PASTORIL Y COMERCIAL HARTENECK LTD.

Managers HARTENECK & CO

Residence BUENOS AYRES.

Port belonging to BUENOS AYRES.

BUILT UNDER
SPECIAL SURVEY

Destined Voyage BUENOS AYRES

If Surveyed while Building, Afloat, or in Dry Dock SPECIAL SURVEY.

LENGTH on Deck as per Rule.....		Feet. 99	Inches. 2	BREADTH — Moulded.....	Feet. 22	Inches. 11	DEPTH, ACTUAL — Top of Floors to top of Main Deck Beams	Feet. 10	Inches. 5½	No. of Decks with Flat laid No. of Tiers of Beams	ONE ONE
Dimensions of Ship per Register. Length, 100' breadth, 23'1" depth, 10'5" . Moulded Depth, 11 ft. 0 ins. Round of Beam, Actual 5¾ ins.											

FRAMING.							FORGINGS AND CASTINGS.									
							Inches in Ship.									
							Inches per Rule Or as Approved.									
FRAME, Angles, L, E or L Bars, for 3/8 length amidships							3	2 1/2	7	3	2 1/2	7	KEEL, Bar or Side Plates depth and thickness		FLAT PLATE	KEEL
Do. for 1/2 at each end							3	2 1/2	6	3	2 1/2	6	STEM, moulding and thickness		5 x 1	5 x 1
Do. in way of Double Bottoms at Solid Floors ..													STERN-POST for Rudder do. do.		5 1/4 x 2 1/4	5 x 2 1/4
Do. in way of Double Bottoms at Solid Floors ..													" for Propeller		5 1/4 x 2 1/4	5 x 2 1/4
Spacing of Frames from centre to centre							2 1/2	2 1/2	5	2	2	5	MAIN PIECE of Rudder, diameter at head ...		3 3/4	3 3/4
REVERSED FRAME, Angles							2 1/2	2 1/2	5	2	2	5	do. at heel		3	3
DEEP FRAMING, depth of girder													RUDDER, how constructed FORGED IRON FRAME AND SINGLE PLATE			
FLOORS, depth and thickness of Floor Plate } at mid-line for 3/8 length amidships }							12		5	12		5	Can the Rudder be unshipped afloat? YES.			
" in way of Engines and Boilers							E=3/8 STEEL; B=1/2 STEEL.			3/8		1/2 STEEL.	KEELSONS AND STRINGERS.			
" thickness at the ends of vessel							5						CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercoastal Plate			
" depth at 3/8 the half breadth, as per Rule ..							STRAIGHT ON TOP.						" Rider Plate			
" height extended at the Bilges													" Bulb Plate to Intercoastal Keelson			
FLOORS & BRACKETS, in Cell Dble Bottoms													" Horizontal Plates on Floors (DOUBLE) ..			
" state if flanged (top & bottom)													" Angles TAP & BOT. TOP			
" Spacing													SIDE KEELSON, Angles			
CENTRE GIRDER, in Double Bottom, depth and thickness													" Bulb or Plate above floors for - lng.			
" Angles, Top													" Intercoastal Plate for - length			
" Bottom													" Attached to outside plating with Angle ..			
SIDE GIRDERS, number on each side & thickness													BILGE KEELSON, Angles			
" state if flanged (top & bottom)													" Bulb or Plate above floors for - lng.			
" Angles													" Intercoastal Plate for - length			
MARGIN PLATE, depth (exclusive of flange) and thickness													" Attached to outside plating with Angle ..			
" Angles to Outside Plating													BILGE STRINGER Angles			
" Floors													" Bulb Plate for - length			
" Height of Floors at the Bilges													" Intercoastal Plate for - length			
INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake													" Attached to outside plating with Angle			
" thickness in Engine and Boiler space													SIDE STRINGER Angles			
" Remainder in Hold													" Bulb or Intercoastal Plate for - lng.			
BEAMS, Main and Raised Quarter Deck, Single Angle, Bulb Angle, Plate or Tee Bulb							3	2 1/2	7	3	2 1/2	7	" Attached to outside plating with Angle			
" Angles on Upper Edge													Main and Raised Quarter Deck Stringer Plate, breadth and thickness			
" Spacing							21			21			" Angle on ditto			
BEAMS, Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb													" Tie Plates, outside Hatchways			
" Angles on Upper Edge													" Diagonal Tie Plates on Bms., No. of Pairs ..			
" Spacing													" Main Dk* Iron or Steel for FULL lng.			
BEAMS, Hold, Plate or Tee Bulb													" R. Q. Dk* Iron or Steel for - lng.			
" Angles on Upper Edge													" Wood Deck, Material & thickness			
" Spacing													Lower Deck Stringer Plate, breadth and thickness			
BEAMS, Poop Deck, Angle, Bulb Angle, Plate or Tee Bulb													" Angles on ditto, No.			
" Angles on Upper Edge													" Tie Plates, outside Hatchways			
" Spacing													" Deck* Material and thickness			
BEAMS, Bridge or Pt. Awng. Deck, Angle, Bulb Angle, Plate or Tee Bulb ... }													Hold Stringer Plate			
" Angles on Upper Edge													" Angles on ditto, No.			
" Spacing													Poop Deck Stringer Plate, breadth & thickness ..			
BEAMS, Forecastle Deck, Angle, Bulb Angle, Plate or Tee Bulb													" Angle on ditto			
" Angles on Upper Edge													" Tie Plates			
" Spacing													" Deck, Material and thickness			
PILLARS, In tween Decks, Size and Spacing													Bridge or Pt. Awng. Deck Stringer Plate, breadth and thickness			
" Hold " " " "							2 5/8	DIA R,	42" APART.	2 5/8,		42"	" Angle on ditto			
" Quarter, tween Dks., " " "													" Tie Plates			
" in Hold " " " "													" Deck, Material and thickness			
WEB FRAMES, In Fore Body, No. and Spacing													* If Iron or Steel Deck, state if whole or part, and if wood deck is laid thereon.			
" Brdth. & Thickness													BULKHEADS.			
" No. of Side Stringers													Number.			
WEB FRAMES, In E. & B. Space, No. & Spacing													In Vessel.			
" Brdth. & Thickness													Per Rule.			
WEB FRAMES, In After Body, No. and Spacing													Thickness.			
" Brdth. & Thickness													10ths or 20ths.			
" No. of Side Stringers													STIFFENERS.			
" Size of Angles or Tee Bars to Web Frames													Horizontal.			
BRACKET PLATES to Stringers between Web Frames, Depth and Thickness													Vertical.			
													Single or Double Frames.			
													Height up.			
													Size.			
													Spacing.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			
													Inches.			

