

Do. of excess of Hatchways  
Do. above Crown of

23.99  
54.17

Length on deck from fore part of stem to after part of sternpost

385.00

By whom built

5c,7,16.

33270 8p-

F.E.

Received by Chief Ship Surveyor

Received from Chief Ship Surveyor

VESSEL'S NAME STEEL S.S. "PORT SAID MARU" Rpt. Kobe No. 2589

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92.)

Transverse No. 79 Depth "d" 16'0"

Framing: Table No. 3 page 14 Description Bulb angle as approved

Longitudinal No. 30415

Proportions  $\frac{\text{Length}}{\text{Depth}} =$  10.7

Awwing

Deck Sheerstrake as approved

RETAIN

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed 100 A.1. (steel) "Awwing Dk with freeboard," as recommended. The Summer freeboard of 9-3½" from centre of disc to top of statutory deck line at Awwing deck, now marked on the vessel's sides, to be inserted in the classification certificate, and recorded in the Register Book, and further, the remaining freeboards, as shown on the accompanying verification form to be inserted in the certificate of classification.

2 Dks (steel) and Awwing Dk (steel)

Cell DB 334' 1118t. FPT 126t. APT 93t.

FK. Collision BH to Awwing Dk. 5 BH to Upper Dk.

© 2021

Lloyd's Register Foundation

BE...  
Angle, Bulb Angle, Plate, Tee Bulb or Channel  
Angles on upper edge

10	3.58	5.75	6.11	32	56
----	------	------	------	----	----

Deck, Material and thickness  
Poop Deck Stringer Plate, breadth & thickness

W1308-0176

14