

Morning or. Venre

in JUN. 2-1919 Index No.  
(For London Office only.)

# Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS. *Run 108  
Rpt No. 2478*

TICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

*wasan Dryd. No #3436*

Port of Survey *None*  
Date of Survey *March 1919*  
Name of Surveyor *A. H. Jones*

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
<i>Washington Maru</i>	<i>Nobe Japanese</i>	<i>24749</i>	<i>5863</i>	<i>1919-3</i>	<i>+100 A1. Morning or recommended.</i>

Length.	Breadth.	Depth.	Under Deck Tonnage.
<i>385.0</i>	<i>51.0</i>	<i>25.6</i>	<i>1200</i>
<i>384.6</i>	<i>51.0</i>	<i>25.6</i>	<i>1200</i>
<i>384.6</i>	<i>50.5</i>	<i>26.68</i>	<i>42.00</i>

Efficient of fineness ..... *.81*  
modification necessary } *.02 A.B.*  
Para. 4 (a) to (e)\* }  
Efficient as corrected ..... *.79*

Stem ..... <i>110</i>	$\{ 160 \div 2 = 80$	Mean
Sternpost <i>10</i>		
at $\frac{1}{8}$ of the length from Stem <i>61</i>	$\{ 88 \div 2 = 44$	Mean
Sternpost <i>24</i>		
usual mean Sheer ..... <i>80</i>	<i>18\frac{1}{2}</i>	Correction
standard mean Sheer [Table, Para. 18] ..... <i>18\frac{1}{2}</i>		
Difference ..... <i>31\frac{1}{2} \div 4 = 7\frac{1}{8}</i>		
limited as Para. 18 (f) ..... <i>7\frac{1}{8}</i>		

sheer in Sheer { At front of bridge house	
amidships { At after end of forecastle	

fall in Sheer {	$\div 2 =$	
Para. 18 (d)		✓ Correction

allowance for Deck Erections:— *None*

board, Table C.....  
ection for Length, if required (Para. 12, 13, and 14) .....

oard by Table A. corrected for sheer, and for length, if required (Para. 12, 13, and 14) .....

ence .....  
ntage as below.....

ction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11) .....

ance for Deck Erections .....

Length.	Length allowed.	Height.
House .....		
ed Qr. Dk.....		
Total .....		
of Ship .....		
onding percentage {		
11, 12, 13, or 14) }		

BOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Iron) Deck:—

Fresh Water Line	above centre of Disc	...	...	...
Indian Summer Line	" "	"	"	"
Winter Line	below "	"	"	"
Winter North Atlantic Line	" "	"	"	"

frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside ceiling should be reported if possible. In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam. In decked vessels the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant eighth of the vessel's length from stem and stern-post.

Port of Survey *None*  
Date of Survey *March 1919*  
Name of Surveyor *A. H. Jones*

Moulded Depth as measured *28' 0"*  
*36' 0"*  
Addition for Keel below base line for draught record.....inches.

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

#### CORRECTION FOR LENGTH.

Length of Ship on Loadline .....	<i>384.6</i>		
Length in Table .....	<i>336.0</i>		
Difference .....	<i>48.6</i>		
Correction for 10ft., Table A. ....	<i>1.1</i>	Table C. ....	<i>.4</i>
× Difference divided by 10 .....	<i>6.8</i>	(if required.)	<i>3.1</i>
If $\frac{6}{10}$ ths length covered divide by 2	<i>3.4</i>		

#### CORRECTION FOR IRON DECK.

Proportion covered, if less than $\frac{7}{10}$ ths length covered .....	
Thickness of usual wood deck, less stringer .....	<i>- 3\frac{1}{2}</i>

#### CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships .....	<i>50</i>	NOTE.—The round of beam should be reported on the full breadth of vessel at the gunwale.
Round of Beam .....	<i>12\frac{3}{4}</i>	
Normal round .....	<i>12\frac{1}{2}</i>	
Difference, .....	<i>\frac{1}{4}</i> $\div 2 =$ .....	
Proportion of Deck uncovered (Para. 19) .....		

Freeboard, Table A .....	<i>3' 8\frac{1}{4}"</i>
Correction for Sheer .....	<i>- 4\frac{3}{4}</i>

Correction for Length .....

Allowance for Deck Erections .....

Correction for Round of Beam .....

Correction for fall in Sheer (if any) .....

Correction for Iron Deck (if required) .....

Additions for non-compliance with provisions of

Para. 11 (d) and (e) *additional Strength = 4\frac{1}{2}*

Other Corrections (if any) .....

*Height between decks 8' 0"*

Winter Freeboard .....	<i>9' 8\frac{1}{4}"</i>
Summer Freeboard .....	<i>9' 1\frac{3}{4}"</i>
Indian Summer Freeboard .....	<i>8' 7\frac{1}{4}"</i>
N. A. Winter Freeboard .....	

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or iron deck with side.

Winter Freeboard from deck line .....

Summer " " " " .....


Indian Summer " " " " .....

N. A. Winter " " " " .....

*9' 10"*  
*9' 3\frac{1}{2}"*  
*8' 9"*  
*9' - 3\frac{1}{2}"*  
*7\frac{1}{2}"*  
*6\frac{1}{2}"*  
*6\frac{1}{2}"*

State dimensions of freeing port area on back of this form.

The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.



© 2021

Lloyd's Register  
Foundation

Do all the Frames extend to the top height in the Poop? ..... Raised Quarter Deck? ..... Bridge House? ..... Forecastle? .....  
 To what height do the Reverse Frames extend? Main B.A. from to 2<sup>nd</sup> up. dks. altern + intermed. from to awning deck  
 Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? .....  
 Give particulars of the means for closing the openings in Bulkhead .....  
 Is the Poop or Raised Quarter Deck connected with the Bridge House? ..... Has the Bridge House an efficient Bulkhead at the fore end? .....  
 Give particulars of the means for closing the openings in Bulkhead .....  
 What is the thickness of the Bridge Front plating? ..... and Coaming plate? .....  
 Give scantlings and spacing of the Stiffeners .....  
 Are bracket plates fitted at each end of the Stiffeners? ..... Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? .....  
 Has the Bridge House an efficient Iron Bulkhead at the after end? .....  
 How are the openings closed? .....  
 Is the Forecastle at least as high as the main or top-gallant rail? ..... Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? .....  
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? *Steel deck house*  
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed? .....  
 Give thickness of plating; scantlings and spacing of Stiffeners .....  
 What is the height of the exposed Casings? ..... Are suitable means provided for closing all openings in them in bad weather? .....  
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:—

Position and Size.		No 1. 27' 7 1/2" x 18' 0"	No 2. 31' 10 1/2" x 18' 0"	No 3. 12' 9" x 16' 0"	No 4. 31' 10 1/2" x 18' 0"	No 5. 24' 7 1/2"			
Item.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.
COLUMNS	2 1	2 1							
Thickness { Sides	.4 1	.4 1	Same as No 1.	Same as No 1	Same as No 1	Same as No 1	Same as No 1	Same as No 1	Same as No 1
Thickness { Ends	.1 1	.4 1							
SHIFING BEAMS OR WEB PLATES	5	5	6	6	2	2	6	6	5
Number { Section and Scantlings	18" x 36	14" x 34			16" x 32	12" x 32			
Material	2A. 4x3x4d	4x3x4d	Same as No 1.	Same as No 1.	2A. 32.32.42	32.32.42	Same as No 1.	Same as No 1.	Same as No 1.
* FOK AND ASTERS	✓	✓	✓	✓	✓	✓	✓	✓	✓
HATCHES	3"	3"	3"	3"	3"	3"	3"	3"	3"
Thickness	Horizontal B.A. stiffeners fitted to side-end coamings as approved.								
Remarks									

\* The depth of Fore-and Afters should be stated from the underside of the hatches in all cases.

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rule

What is the thickness of the Bridge Sheerstrake?

Strake between Main and Bridge Sheerstrakes?

Delete the words { The Crew are, are not, berthed in the bridge house.  
that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.

Length of Bulwarks in well

Area of Freeing Ports required by Para. 11 (e) each side of vessel =


Sq. ft.

Ft. Tenth. Ft. Tenth. No.

×	×		Freeing Ports (each side of vessel)	=	Sq. ft.
×	×				

Total deficiency or excess =

Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel. The First entry Report is now forwarded.  
The Freeboard recommended + which has been marked is as assigned  
the sister vessel "Argonne" (Kobe Report No. 1921) London letter 18<sup>th</sup> Feby. 1916.  
Owners The Kawasaki Dockyard Co. Ltd. A Verification Rpt form is en

, Address Kobe

Fee £ per ton 140/-

Received by me March 28 1919

M.L.

Lloyd's Register Foundation