

Lloyd's Register of Shipping.
SURVEYS FOR FREEBOARD.—STEAM SHIPS.

Index No.
(For London Office only.)

ARTICLES RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH
ANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR
GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS
CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey
Date of Survey
Name of Surveyor

Table with 6 columns: Ship's Name, Port of Registry and Nationality, Official Number, Gross Tonnage, Date of Build, Particulars of Classification.

Table with 4 columns: LENGTH, BREADTH, DEPTH, UNDER DECK TONNAGE. Includes sub-headers for Frame Depth, Ceiling, Peak, Rule, Sheer, Tanks.

Moulded Depth as measured
Addition for Keel below base line for draught record

NOTE.— If the depth is measured when vessel is afloat, the details of measurement should be reported.

CORRECTION FOR LENGTH.

Length of Ship on Loadline
Length in Table
Difference
Correction for 10ft., Table A.
x Difference divided by 10
If 1/10ths length covered divide by 2

CORRECTION FOR IRON DECK.

Proportion covered, if less than 1/10ths length covered
Thickness of usual wood deck, less stringer

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships
Round of Beam
Normal round
Difference
Proportion of Deck uncovered (Para. 19)

NOTE.— The round of beam should be reported on the full breadth of vessel at the gunwale.

ALLOWANCE FOR DECK ERECTIONS:—

Length, if required (Para. 12, 13, and 14)

Table A. corrected for sheer, and for length

below

for R. Q. Dk. if engine and boiler openings not
by bridge house (Para. 11)
for Deck Erections

Length. Length allowed. Height.

Dk.
ip

percentage
(12, 13, or 14)

RD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Steel) Deck:—

Fresh Water Line
Indian Summer Line
Winter Line
Winter North Atlantic Line

skin planking, or ceiling are of unusual thickness the breadth of vessel to inside
should be reported if possible.

+ State dimensions of freeing port area on back of this form.
The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line.

© 2021

Lloyd's Register Foundation