

F.E.

ved by Chief Ship Surveyor 20.4.15

Received from Chief Ship Surveyor

SEL'S NAME Steel Liner S.S. "Harbin Maru" Rpt. Kobe No. 1601

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report. 24/5/92.)

Transverse No. 72Depth "d" 18.58Framing: Table No. 3 page 10Description Butt AngleLongitudinal No. 28800Proportions $\frac{\text{Length}}{\text{Depth}} = \frac{10.5}{1}$ Deck Sheerstrake as approved.


This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed * 100A.1 (Steel) "Shelter Deck" with freeboard," as recommended. The Summer freeboard of 6.32 from centre of disc to top of statutory deck line at Shelter deck, now marked on the vessel's sides, to be inserted in the classification certificate, and recorded in the Register Book, and further, the remaining freeboards, as shown on the accompanying verification form to be inserted in the certificate of classification.

* 100A.1 (Steel) "Shelter Deck with freeboard."

100A.1 (Steel) * Shelter Deck (steel w.s.) + 2" Deck (steel) in last hold

WB = Cell DB a 102 a E + B 61 f 174 686 C. FRT 52 C APT 50 C

FK. 6BH. Can Regd axes B 170 F 47 a Shelter Deck

Date of Build 1.15.

© 2021

Lloyd's Register Foundation

W1322-0069/12

P.T.O.

The Surveyor should be requested to state the size
& spacing of the 2nd deck beams in No 1 Hold, as this has been
omitted from the report, and informed it is concluded the shelter
deck sheerstrake has been doubled at the ends of the Bridge,
that the forecastle deck is wood sheathed & that the
boat deck beams are $6 \times 3\frac{1}{2} \times 40$ as shown in the
midship section & that the bridge & boat decks are
also wood sheathed, & the hull of the shelter deck stiffer for $\frac{1}{2}$ ft
amidships & fore of Bridge are symmetrically riveted.
He should also be requested in future cases
to amend the appended pages & agree with
the report & vessel as built - W.
see

M
20. 4. 15



© 2021

Lloyd's Register
Foundation

0069 12