SIR JAMES CLARK. ROSS

3 Decks. ~~IRON OR~~ STEEL STEAMER.

Received at London Office THUR. 10 AUG 1905

State if Report is also sent on the Machinery of the Vessel Yes

Date of completion of report ..... *Port of* ..... No. 5941

Survey held at Belfast. *Date, First Survey* 18th. October. 1904 *Last Survey* August 3rd. 1905

On the S.S. Mahronda. *Rig* Schooner

TONNAGE under Tonnage Deck 7318.12
Do. between Tonnage Dk. and 3rd and 4th Dk.
Total under Upper Dk.
Do. of Poop 143.23
Do. of Bridge House Round 38.71
Do. of Forecastle
Do. of Houses on Dk. Side 107.85
Do. of excess of Hatchways 28.02
Do. above Crown of Engine Room
Gross Tonnage 7629.93
Less Crew Space 184.57
Less above Crown of Engine Room
TONNAGE FOR FEES 7448.36
Less Engine Room 2441.58
Less Navigation Spaces 85.35
Register Tonnage *as cut on Beam* 4921.43

THREE DECKED VESSEL.

CLASS 100 A.1.

	FEET.
Half Breadth (moulded)	29.00
Depth from upper part of Keel to top of Upper Deck Beams (with the normal round up of beam)	36.61
Girth of Half Midship Frame (as per Rule)	60.91
	126.52
deduct 7 feet	7.00
1st Number	119.52
Length on deck from after part of stem to fore part of stern post	468
2nd Number	559.35
Proportions—Breadth to Length	8.06
Depth to Length—Upper Deck to top of Keel	12.85
Main Deck ditto	

Destined Voyage Calcutta

Master R. Bannatyne
Year of appointment (1) As Master in service of owner of present vessel:—18 (2) As Master of this vessel 18
Built at Belfast
When built 1905 *Launched* 17th June 1905
By whom built Harland & Wolff Ld.
Owners T. & J. Brocklebank. Ld.
Managers (Where necessary to be entered in Reg. Book.)
Residence
Port belonging to Liverpool.

If Surveyed while Building, Afloat, ~~or in Dry Dock~~ Yes.

	Feet.	Inches.		Feet.	Inches.		Feet.	Inches.	
LENGTH on Deck as per Rule	468	0	**BREADTH**—Moulded	58	0	**DEPTH, ACTUAL**—Top of Floors to top of Upper Dk. Beams	31	5	No. of Decks with flat laid Two.
						Do. do. do. do. Main Dk. Beams	19	11	No. of Tiers of Beams Two.

Dimensions of Ship per Register, Length 470.3 breadth 58.4 depth 31.38. Moulded depth, ft. 35 ins. 5 To Upper Dk. Round of Upper Dk. Beam, Actual 12 ins.

FRAMING.

	Inches in Ship	Inches in Ship.	16ths or 20ths in Ship.	Inches per Rule Or as	Inches per Rule as Approved	16ths or 20ths per Rule ved.
FRAME, ~~Angles or~~ ⌐, [or ⌐ Bars for ¾ length amidships	11×3½×3½		×12	11×3½×3½		×12
Do. for ¼ at each end Angles	7	3½	11	7	3½	11
Do. in way of Double Bottoms at Solid Floors	3½	3½	10	3½	3½	10
,, ,, at intermdt. Bkts.						
Distance of Frames from moulding edge to moulding edge, all fore and aft	26			26		
REVERSED FRAME, Angles	7	3½	11	7	3½	11
	11			11		
DEEP FRAMING, depth of girder						
FLOORS, depth and thickness of Floor Plate at mid-line for ¾ length amidships						
,, in way of Engines and Boilers						
,, thickness at the ends of vessel						
,, depth at ¾ the half breadth, as per Rule						
,, height extended at the Bilges						
BRACKETS in **Cell Dble Bottoms**	Flanged		10			10
,, ,, Distance apart	26			26		
CENTRE GIRDER, in Double bottom, depth and thickness	60		11	60		11
,, ,, Angles, Top	4	4	10	4	4	10
,, ,, ,, Bottom	4½	4½	13	4½	4½	13
SIDE GIRDERS, number on each side & thickness 2	Flanged		10	2		10
,, ,, Angles	3½	3½	10	3½	3½	10
MARGIN PLATE, depth (exclusive of flange) and thickness	52½		11	52½		11
,, ,, Angles to Outside Plating	4	4	11	4	4	11
INNER BOTTOM PLATING, breadth and thickness of **Middle Line Strake**	42		11	42		11
,, ,, ,, in Engine and Boiler space			11 & 12			11-12
,, ,, ,, Remainder in Holds			9			9
BEAMS, Upper Deck, ~~Single Angle, Bulb Angle, Plate or Tee Bulb~~ Channel	10×3½×3½		13	10×3½×3½		13
,, Angles on upper edge						
,, Average space	52			52		
BEAMS, Middle Deck, ~~Single Angle, Bulb Angle, Plate or Tee Bulb~~ Channel	12×3½×3½		15	12×3½×3½		15
,, Angles on upper edge						
,, Average space	52			52		
BEAMS, Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb						
,, Angles on upper edge						
,, Average space						
BEAMS, Hold, or Orlop, Plate or Tee Bulb						
,, Angles on upper edge						
,, Average space						
BEAMS, Poop Deck, ~~Angle, Bulb Angle, Plate or Tee Bulb~~ Channel	8×3×3×11			8×3×3×11		
,, Angles on upper edge						
,, Average space	52			52		
BEAMS, Bridge Deck, ~~Angle, Bulb Angle, Plate or Tee Bulb~~ Channel	9×3½×3½		12	9×3½×3½		12
,, Angles on upper edge						
,, Average space	52			52		
BEAMS, Forecastle Deck, ~~Angle, Bulb Angle, Plate or Tee Bulb~~	9×3½×3½		12	9×3½×3½		12
,, Angles on upper edge						
,, Average space	52			52		
PILLARS, In 'tween Deck, size and spacing	3"	52"		3"	52"	
,, ,, **Hold** ,, ,,	4½	52		4½	52	
,, **Quarter 'tween Dks.,** ,, ,,	3	52		3	52	
,, ,, **in Hold** ,, ,,	4½	52		4½	52	
WEB-FRAMES, In Fore Body, No. and spacing						
,, ,, ,, brdth. & thickness						
,, No. of Side Stringers ,, ,,						
WEB-FRAMES, In E. & B. Space, No. & spacing	2 as per Rule			2 As per Rule		
,, ,, ,, brdth. & thickness	24		12	24		12
WEB-FRAMES, In After Body, No. and spacing						
,, ,, ,, brdth. & thickness						
,, No. of Side Stringers ,, ,,						
,, Size of Angles or Tee-Bars to **Web-Frames**						
BRACKET PLATES to Stringers between Web Frames, depth and thickness						

FORGINGS or CASTINGS.

	Inches in Ship.	Inches per Rule. Or as Approved.
KEEL, Bar ~~or Side Plates~~, depth and thickness	3×10	3×10
STEM, moulding and thickness	12×3½	12×3½
STERN-POST for Rudder do. do.	13×8½	13×8½
,, for Propeller	13×8½	13×8½
MAIN PIECE of **Rudder,** diameter at head	11	10½
,, ,, do. at heel	8¼×7	

RUDDER, how constructed Single plate
Can the Rudder be unshipped afloat? Yes.

KEELSONS & STRINGERS.

	Inches in Ship.	Inches in Ship.	20ths in Ship.	Inches per Rule Or as	Inches per Rule as Approved	20ths per Rule ved.
CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercostal Plate						
,, Rider Plate						
,, Bulb Plate to Intercostal Keelson						
,, Horizontal Plates on Floors						
,, Angles						
SIDE KEELSON, Angles						
,, Bulb or Plate above floors, for lng.						
,, Intercostal Plate, for length						
,, Attached to outside Plating with Angle						
BILGE KEELSON, Angles						
,, Bulb or Plate above floors, for lng.						
,, Intercostal Plate for length						
,, Attached to outside Plating with Angle						
~~Bilge~~ **STRINGER** Angles between Dks.	6½	4½	10	6½	4½	10
,, Bulb Plate for length						
,, Intercostal Plate for full length			10			10
,, Attached to outside Plating with Angle	3½	3½	10	3½	3½	10
SIDE STRINGERS Angles	6½	4½	15	6½	4½	15
,, ~~Bulb or~~ Intercostal Plate, for full lng.			10			10
,, Attached to outside plating with Angle	3½	3½	10	3½	3½	10
Upper Deck Stringer Plates, br'dth & thickness	75		15	75		15
,, Angle on ditto	6×6		15	6×6		15
,, Tie Plates fore and aft, outside Hatchways						
,, Deck.* ~~Iron or~~ Steel, for full lng.			9·8			9·8
,, Wood Deck. Material & thickness						
Middle Deck Stringer Plate, br'dth & thickness	75		11	75		11
,, Angles on ditto, No. 2	4×4		9	4×4		9
,, Tie Plates outside Hatchways						
,, Diagonal Tie Plates on Bms., No. of prs.						
,, Deck.* ~~Iron or~~ Steel, for full lng.			9·8			9
,, Wood Deck. Material & thickness						
Lower Deck Stringer Plate, br'dth & thickness						
,, Angles on ditto, No.						
,, Tie Plates, outside Hatchways						
,, Deck.* Material and thickness						
Hold, or Orlop Stringer Plate, br'dth & thckn's						
,, Angles on ditto, No.						
,, Tie Plates outside Hatchways						
,, Deck. Material and thickness						
Poop Deck Stringer Plate, breadth & thickness	40		7	40		7
,, Angle on ditto	3×3		8	3×3		8
,, Tie Plates	21		8	21		8
,, Deck. Material and thickness Y.P.	6×3½			6×3½		
Bridge Deck Stringer Plate, br'dth & thickness	45		10	45		10
,, Angle on ditto	3½×3½		8	3½×3½		8
,, Tie Plates	21		8	21		8
,, Deck. Material and thickness Y.P.	6×3½			6×3½		
Forecastle Deck Stringer Plate, b'dth & th'kns	36		8	36		8
,, Angle on ditto	3½×3		8	3½×3		8
,, Tie Plates						
,, Deck. Material and thickness R.P.	6×3½		8	Steel		8

* *If Iron or Steel Deck, state if whole or part, and if Wood Deck is laid thereon.*

BULKHEADS.

	Number. In Vessel.	Number. Per Rule.	Thickness. 16ths or 20ths.	STIFFENERS. Horizontal. Size. Inches.	Horizontal. Spacing Inches.	Vertical. Size. Inches.	Vertical. Spacing Inches.	Single or Double Frames.	Height up.
W. T. BULKHEADS	7	7	8-7	8×3½×3½		14-10	30"	Dbl.	U. Dk.
PARTITION ,,						20			
LONGITUDINAL ,,							30"		

Are the outside Plates doubled two spaces of Frames in length? Aft & Fwd.
Are the ~~Sluice Valves and~~ Watertight Doors in efficient working order? Yes.

Form No. 1B. 9-06

Lloyd's Register Foundation
W133-0255(1/2)

PLATING.

STRAKES.	AS IN SHIP. Amidship. Breadth.	Amidship. Thickness.	Forward. Thickness.	Aft. Thickness.	PER RULE OR AS APPROVED. Amidship. Breadth.	Amidship. Thickness.
	Inches.	40ths or 20ths	40ths or 20ths	40ths or 20ths	Inches.	40ths or 20ths
Flat Plate Keel	53	20	16	18	53	20
(If Bar Keel, state, Riveting)						
Garboard or A Strake	54½	15	15	14	36	15
B "		13	13	13		13
C "		13	13	13		13
D "		13	13	16		13
E "		13	13	16		13
F "		14	11	16		14
G "		14	11	16		14
H "		14	11	14		14
J "		14	11	14		14
K "		14	11	14		14
L "		14	11	14		14
M "		14	11	14		14
N "		14	11	14		14
O "		14	11	11		14
Sheerstrake P "	46	16	13	13	46	16
Q "						
R "						

State actual thickness in way of Double Bottom.

Write 'Sheer Strake' opposite its corresponding letter.

Doubling of Flat Plate Keel: Bar Keel in lieu

Length and thickness: of Bilges: Full 14; of Sheerstrakes: " 14; of Strake below: " 14

Poop Sides: 6-5/16

Bridge Sides: 16-12 5/16

Forecastle Sides: 6-5/16

RIVETING.

EDGES.

	Single or Double.	Breadth of Lap.	Rivets. Diam.	Rivets. Spacing cr. to cr.
		Inches.	Inches.	Inches.
Flat Plate Keel	Dbl	6¾	1⅛	4⅓
Garboard or A Strake	"	6	1	3 5/7
B "	"	5¼	⅞	3¼
C "	"	"	"	"
D "	"	"	"	"
E "	"	6	1	3 5/7
F "	"	"	"	"
G "	"	"	"	"
H "	Dbl & Tbl	"	"	"
J "	"	"	"	"
K "	"	"	"	"
L "	Dbl	"	"	"
M "	"	"	"	"
N "	"	"	"	"
O "	"	"	"	"
Sheerstrake P "				
Q "				
R "				
Doubling of Flat Plate Keel				
Length and thickness: of Bilges				
of Sheerstrakes				
of Strake below				
Poop Sides	Sgl.	2½	¾	3⅜
Bridge Sides	Sgl & Dbl	2½-3/2-3 5/16-3	¾-⅞	3¼
Forecastle Sides	Sgl.	2½	¾	3⅜

BUTTS.

	Double or Treble and for what Length.	Rivets. Diam.	Rivets. Spacing cr. to cr.	Straps. Breadth.	Straps. Thickness.	If Lapped. Breadth.	If Lapped. For what Length.
		Inches.	Inches.	Inches.	40ths or 20ths	Inches.	Feet.
Flat Plate Keel	Tbl.	1⅛	4	22	14-13		
Garboard or A Strake	Quad	1	3½			14½	½ L
B "	Dbl	⅞	3⅜			10¾	Full.
C "	Quad	"	"			12½	½ L
D "	Tbl.	"	"			9¾	Full
E "	Quad	"	"			12½	½ L
F "	Dbl	1	3½			10¾	Full
G "	Quad	"	"			14½	½ L
H "	Tbl	"	"			10¾	Full
J "	Quad	"	"			14½	½ L
K "	Tbl	1	"			10¾	Full
L "	Quad	"	"			14½	½ L
M "	Tbl	"	"			10¾	Full
N "	Quad	"	"			14½	½ L
O "	Tbl.	"	"	19	14		Full
Sheerstrake P "	Tbl	"	"	22½	16		
Q "							
R "							
Doubling of Flat Plate Keel							
Length and thickness: of Bilges							
of Sheerstrakes							
of Strake below							
Poop Sides	Tbl	¾	2⅝			5	Full
Bridge Sides	Tbl	⅞-¾	3½ 2⅝			10½ 8½	"
Forecastle Sides	Dbl.	¾	2⅝			5	"

Manufacturer's name or trade mark of the Iron or Steel (state process of manufacture of Steel) used for Frames, Floors, Beams, Keelsons, Tie and Stringer Plates, Plating, &c.? Open Hearth. Palmers, Steel Co. Scotland. South Durham, Dowlais Cardiff, D. Colville & Sons. W. Beardmore & Co Glasgow. Jas. J. & Co. Glenyarnock. J. Dunlop & Co Lanarkshire I. Co. Shelton I. & S. Co. Bowman Low & Co.

Has the Steel been tested as required by the Rules? Yes.

Upper Deck	Butts, ~~treble~~ quad riveted for	3/5 ths length amidship.
Stringer Plate	Straps, ~~single, double or~~ overlapped for	whole length amidship.
Middle Deck	Butts, treble riveted for	whole length amidship.
Stringer Plate	Straps, ~~single, double or~~ overlapped for	whole length amidship.

Butts of Bilge & Side Stringers and Tie Plates, treble ~~or double~~ riveted?

Inner Bottom Plating, riveting of Edges double. Butts treble & double

Centre Girder Butts, quad riveted. Keelson Butts, riveted.

Frames, riveted through Plates with 1 9/16 in. Rivets, about 6 2 5/4 apart.

Rivets, state whether Iron or Steel Iron & Steel

FRAMES extend in one length from Centre girder to Margin plate & from Margin plate to gunwale

REVERSED FRAMES on floors and frames extend from Centre girder to Margin plate & from Margin plate to gunwale and Forecastle Dk alternately. Channel Frames amidships.

MASTS, SPARS, &c.

	Material.	Total Length.	Diameter and Thickness. At Partners.	Heel.	Hounds.	Head.	No. of Plates in round.	Angles. Number.	Angles. Size.	Riveting. Seams.	Riveting. Butts.
			Inches.								
Lower Masts. Fore	Steel	91.6	26×8/20	25×8/20	16×7/20	8×6/20	3	3	5½×3×7/16	Single	Double Single
Main	"	94.0	26×8/20	25×8/20	16×7/20	8×6/20	3	3	3½×3×7/16	Single	& Quad.
Mizen	—										
Bowsprit											

Topmasts, Yards and Remainder of Spars Pitch Pine "

Rigging, Material and Size, Shrouds Steel wire 4" Stays 4" Steel wire Double

Sails. One Suit of fore & aft- Sails, and the following spare sails

EQUIPMENT No. 61386 LETTER C† Rule Table 22 ANCHORS.

Number of Certificate.	Anchors.	Weight, Ex. Stock. Cwts.	qrs.	lbs.	Weight of Stock. Cwts.	qrs.	lbs.	Test, per Certificate. Tons.	cwts.	qrs.	lbs.	Weight Required by Table 22. Cwts.	qrs.	lbs.	Description of Anchor.	Makers.	Where and when tested and Superintendent.
53988	1st Bower	77	1	14	Stockless			57	8	3	0	77	0	0	Hall Cast Steel	~~J. Hingley & Sons~~	LPHN 31/5/05 H Green
53989	2nd "	77	0	14	"			57	8	3	0	77	0	0	Head. "	"	" 31/5/05 "
54003	3rd "	65	1	7	"			51	5	0	0	65	2	0	" "	"	" 5/6/05 "
	4th "																Hammer Drop
	Collective weight	219	3	7								219	2	0			Bend tests
53765	Stream	21	3	16	5	2	20	22	7	2	0	22	0	0	Trotmans	"	" 11/5/05 "
56662	Kedge	11	0	15	2	3	25	13	2	2	0	10	0	0	" "	"	" 8/12/03 "

Returned by proof bowers jaws 8/11/04

If Patent state name of Patentee. If Stockless, state Mechanical Power.

CHAIN CABLES.

Number of Certificate.	Fathoms.	Size.	Test per Certificate. Tons.	Weight of Chain Cable. Supplied.	Weight of Chain Cable. Per Table 22.	Fathoms and Size per Table 22.	Description.	Makers of Cables.	When and where tested, and Superintendent.
36805	150	2 7/16	149 5/8	444.3.25	890.1.4	300×2 7/16	Stud	~~J. Hingley & Sons~~	LPHN 5/10/05
36838	150	"	106 7/8	445.1.20			"		" 31/10/05
	300			890.1.17					H Green Supt.
Iron Stream ~~Chain~~ or Steel Wire	120	5	59			120-5	Steel wire		

HAWSERS AND WARPS.

Material.	Fathoms.	Size.	Breaking Test of Steel Wire Towline.	Fathoms and Size per Table 22.
Towline	150	5¾	78	150-5¾
Hawser 2 Hy	90	3½	26	100-8 Manila
Warp 2 Hy	90	3	18	4 Hy 90
Warps 4 Hy	100	8	Manila	
4 Hy	100	7	Manila	

Boats 2, 28 ft. Life boats & 4, 26 ft. Cutters

Pumps, Number Seven Diameter of Barrel 6" State whether they are in efficient working order Yes.

Windlass is Iron patent Capstan

Engine Room Skylights.—How constructed? Steel plates

What arrangements for deadlights in bad weather? Steel shutters & bulls eyes

Coal Bunker Openings.—How constructed? Steel Coamings How are lids secured? Battened Height above deck? 9"

Number of Scuppers, and numbers and dimensions of Freeing Ports, &c. 8 Scuppers. 11 Wash ports. 3.0×1.0 each side.

Ceiling in Holds, thickness and material R.P. 2½ Under Hatchways only Ceiling 'tween Decks, thickness and material 2" Red Pine

Cargo Hatchways.—How formed? Steel Coamings Hatches, If strong and efficient? Yes.

State size No. 1 Hatch (Forward) 21.8×16.0 No. 2 Hatch 30.4×17.0 No. 3 Hatch 21.8×16.0 No. 4 Hatch 30.4×17.0

Number of Web Plates, Shifting Beams and Fore and Afters to each Hatch Nos 1.2.3, 2 Webs, 2 Beams. Nos 2 & 4, 3 Webs, 3 Beams. No. 5 Hatch 21.8×16.0

No. of Breasthooks 8 No. of Crutches 3 & deep floors

Bulwarks, height above deck and description 4.6"×5/20 Main Rail, material and size Steel bulb angle 6×3½×5/16

The above is a correct description. FOR HARLAND & WOLFF LTD. Surveyor's Signature E. J. Hilton

Builder's Signature (here only) A. H. Carlisle Surveyor to Lloyd's Register of British and Foreign Shipping.

Form No. 1.B.

Correspondence.—State dates and initials of letters respecting this case (*Reference should be made to any correspondence connected with this case*) M. 2.9.04. 20.2.05

Workmanship. Are the butts of plating planed or otherwise fitted? Lapped & planed.

Is the riveted work properly closed? Yes.

Are the liners between the frames and plates solid single pieces? Yes Do the holes for riveting plate to frames, butt straps, or plate to plate, &c., conform well to each other? Yes Are the rivet holes well and sufficiently countersunk in the plate and punched from the faying surfaces? Yes Do any rivets break into or through the seams or butts of plating? Very few

Are the butts of Plating, Stringers, &c., properly shifted and strapped? Yes

Have all the upper and weather decks been tested as required by the Rules (Sec. 23, par. 24)? Yes State results of tests Satisfactory

Have all the gutterways been tested as required by the Rules (Sec. 23, par. 25)? Yes State results of tests Satisfactory

General Remarks (State quality of workmanship, &c.) This vessel has been built in accordance with the Rules and the approved plans and the Secretary's letters of above dates.

The workmanship and materials are good throughout.

Cove ceiling is fitted over the timbers and under the hatchways only, as specified by the Owners.

No cement has been laid on the inner surface of the steel plating inside the double bottom except over the sunken strakes and in the Boiler space. Cement laid elsewhere as usual. Specified by the Owners.

The Surveyor should state the Number of Report and Name of any Sister Vessel.

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 50.5 ft., R.Q.D. or Break ft., Bridge Dk. 86.66 ft., F'castle 57.25 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated not joined

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 2 Dks (Stl) and deep framing

Official No. ; Signal Letters

How are the surfaces preserved from oxidation? Inside Portland Cement & Paint Outside Paint; cemented only on raised Strakes of plating in Cell Dk. Brick wash elsewhere.

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cell Dk.

Where fitted.	*Length. Feet.	Water Capacity. Tons.	Where fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	138.8	671	Fore peak tank,		
Double bottom, under Engines and Boilers,	82.4	468	After peak tank,	130	87
Double bottom, if under Engines only,			Midship deep tank,		
Double bottom, if under Boilers only,			Other tanks, if fitted,		
Double bottom, forward,	179.10	877 2/16	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules Yes.

Order for Special Survey No. 491

Date 16th Oct. 1904

No. 869 in builder's yard.

Dates of Surveys held while building: 1904. Oct. 18.22.27. Nov 3.5.8.11.25.28. Dec 1.13.15.20.23. 1905 Jan. 4.10.12.16. 19.23.25.27.31. Feb 1.3.14.15.20.21.23.25.28. Mar. 2.6.9.14.17.21.24. Apl. 4.7.11.13.18.20.28. May 2.5.10.16.18.23.29. June 2.6.9.13.14.16.19.21.26.29.30 July 4.7.17.18.19.24.25.26.27.28 Aug 1.3

Total No. of Visits 76

The amount of Entry Fee £ 5:0:0

Special Survey Fee £211:4:0

Travelling Expenses, if any £ : :

Fees applied for, 8/8/ 1905

Received by me, 15 Aug 1905 £216:4:0

Certificate to be sent to This Office.

State whether the Vessel has been built under Special Survey Yes.

I am of opinion this Vessel should be Classed ✠ 100 A.1. Steel

With, or without Freeboard, as condition of Class Without

E. J. Hilton Surveyor to Lloyd's Register of British and Foreign Shipping.

The Surveyors are requested not to write on or below the Committee's Minute.

Committee's Minute FRI 11 AUG 1905

Character assigned 100 A1 (subject to Lloyds rule & Q) + LMC 8.05 Elec. light

15/8/05

© 2020 Lloyd's Register Foundation