

MAXIMUM	TENSILE	STRENGTH	OF	SHELL	&	BUTT	STRAPS	=	32	TONS
MINIMUM	"	"	"	"	"	"	"	=	28	"
FURNACES,	WRAPPERS	&	ALL	FLANGED	PLATES	=	26	TO	30	"
COMBUSTION	CHAMBER	SCREWED	STAYS	TO	BE	OF	STEEL			
MATERIAL	TO	BE	TESTED	AS	REQUIRED	BY	LLOYDS.			

FAIRFIELD ENGINE WORKS
COVAN, GLASGOW

CHECKED 13-1-21
BY W.H.

DEPARTMENT	PRINT	ISSUED	PRINT	RETURNED
<i>Electric</i>	<i>13-1-21</i>			
<i>Office</i>	<i>" "</i>			
<i>Design</i>	<i>13-1-20</i>			
<i>Foundry</i>				
<i>2. Boiler Dept</i>	<i>14-1-21</i>			
<i>Office</i>	<i>20-1-21</i>			

U.S. REPAIRING & ENGINE CO.
ENGINE DEPT
28 APR. 1921
NEW YORK, U.S.A.

NOTE: EVERY PRINT ISSUED MUST BE RETURNED TO DRAWING OFFICE WHEN WORK IS FINISHED

S. E. BOILERS.
ENGINE N^o 611.
SCALE 1" = 1 FOOT.

Cynthia

GLASGOW REPORT No. 41073.

Fairfield ~~St~~ E Col 4

Bolton 611.

Monmouth St 20 18' 37 1/2

RETAIN

© 2020

Lloyd's Register
Foundation