

9-DEC-1922

Chief Surveyors 6.12.22

Received from Chief Surveyors \_\_\_\_\_

NAME See 9/s Anamba

Report JG

No. \_\_\_\_\_

**For the CHIEF SHIP SURVEYOR and CHIEF ENGINEER SURVEYOR.**

(In cases which have to be submitted to the Classing Committee "the endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/22.)

Survey Scantlings

When due \_\_\_\_\_

*See Endorsement  
8.12.22*

It is submitted the Singapore Surveyors be informed that the thickness of deck plating and floors are as follows:-

Awning Dk. Stringer Plate  $36 \times \frac{8}{20}$ " to  $28 \times \frac{7}{20}$ "

Awning Dk plating  $\frac{6}{20}$ " full length,  $\frac{8}{20}$ " abreast hatches.

Main Dk Stringer Plate  $40 \times \frac{11}{20}$ " to  $30 \times \frac{8}{20}$ "

Main Dk Plating  $\frac{7}{20}$ " to  $\frac{6}{20}$ ", and  $\frac{8}{20}$ " abreast hatches.

Bridge Dk. Stringer plate  $30 \times \frac{7}{20}$ ", Dies  $12 \times \frac{6}{20}$ ",  $2 \frac{1}{2}$ " Feak.

Floors  $\frac{7}{20}$ ", in Boiler space  $\frac{8}{20}$ "

W1365-0164

*M. A.W.J. 9/12/22.*

Lloyd's Register  
Foundation