

No. 266.

PROFILE & DECK PLANS.

SCALE 1/8 INCH TO ONE FOOT.

GIRDERS AT HEAD OF W.S. PILLARS

UPPER DECK										2ND DECK									
FRAMING	S	B	H	SPACING	DEPTH	WEIGHT	AREA	MO. INCHES	SPACING	FRAMING	S	B	H	SPACING	DEPTH	WEIGHT	AREA	MO. INCHES	SPACING
1-10	10.8	14.4	5	24.0	11	12	130	8.4	5.0	11-20	11.0	14.4	5	24.0	11	12	130	8.4	5.0
21-30	10.8	14.4	5	24.0	11	12	130	8.4	5.0	31-40	11.0	14.4	5	24.0	11	12	130	8.4	5.0
41-50	10.8	14.4	5	24.0	11	12	130	8.4	5.0	51-60	11.0	14.4	5	24.0	11	12	130	8.4	5.0
61-70	10.8	14.4	5	24.0	11	12	130	8.4	5.0	71-80	11.0	14.4	5	24.0	11	12	130	8.4	5.0
81-90	10.8	14.4	5	24.0	11	12	130	8.4	5.0	91-100	11.0	14.4	5	24.0	11	12	130	8.4	5.0
101-110	10.8	14.4	5	24.0	11	12	130	8.4	5.0	111-120	11.0	14.4	5	24.0	11	12	130	8.4	5.0
121-130	10.8	14.4	5	24.0	11	12	130	8.4	5.0	131-140	11.0	14.4	5	24.0	11	12	130	8.4	5.0
141-150	10.8	14.4	5	24.0	11	12	130	8.4	5.0	151-160	11.0	14.4	5	24.0	11	12	130	8.4	5.0
161-170	10.8	14.4	5	24.0	11	12	130	8.4	5.0	171-180	11.0	14.4	5	24.0	11	12	130	8.4	5.0
181-190	10.8	14.4	5	24.0	11	12	130	8.4	5.0	191-200	11.0	14.4	5	24.0	11	12	130	8.4	5.0
201-210	10.8	14.4	5	24.0	11	12	130	8.4	5.0	211-220	11.0	14.4	5	24.0	11	12	130	8.4	5.0
221-230	10.8	14.4	5	24.0	11	12	130	8.4	5.0	231-240	11.0	14.4	5	24.0	11	12	130	8.4	5.0
241-250	10.8	14.4	5	24.0	11	12	130	8.4	5.0	251-260	11.0	14.4	5	24.0	11	12	130	8.4	5.0
261-270	10.8	14.4	5	24.0	11	12	130	8.4	5.0	271-280	11.0	14.4	5	24.0	11	12	130	8.4	5.0
281-290	10.8	14.4	5	24.0	11	12	130	8.4	5.0	291-300	11.0	14.4	5	24.0	11	12	130	8.4	5.0
301-310	10.8	14.4	5	24.0	11	12	130	8.4	5.0	311-320	11.0	14.4	5	24.0	11	12	130	8.4	5.0
321-330	10.8	14.4	5	24.0	11	12	130	8.4	5.0	331-340	11.0	14.4	5	24.0	11	12	130	8.4	5.0
341-350	10.8	14.4	5	24.0	11	12	130	8.4	5.0	351-360	11.0	14.4	5	24.0	11	12	130	8.4	5.0
361-370	10.8	14.4	5	24.0	11	12	130	8.4	5.0	371-380	11.0	14.4	5	24.0	11	12	130	8.4	5.0
381-390	10.8	14.4	5	24.0	11	12	130	8.4	5.0	391-400	11.0	14.4	5	24.0	11	12	130	8.4	5.0
401-410	10.8	14.4	5	24.0	11	12	130	8.4	5.0	411-420	11.0	14.4	5	24.0	11	12	130	8.4	5.0
421-430	10.8	14.4	5	24.0	11	12	130	8.4	5.0	431-440	11.0	14.4	5	24.0	11	12	130	8.4	5.0
441-450	10.8	14.4	5	24.0	11	12	130	8.4	5.0	451-460	11.0	14.4	5	24.0	11	12	130	8.4	5.0
461-470	10.8	14.4	5	24.0	11	12	130	8.4	5.0	471-480	11.0	14.4	5	24.0	11	12	130	8.4	5.0
481-490	10.8	14.4	5	24.0	11	12	130	8.4	5.0	491-500	11.0	14.4	5	24.0	11	12	130	8.4	5.0
501-510	10.8	14.4	5	24.0	11	12	130	8.4	5.0	511-520	11.0	14.4	5	24.0	11	12	130	8.4	5.0
521-530	10.8	14.4	5	24.0	11	12	130	8.4	5.0	531-540	11.0	14.4	5	24.0	11	12	130	8.4	5.0
541-550	10.8	14.4	5	24.0	11	12	130	8.4	5.0	551-560	11.0	14.4	5	24.0	11	12	130	8.4	5.0
561-570	10.8	14.4	5	24.0	11	12	130	8.4	5.0	571-580	11.0	14.4	5	24.0	11	12	130	8.4	5.0
581-590	10.8	14.4	5	24.0	11	12	130	8.4	5.0	591-600	11.0	14.4	5	24.0	11	12	130	8.4	5.0
601-610	10.8	14.4	5	24.0	11	12	130	8.4	5.0	611-620	11.0	14.4	5	24.0	11	12	130	8.4	5.0
621-630	10.8	14.4	5	24.0	11	12	130	8.4	5.0	631-640	11.0	14.4	5	24.0	11	12	130	8.4	5.0
641-650	10.8	14.4	5	24.0	11	12	130	8.4	5.0	651-660	11.0	14.4	5	24.0	11	12	130	8.4	5.0
661-670	10.8	14.4	5	24.0	11	12	130	8.4	5.0	671-680	11.0	14.4	5	24.0	11	12	130	8.4	5.0
681-690	10.8	14.4	5	24.0	11	12	130	8.4	5.0	691-700	11.0	14.4	5	24.0	11	12	130	8.4	5.0
701-710	10.8	14.4	5	24.0	11	12	130	8.4	5.0	711-720	11.0	14.4	5	24.0	11	12	130	8.4	5.0
721-730	10.8	14.4	5	24.0	11	12	130	8.4	5.0	731-740	11.0	14.4	5	24.0	11	12	130	8.4	5.0
741-750	10.8	14.4	5	24.0	11	12	130	8.4	5.0	751-760	11.0	14.4	5	24.0	11	12	130	8.4	5.0
761-770	10.8	14.4	5	24.0	11	12	130	8.4	5.0	771-780	11.0	14.4	5	24.0	11	12	130	8.4	5.0
781-790	10.8	14.4	5	24.0	11	12	130	8.4	5.0	791-800	11.0	14.4	5	24.0	11	12	130	8.4	5.0
801-810	10.8	14.4	5	24.0	11	12	130	8.4	5.0	811-820	11.0	14.4	5	24.0	11	12	130	8.4	5.0
821-830	10.8	14.4	5	24.0	11	12	130	8.4	5.0	831-840	11.0	14.4	5	24.0	11	12	130	8.4	5.0
841-850	10.8	14.4	5	24.0	11	12	130	8.4	5.0	851-860	11.0	14.4	5	24.0	11	12	130	8.4	5.0
861-870	10.8	14.4	5	24.0	11	12	130	8.4	5.0	871-880	11.0	14.4	5	24.0	11	12	130	8.4	5.0
881-890	10.8	14.4	5	24.0	11	12	130	8.4	5.0	891-900	11.0	14.4	5	24.0	11	12	130	8.4	5.0
901-910	10.8	14.4	5	24.0	11	12	130	8.4	5.0	911-920	11.0	14.4	5	24.0	11	12	130	8.4	5.0
921-930	10.8	14.4	5	24.0	11	12	130	8.4	5.0	931-940	11.0	14.4	5	24.0	11	12	130	8.4	5.0
941-950	10.8	14.4	5	24.0	11	12	130	8.4	5.0	951-960	11.0	14.4	5	24.0	11	12	130	8.4	5.0
961-970	10.8	14.4	5	24.0	11	12	130	8.4	5.0	971-980	11.0	14.4	5	24.0	11	12	130	8.4	5.0
981-990	10.8	14.4	5	24.0	11	12	130	8.4	5.0	991-1000	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1001-1010	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1011-1020	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1021-1030	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1031-1040	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1041-1050	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1051-1060	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1061-1070	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1071-1080	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1081-1090	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1091-1100	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1101-1110	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1111-1120	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1121-1130	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1131-1140	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1141-1150	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1151-1160	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1161-1170	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1171-1180	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1181-1190	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1191-1200	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1201-1210	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1211-1220	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1221-1230	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1231-1240	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1241-1250	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1251-1260	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1261-1270	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1271-1280	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1281-1290	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1291-1300	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1301-1310	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1311-1320	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1321-1330	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1331-1340	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1341-1350	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1351-1360	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1361-1370	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1371-1380	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1381-1390	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1391-1400	11.0	14.4	5	24.0	11	12	130	8.4	5.0
1401-1410	10.8	14.4	5	24.0	11	12	130	8.4	5.0	1411									

RECEIVED

Profile & Decks
N^o 266
S.S. "Calcutta Main"
Nagasaki Rept N^o 1138



© 2021

Lloyd's Register
Foundation