

Writes "Bridge Sheer Stroke" and "Upper Deck Sheer Stroke" opposite the corresponding letter.

0159 $2\frac{1}{2}$

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ✓ ft., R.Q.D. ✓ ft., Bridge ✓ ft., Forecastle ✓
(in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ✓

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as
should appear in the Register Book) 1 DK (all)

Official No. ✓ 133227; Signal Letters ✓

State if Machinery is fitted aft ✓

How are the surfaces preserved from oxidation? Inside Portland Cement Bituminous Enamel on side Outside Bituminous Enamel

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors ✓

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capac Tons.
Double bottom, aft, ✓			Fore peak tank, ✓		
Double bottom, under Engines and Boilers, ✓			After peak tank, ✓		
Double bottom, if under Engines only, ✓			Deep tank, aft, ✓		
Double bottom, if under Boilers only, ✓			Deep tank, forward, ✓		
Double bottom, forward, ✓			Other tanks, if fitted, ✓		
			(If necessary, furnish further information by sketch.) ✓		
	Total capacity of double bottom ✓				

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules ✓

Order for Special Survey No. 1989

Date

22/11/12

No.

110

in builder's yard.

DATES of Surveys
held while building

1912:- Dec 19. 31 1913:- Jan 4. 14. 28. Feb 12. 22. Mar 6. 18. 31. Apr. 2. 17
May 1-16. Jun 25. Jul 2. 16. Aug 18. 25. Sep. 8. 17.

Total No. of Visits 21

Surveyor's Signature Allison G. Wilson

Lloyd's Register
Foundation