

Awning or Shelter Deck, or Pt. Awning Deck.

STEEL STEAMER.

No. 2685

State if Report is also sent on the Machinery of the Vessel *yes* TUE 10 FEB. 1920
Port of *Kobe* Date of completion of Report *December 23rd 1919* Received at London Office
Survey held at *Kobe* Date, First Survey *July 14th 1919* Last Survey *December 2nd 1919*
On the *SINGLE SCREEN STEAMER "EASTERN MOON"* Rig *2 Masts*

TONNAGE under 4184.35 CLASS 100 A.1. Awning Deck FEET.
Do. between Tonnage Dk. and 1395.00 Breadth (greatest moulded) 51.00
Do. 4th. or Awning Dk. 5579.35 Depth, at middle of length from top of keel to top of 36.00
Total under Upper Dk. beams at side of uppermost Continuous Deck
Do. of Poop Deduct height of 'tween deck when this does not exceed 8ft. 28.00
Do. of R. Qr. Dk. Transverse Number 79.00
Do. of Bridge House Length on deck from fore part of stem to after part of 385.00
Do. of Forecastle sternpost 304.15
Do. of Houses on Deck 264.44 Longitudinal Number 16.0
Do. of Houses on Deck 23.31 Depth "d" at middle of length. See Secs. 2 & 13. 10.7
Do. of Houses on Deck 107.54 Proportions, Depths to Length, Uppermost Continuous Deck at side to top of keel 13.7
Do. of Houses on Deck 5974.64
Do. of Houses on Deck 296.18
Do. of Houses on Deck 1240.96
Do. of Houses on Deck 379.01
Do. of Houses on Deck 65.71
Do. of Houses on Deck 4292.78
Destined Voyage *Building*
If Surveyed while Building, Afloat, or in Dry Dock *Building*

Ft.	Ins.	BREADTH	Ft.	Ins.	DEPTH, ACTUAL	Top of Floors to top of Awn. or Shelter Dk. Beams	Ft.	Ins.	No. of Decks with flat laid
385	0	Moulded	51	0	Do.	Do.	33	7	3
							25	7	No. of Tiers of Beams 3
per Register, 36 ft. Awn. or Shelter Dk. Moulded depth, ft. 36 ins. 0 To Awning or Shelter Dk. Round up of Uppermost Dk. Beam, Actual 12 3/4 ins.									
385.0 breadth 51.0 depth. 28 ft. Upper Deck. Moulded depth, ft. 28 ins. 0 To Upper Dk.									
FRAMING.						PILLARS.			
Inches in Ship	Inches in Ship	Inches in Ship	Inches in Ship	Inches in Ship	Inches in Ship	UPPER	Inches in Ship	Inches in Ship	Inches in Ship
9	3 1/2	52	9	3 1/2	52	PILLARS, in 'tween Deck, size and spacing	7 x 3 1/2	3 1/2 x 40	about 33-0 1/2 in
6	3 1/2	38	6	3 1/2	36	" " " " "	5 x 5	44-40	" " "
3 1/2	3 1/2	40	3 1/2	3 1/2	40	Quarter, 'tween Dks., "	8 x 8	56	approved or equal
8	3 1/2	40	8	3 1/2	40	" " in Hold "			
KEELSONS AND STRINGERS.						CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercoastal Plate			
25 1/2			25 1/2			Rider Plate			
24			24			Flat Keel Plate Angles			
3 1/2	3	36	3 1/2	3 1/2	36	Horizontal Plates on Floors			
3 1/2	3 1/2	40	3 1/2	3 1/2	40	Angles or Bulb Angles			
7	3 1/2	40	7	3	40	SIDE KEELSONS, Number			
6 in A.P.			6 in A.P.			Angles or Bulb Angles			
						Plate above floors, for length			
						Intercoastal Plate, for length			
						Attached to outside plating with Angle			
						BILGE KEELSON, Angles			
						Intercoastal Plate, for length			
						Attached to outside plating with Angle			
						SIDE STRINGERS, Number	2 in No. 1 Hold	2 in No. 1 Hold	
						Angle	7 3 1/2 .58	7 3 1/2 .58	
						Intercoastal Plate, for No. 1 Hold lng.	.42	.42	
						Attached to outside plating with Angle	Flanged 3 1/2	Flanged 3 1/2	
						Awning or Shelter Deck Stringer Plates, breadth and thickness	53-34 x 54-42	53-34 x 54-42	
						Angle on ditto	4 1/2 x 4 1/2 .58	4 1/2 x 4 1/2 .58	
						Tie Plates, fore and aft, outside Hatchways			
						Deck, * Iron or Steel, for Whole lng.	42-38	42-38	
						Wood Deck, Material & thickness	No Wood deck	No Wood deck	
						Upper Deck Stringer Plate, breadth and thickness	46-34 x 46-42	46-34 x 46-42	
						Angles on ditto, No.	3 1/2 x 3 1/2 .46	3 1/2 x 3 1/2 .46	
						Tie Plates, outside Hatchways			
						Deck, * Iron or Steel, for Whole lng.	34-30	34-30	
						Wood Deck, Material & thickness	No Wood deck	No Wood deck	
						Second Deck Stringer Plates, br'dth & thickn's	46-34 x 42	46-34 x 42	
						Angles on ditto, No.	3 1/2 x 3 1/2 .46	3 1/2 x 3 1/2 .46	
						Tie Plates, outside Hatchways			
						Deck, * Material and thickness	34-30	34-30	
						Third, Fourth & Fifth Deck Stringer Plate, breadth and thickness			
						Angles on ditto, No.			
						Tie Plates, outside Hatchways			
						Deck, Material and thickness			
						Poop Deck Stringer Plate, breadth & thickness			
						Angles on ditto			
						Tie Plates			
						Deck, Material and thickness			
						Bridge Deck Stringer Plate, br'dth & thickness			
						Angle on ditto			
						Tie Plates			
						Deck, Material and thickness			
						Forecastle Deck Stringer Plate, br'dth & th'kns			
						Angle on ditto			
						Tie Plates			
						Deck, Material and thickness			

GENERAL REMARKS—(continued).

"S.S. Naples Maru" (Kobe report 2587) S.S. France Maru (Kobe report 2647) "S.S. England Maru" (Kobe report 2669)

WEB-FRAME
" " No
WEB-FRAME
" " No
WEB-FRAME
Partial
" " No
" " Size of
BRACKET 1
Web Frame

BULKHEAD

W.T.BULKHEAD

„ COLLISION
PARTITION
LONGITUDINAL

Are the outer

Are the steel

STEEL

FLAT PLATE
(If Bar Keel
GARBOARD)

State actual
thickness
way of Deck
Bottom

Write "Aunting or Shelter Deck" "Shelter Strake" opposite its corresponding letter.

Ann. 8

TRUNK
CLEAR
DO.

DECK

"

Length

POOP

SHORE

FORE

FR

RE

Upper

Str

FR

RE

FR

RE

FR

RE

FR

RE

FR

RE

FR

RE

FR

RE

FR

RE

FR

RE

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ☒ ft., R.Q.D. ☒ ft., Bridge ☒ ft., Forecastle ☒ ft.
(in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ☒

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 2 Decks (steel) and Awning Deck (steel)

Official No. 26180; Signal Letters R.S.K.G.

State if Machinery is fitted aft No.

How are the surfaces preserved from oxidation? Inside 3 coats of paint Outside 3 coats of paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cellular

Where Fitted.	Length.	Water Capacity.	Where Fitted.	Length.	Water Capacity.
	Feet.	Tons.		Feet.	Tons.
Double bottom, aft,	116.9	342.0	Fore peak tank,	126.0	126.0
Double bottom, under Engines and Boilers,	44.6	182.0	After peak tank,		93.0
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,	172.1	594.0	Other tanks, if fitted,		
Total capacity of double bottom		1118.0	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules. Yes

Order for Special Survey No.

Date

No. 454 in builder's yard.

DATES of Surveys held while building

19 July 14. 16. 21. 26. 28. 29. 31. Aug. 1. 2. 4. 5. 6. 7. 8. 9. 11. 12. 13. 14. 15. 16. 18. 19. 20. 21. 22. 23.
Aug. 25. 26. 27. 28. 29. 30. Sept. 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 13. 14. 16. 17. 18. 19. 20.
Oct. 1. 2. 3. 4. 5. 7. 8. 9. 10. 11. 13. 14. 16. 17. 18. 19. 20. 21. 22. 24. 25. 27. 28. 29. 30.
Nov. 1. 3. 4. 5. 6. 7. 11. 13. 15. 17. 18. 20. 22. 24. 25. 26. 28. 29. Dec. 2

Total No. of Visits 95

Surveyor's Signature

H. J. House

© 2021

Lloyd's Register
Foundation

Rpt. 4

Date of

No. in

Reg. Bo

Master

Engine

Boilers

Register

Nom. Ho

ENGIN

Dia. of

Is the sc

in the p

between

liners an

Dia. of T

collars

No. of

No. of

No. of

In Engi

No. of B

Are all t

Are all

Are they

Are they

What p

Are all

Are the

Is the S

BOILE

Total B

Workin

Can eac

each boi

Smallest

Thicknes

long. se

Per cent

Size of

Length

Working

Pitch of

Material

Material

Area a

Thickne

Diamete

Pitch

thicknes

Workin

Diamete

Pitch of

SUPE

Date of

Diamete