

the front of the

Is it fitted with a watertight door yes worked from top platform.

BOILERS, &c.— (Letter for record S. ) Total Heating Surface

L. Hymettus

Nwe. 50000

It is submitted that it should be pointed out to the Nwe Surveyors that the heating surface of the Aux Dr. should be taken into account in calculating the NP, which in this case is increased to 580. + the fee of £49.

Nwe  
31/1/06.

31. 1.06

31-1-06.

© 2021

Lloyd's Register  
Foundation

W1474-0078

Working pressure by rules 9 x 12 Length as per rule 30" Distance apart 9 1/4" Number and pitch

Working pressure by rules 196 lbs Superheater or Steam chest; how connected to boiler none Can the superhe

separately Diameter Length Thickness of shell plates Material Description of

180 lbs T  
-6 g N  
180 lbs  
1/2" Length 11  
seams S.  
width of  
Size of ma  
Material  
led  
32" Back  
nuts  
pressure by r  
re by rules  
Material  
Worki  
Back  
Chamber

General

Is a Report also sent of the Hull

BOIL

No. a

Date o

each b

Small

Thickn

Diam

Per ce

Size o

Length

Work

Pitch

Mater

Mater

<sup>a</sup>  
Diam

Thickn

Diam

Pitch

thickn

Work

Copyrightable Ink.]



© 2021

Lloyd's Register  
Foundation

General