

HOLD PILLARS.					
FR.	S.	B. H.	EXCH.	L.	RULE SIZE
			TOG.		
19	24.25	2.75	15.8	39.8	19.5 18 O.P.X. 64
3	24.75	3.00	14.5	36.0	18.1 18 O.P.X. 74
46	24.75	35.00	14.5	125.5	6.2 18 O.P.X. 78
61	25.00	35.00	17.0	15.0	5.0 20 O.P.X. 82
110	25.62	35.00	14.5	120.0	7.3 18 O.P.X. 70
125	24.75	35.00	14.5	125.5	7.5 18 O.P.X. 70
139	22.50	34.25	14.5	111.2	8.3 18 O.P.X. 64
155	22.50	36.25	14.5	98.7	7.0 17 O.P.X. 60

— LLOYD'S NUMBERS —
— TRANS. NUMBER = ---- 81. —
— LONGTL. " " = 30537. —

RIDER PLATE TO EXTEND AS INDICATED
ABOVE AND TO LAP 3 ON DIAMOND PLATE
AT INTERSECTION OF GIRDER & PILLAR BEAM

GIRDERS UNDER 2ND DECK					PILLAR BEAMS UNDER 2ND DECK					
GIRDER	DEPTH	THICKNESS	DECK ANGLE	CHANNEL ON LOWER PLATE	RIDER PLATE	PILLAR BEAMS	DEPTH	THICKNESS	DECK ANGLE	CHANNEL ON LOWER PLATE

Standard Shipbuilding Corporation

S/S. No 2

"MUSCATINE"

Profile & Deck Plan

New York Report No. 14883



© 2021

W1539-0155
Lloyd's Register
Foundation