

Rpt. 1*.

PARTICULARS OF LONGITUDINAL FRAMING.

Duplicate

*Province Town
22. 1912*

FRAMING.			AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.							
			In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames.		Spacing of Rivets on each side of Transverses and Bulkheads.	Rivets in Brackets to Bulkheads.				
			Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Diam.		Speng.	Number.	Diameter.		
Framing of L, L or C																						
Frames in Bridge 'tween Decks...																						
Frames from Uppermost Continuous Deck																						
Framing from Awning, Shelter or Upper Deck to Margin Plate.	No. 1		6	35	35	6	35	35	6	35	35	6	35	35	6	35	35	7/8	5 1/4	5 1/4	5	3/4
	" 2		6	35	35	6	35	35	6	35	35	6	35	35	6	35	35	"	"	"	5	3/4
	" 3		6	35	35	6	35	35	6	35	35	6	35	35	6	35	35	"	"	"	6	7/8
	" 4		7	30	34	7	30	34	7	30	34	7	30	34	7	30	34	7/8	5 1/4	"	6	"
	" 5		7	40	35	7	40	35	7	40	35	7	40	35	7	40	35	"	"	1 1/2 for 9 rivets	6	"
	" 6		7	45	35	7	45	35	7	45	35	7	45	35	7	45	35	"	"	"	7	7/8
	" 7		10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	7/8	5 1/4	"	7	7/8
	" 8		10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	"	"	3 1/2 for 9 rivets	8	7/8
	" 9		10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	"	"	"	8	"
	" 10		10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	10	37 1/2	37 1/2	"	4 1/8	"	8	"
	" 11		10	45	35	10	45	35	10	45	35	10	45	35	10	45	35	"	4 1/8	"	8	"
	" 12																					
	" 13																					
	" 14																					
	" 15																					
	" 16																					
Spacing of Longitudinal Frames			Amidships			At Ends			Amidships			At Ends										
			2' 6" x 2' 8"			1' 9"			2' 4" x 2' 8"			1' 9"										
Double Bottoms L, L or C			Tank Top Longitudinals			Bottom			Bottom			Bottom										
			7 30 34			7 30 34			7 30 34			7 30 34			7 30 34 7/8 5 1/4 4 1/8 for 4 rivets							
			7 40 35			7 40 35			7 40 35			7 40 35			" " 3 1/2 " " "							
			2' 6"			2' 6"			2' 6"			2' 6"										
Spacing of Longitudinals			Amidships			At Ends			Amidships			At Ends										
			2' 6"			2' 6"			2' 6"			2' 6"										
Transverses.															Rivets in Lugs to Shell Diam. Speng.							
In Bridge 'tween Decks			Depth and Thickness			Face Angles			Lugs to Shell													
			15' x 38			15' x 38			15' x 38			15' x 38										
			6 3 1/2 38			6 3 1/2 38			6 3 1/2 38			6 3 1/2 38										
			3 1/2 3 1/2 38			3 1/2 3 1/2 38			3 1/2 3 1/2 38			3 1/2 3 1/2 38			7/8 5							
In Awning, Shelter or Upper 'tween Decks.			Depth and Thickness			Face Angles			Lugs to Shell													
			3 1/2 x 50			2 7/8 x 50			3 1/2 x 50			2 7/8 x 50										
			6 4 80			6 4 80			6 4 80			6 4 80										
			6 6 46			6 6 46			6 6 46			6 6 46			7/8 5							
In Hold.			Depth and Thickness			Face Angles			Lugs to Shell													
			10' 0"			10' 0"			10' 0"			10' 0"			10' 0" 11' 0"							
			10' 0"			10' 0"			10' 0"			10' 0"										
Spacing of Transverse Frames																						
Longitudinal Beams of L, L or C			Bridge Deck			Awg. or Shltr. Dk.			Upper			Second			Third			Spacing.				
			6 35 35			6 35 35			6 35 35			6 35 35			7' 9" x 7 1/2"			Transverse Beams.				
																		12 x 38 6 x 47 1/2 13 x 40 6 x 47 1/2 13 x 40 6 x 47 1/2				

The particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.