





## PARTICULARS OF LONGITUDINAL FRAMING.

GEN.	FRAMING.	AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.		Rivets in Brackets to Bulkheads.			
		In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames. Diam. Spacing.	Spacing of Rivets on each side of Transverses and Bulkheads. Inches.	Number.	Diameter. Inches.		
		Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.					Ins.	
	Framing of $\angle$ , $\times$ or $\square$ .....																		
	Frames in Bridge 'tween Decks ...																		
	Frames from Uppermost Continuous Deck																		
	Framing from Awning, Shelter or Upper Deck to Margin Plate.	No. 1	6	.35	3.5	6	.35	3.5	6	.35	3.5	6	.35	3.5	7/8	5/4	5/4	6	3/4
" 2		6	.35	3.5	6	.35	3.5	6	.35	3.5	6	.35	3.5	"	"	"	6	3/4	
" 3		6	.35	3.5	6	.35	3.5	6	.35	3.5	6	.35	3.5	"	"	"	6	7/8	
" 4		7	.30	3.4	7	.30	3.4	7	.30	3.4	7	.30	3.4	"	"	"	6	"	
" 5		7	.40	3.5	7	.40	3.5	7	.40	3.5	7	.40	3.5	"	"	4 3/8 for 9 Rivets	8	7/8	
" 6		7	.45	3.5	7	.45	3.5	7	.45	3.5	7	.45	3.5	"	"	"	8	"	
" 7		10	.375	3.375	10	.375	3.375	10	.375	3.375	10	.375	3.375	"	"	3 1/2 for 9 Rivets	8	7/8	
" 8		10	.375	3.375	10	.375	3.375	10	.375	3.375	10	.375	3.375	"	"	"	8	7/8	
" 9		10	.375	3.375	10	.375	3.375	10	.375	3.375	10	.375	3.375	"	"	"	8	"	
" 10		10	.45	3.5	10	.45	3.5	10	.45	3.5	10	.45	3.5	"	4 3/8	"	8	"	
" 11		10	.45	3.5	10	.45	3.5	10	.45	3.5	10	.45	3.5	"	"	"	8	"	
" 12																			
" 13																			
" 14																			
" 15																			
" 16																			
	Spacing of Longitudinal Frames	Amidships			2'-4" to 2'-8"			At Ends			2'-4" to 2'-8"								
	Double Bottoms $\angle$ , $\times$ or $\square$	Tank Top Longitudinals			7.30 3.4			7.30 3.4			7.30 3.4			7/8 5/4	4 3/8 for 4 Rivets				
		Bottom			7.40 3.5			7.40 3.5			7.40 3.5			"	3 1/2 " " "				
	Spacing of Longitudinals	Amidships			2'-6"			At Ends			2'-6"								
	Transverses.																		
	In Bridge 'tween Decks	Depth and Thickness			15 x .38			15 x .38			15 x .38			15 x .38					
		Face Angles			6 3 1/2 .38			6 3 1/2 .38			6 3 1/2 .38			6 3 1/2 .38					
		Lugs to Shell			3 1/2 3 1/2 .38			3 1/2 3 1/2 .38			3 1/2 3 1/2 .38			3 1/2 3 1/2 .38		7/8 5"			
	In Awning, Shelter or Upper 'tween Decks.	Depth and Thickness			31 x .50			31 x .50			31 x .50			31 x .50					
		Face Angles			6 4 .80			6 4 .80			6 4 .80			6 4 .80					
		Lugs to Shell			6 6 .46			6 6 .46			6 6 .46			6 6 .46		7/8 5"			
	In Hold.	Depth and Thickness			6 6 .46			6 6 .46			6 6 .46			6 6 .46					
		Face Angles			6 6 .46			6 6 .46			6 6 .46			6 6 .46					
		Lugs to Shell			6 6 .46			6 6 .46			6 6 .46			6 6 .46					
		Brackets			10'-0"			10'-0"			10'-0"			10'-0"					
	Spacing of Transverse Frames	State if jogged or liners.			10'-0"			10'-0"			10'-0"			10'-0"					
	Longitudinal Beams of $\angle$ , $\times$ or $\square$	Bridge Deck			6.35 3.5			6.35 3.5			6.35 3.5			6.35 3.5					
		Awg. or Shltr. Dk.			6.35 3.5			6.35 3.5			6.35 3.5			6.35 3.5					
		Upper			6.35 3.5			6.35 3.5			6.35 3.5			6.35 3.5					
		Second																	
		Third																	

The particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.

**PARTICULARS FOR RECORD in the REGISTER BOOK.**—Length of Poop 48 ft., R.Q.D. ☒ ft., Bridge ☒ ft., Forecastle ☒ ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated.

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given in the Report Book).  
 Official No. 220625; Signal Letters M.D.L.P. State if Machinery is fitted aft 40  
 How are the surfaces preserved from oxidation? Inside Bitumestie Cement Outside Paint  
 Cellular

**PARTICULARS OF WATER BALLAST.**—State whether the Double bottom is constructed on the cellular system or with girders on floors.

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	127-7"	439.39	Fore peak tank,	20'-4"	
Double bottom, under Engines and Boilers,	55-0"	250.60	After peak tank,	8'-0" to 15'-0"	
Double bottom, if under Engines only,			Deep tank, aft,	20'-0"	
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,	161-6"	82-38	Other tanks, if fitted,		
Total capacity of double bottom	1272-37		(If necessary, furnish further information by sketch.)		

\* The wells are not to be included in the lengths of the tanks. 344 -1

Order for Special Survey No.

Date

No. 8

in builder's yard.

DATE OF SURVEY  
held while building

1919: Apr 15-22 20 May 6-13 20 Jun 3-18 25 Jul 9 Aug 5-26 Sep 3-9 16 25-30 Oct 6-15 21 22 29  
 21-26 Dec 4-15 17 24 31 1920: Jan 6-9 13 20 27 Feb 10-18 24 Mar 2-29 17 23 24 Apr 6-13 18  
 7-13 18 27 Jun 11-16 18 25 30 Jul 21-28 Aug 4-11 19 25 Sep 8-15

Surveyor's Signature

© 2020  
 Lloyd's Register  
 Foundation