

Port of Hull

Received at London Office FEB. 29 AUG 1906

No. in Survey held at Hull Date, first Survey May 4/04 Last Survey 18th Augt 1906
 Reg. Book. 14 on the Steel S. S. Tees (Number of Visits 49)
 Master Goolc Built at Goolc By whom built Goolc S. B. & Co. Ltd Tons {Gross 507 Net 222
 Engines made at Hull By whom made Charles L. & Co. Ltd when made 1906
 Boilers made at do By whom made do when made 1905
 Registered Horse Power 80 Owners E. P. Hutchinson Port belonging to Hull
 Nom. Horse Power as per Section 28 80 Is Refrigerating Machinery fitted for cargo purposes No Is Electric Light fitted No

ENGINES, &c.—Description of Engines Triple No. of Cylinders 3 No. of Cranks 3
 Dia. of Cylinders 13", 21", 35" Length of Stroke 24" Revs. per minute 130 Dia. of Screw shaft 7.9" Material of Scraper
 as fitted 8.4" screw shaft)
 Is the screw shaft fitted with a continuous liner the whole length of the stern tube No liners Is the after end of the liner made water tight
 in the propeller boss Yes If the liner is in more than one length are the joints burned ✓ If the liner does not fit tightly at the part
 between the bearings in the stern tube, is the space charged with a plastic material insoluble in water and non-corrosive ✓ If two
 liners are fitted, is the shaft lapped or protected between the liners ✓ Length of stern bush 2'-10"
 Dia. of Tunnel shaft 6.49" Dia. of Crank shaft journals 6.8" Dia. of Crank pin 7" Size of Crank webs 4 1/2 x 13 Dia. of thrust shaft under
 collars 7" Dia. of screw 9-9 Pitch of Screw 11-0 No. of Blades 4 State whether moveable No Total surface 30 sq. ft.
 No. of Feed pumps 2 Diameter of ditto 2 1/4" Stroke 12" Can one be overhauled while the other is at work Yes
 No. of Bilge pumps 2 Diameter of ditto 2 1/4" Stroke 12" Can one be overhauled while the other is at work Yes
 No. of Donkey Engines 2 Sizes of Pumps 6" x 6" x 6" + 2 1/2" x 5" x 5" No. and size of Suctions connected to both Bilge and Donkey pumps
 In Engine Room Two. One 2 1/2" + One 3 1/2" In Holds, &c. One each 2 1/2", to each, the tunnel
 well, port starboard hold, after peak, aft tank, fore hold, and fore peak.
 No. of Bilge Injections 1 sizes 3 1/2" Connected to condenser, or to circulating pump pump Is a separate Donkey Suction fitted in Engine room & size Yes 3"
 Are all the bilge suction pipes fitted with roses Yes Are the roses in Engine room always accessible Yes Are the sluices on Engine room bulkheads always accessible 0
 Are all connections with the sea direct on the skin of the ship Yes Are they Valves or Cocks both
 Are they fixed sufficiently high on the ship's side to be seen without lifting the stokehold plates Yes Are the Discharge Pipes above or below the deep water line above
 Are they each fitted with a Discharge Valve always accessible on the plating of the vessel Yes Are the Blow Off Cocks fitted with a spigot and brass covering plate Yes
 What pipes are carried through the bunkers None How are they protected ✓
 Are all Pipes, Cocks, Valves, and Pumps in connection with the machinery and all boiler mountings accessible at all times Yes
 Are the Bilge Suction Pipes, Cocks, and Valves arranged so as to prevent any communication between the sea and the bilges Yes
 Dates of examination of completion of fitting of Sea Connections 18th 8. 06 of Stern Tube 18. 8. 06 Screw shaft and Propeller 18. 8. 06
 Is the Screw Shaft Tunnel watertight Yes Is it fitted with a watertight door Yes worked from top platform

BOILERS, &c.—(Letter for record) Manufacturers of Steel Kaarder & Co. Germany
 Total Heating Surface of Boilers 1450 sq. ft. Forced Draft fitted No No. and Description of Boilers One S. S. by L. Muller
 Working Pressure 180 lbs Tested by hydraulic pressure to 360 lbs Date of test 20. 1. 05 No. of Certificate 1362
 Can each boiler be worked separately ✓ Area of fire grate in each boiler 40 1/2 sq. ft. No. and Description of Safety Valves to
 each boiler Two Spring Area of each valve 3.97 sq. in. Pressure to which they are adjusted 195 lbs Are they fitted with easing gear Yes
 Smallest distance between boilers or uptakes and bunkers or woodwork 10 1/2" dia. of boilers 12'-6" Length 10'-3" Material of shell plates Steel
 Thickness 1" Range of tensile strength 29-32 tons Are the shell plates welded or flanged No Descrip. of riveting: cir. seams DR Lap
 long. seams S.P.L. 5 Rivet Diameter of rivet holes in long. seams 1 1/16" Pitch of rivets 7 1/2" Lap of plates or width of butt straps 16"
 Per centages of strength of longitudinal joint 88 Working pressure of shell by rules 181 lbs Size of manhole in shell 16" x 12"
 rivets. 88 plate 85.8 Size of compensating ring Flanged No. and Description of Furnaces in each boiler Three plain Material Steel Outside diameter 3'-2 1/4"
 Length of plain part 6-7" Thickness of plates 4 1/2" Description of longitudinal joint Welded No. of strengthening rings ✓
 top 6-7" bottom 7-4" crown 4 1/2" bottom 6 1/4" Working pressure of furnace by the rules 185 lbs Combustion chamber plates: Material Steel Thickness: Sides 5/8" Back 5/8" Top 5/8" Bottom 5/8"
 Pitch of stays to ditto: Sides 7 1/4" x 8 1/2" Back 9" x 7 1/2" Top 7 1/4" x 8 1/2" If stays are fitted with nuts or riveted heads Nuts Working pressure by rules 197 lbs
 Material of stays Steel Diameter at smallest part 1 1/2" Area supported by each stay 67.5" Working pressure by rules 208 lbs End plates in steam space:
 Material Steel Thickness 1 1/2" Pitch of stays 17" x 15" How are stays secured Nuts Working pressure by rules 186 lbs Material of stays Steel
 Diameter at smallest part 2 7/16" Area supported by each stay 255" Working pressure by rules 204 lbs Material of Front plates at bottom Steel
 Thickness 7/8" Material of Lower back plate Steel Thickness 2 3/4" Greatest pitch of stays 16" x 10" Working pressure of plate by rules 304 lbs
 Diameter of tubes 3 1/4" Pitch of tubes 4 1/2" x 4 1/2" Material of tube plates Steel Thickness: Front 7/8" Back 7/8" Mean pitch of stays 9"
 Pitch across wide water spaces 13 1/2" Working pressures by rules 190 lbs Girders to Chamber tops: Material Steel Depth and
 thickness of girder at centre 8" x 1 3/4" Length as per rule 2'-8" Distance apart 7.5" Number and pitch of stays in each 3 @ 7 1/4"
 Working pressure by rules 190 lbs Superheater or Steam chest; how connected to boiler None Can the superheater be shut off and the boiler worked
 separately ✓ Diameter ✓ Length ✓ Thickness of shell plates ✓ Material ✓ Description of longitudinal joint ✓ Diam. of rivet
 holes ✓ Pitch of rivets ✓ Working pressure of shell by rules ✓ Diameter of flue ✓ Material of flue plates ✓ Thickness ✓
 If stiffened with rings ✓ Distance between rings ✓ Working pressure by rules ✓ End plates: Thickness ✓ How stayed ✓
 Working pressure of end plates ✓ Area of safety valves to superheater ✓ Are they fitted with easing gear ✓

If not, state whether, and when, one will be sent? In a Report also sent on the Hull of the Ship?

VERTICAL DONKEY BOILER— Manufacturers of Steel

No. _____ Description _____

Made at _____ By whom made _____ When made _____ Where fixed _____

Working pressure tested by hydraulic pressure to _____ Date of test _____ No. of Certificate _____ Fire grate area _____ Description of Safety _____

Valves _____ No. of Safety Valves _____ Area of each _____ Pressure to which they are adjusted _____ Date of adjustment _____

If fitted with easing gear _____ If steam from main boilers can enter the donkey boiler _____ Dia. of donkey boiler _____ Length _____

Material of shell plates _____ Thickness _____ Range of tensile strength _____ Descrip. of riveting long. seams _____

Dia. of rivet holes _____ Whether punched or drilled _____ Pitch of rivets _____ Lap of plating _____ Per centage of strength of joint _____ Rivets _____ Plates _____

Working pressure of shell by rules _____ Thickness of shell crown plates _____ Radius of do. _____ No. of stays to do. _____ Dia. of stays _____

Diameter of furnace Top _____ Bottom _____ Length of furnace _____ Thickness of furnace plates _____ Description of joint _____

Working pressure of furnace by rules _____ Thickness of furnace crown plates _____ Stayed by _____

Diameter of uptake _____ Thickness of uptake plates _____ Thickness of water tubes _____ Dates of survey _____

SPARE GEAR. State the articles supplied:— *Two each top and bottom end connecting rod bolts nuts*
Two main bearing bolts and nuts, one set
coupling bolts and nuts, one set feed bilge pump
valves, and a quantity of assorted bolts nuts etc.

FOR EARLE'S
SHIPBUILDING & ENGINEERING CO. LIMITED.
J. Lounsbury
MANAGER.

The foregoing is a correct description,
 Manufacturer.

Dates of Survey while building	During progress of work in shops—	1904: May 4. 11. 20. 27. Jun 14. 20. 24. 27. July 5. 19. 26. 29. Aug 4. 6. 19. 31. Sep 6. 14. 22. 27. Oct 3. 14. 18. 21.
	During erection on board vessel—	Oct 26. 31. Nov 3. 15. 18. 27. 28. Dec 2. 9. 1905: Jan 20. 1906: Mar 23. May 11. 22. Jun 7. 9. 11. 17. 18. July 19. 24. 27. Aug 16. 17. 18.
	Total No. of visits	49

Is the approved plan of main boiler forwarded herewith *Yes*
 " " " donkey " " " *Yes*

Dates of Examination of principal parts—					
Cylinders	Slides	Covers	Pistons	Rods	
Connecting rods	Crank shaft	Thrust shaft	Tunnel shafts	Screw shaft	7.7.06 Propeller 18.8.06
Stern tube	7.7.06	Steam pipes tested	19.7.06	Engine and boiler seatings	7.7.06 Engines holding down bolts 24.7.06
Completion of pumping arrangements	16.8.06	Boilers fixed	16.8.06	Engines tried under steam	16.8.06
Main boiler safety valves adjusted	20.7.06	Thickness of adjusting washers	Star $\frac{9}{32}$ " Port $\frac{1}{4}$ "		
Material of Crank shaft	Iron	Identification Mark on Do.	1434. T.F	Material of Thrust shaft	Iron Identification Mark on Do. 253
Material of Tunnel shafts	Iron	Identification Marks on Do.	253	Material of Screw shafts	Iron Identification Marks on Do. 253
Material of Steam Pipes	Solid drawn Copper		Test pressure	360 lbs \square	

General Remarks (State quality of workmanship, opinions as to class, &c. *The engines and boilers*)
 of this vessel have been constructed under special survey in accordance with the Rules. The materials and workmanship are good. The boilers tested by hydraulic pressure, and with the engines fitted on board ^{tested under steam} and found satisfactory. They are now in good order and safe working condition, and respectfully submitted as being eligible in our opinion to be classed with the notation of *K.L.M. 6.8.06* in the Register Book

It is submitted that this vessel is eligible for THE RECORD *H.L.M.C. 8.06*

The amount of Entry Fee..	£ 1 : - : -	When applied for,	28/8/1906
Special	£ 12 : - : -		
Donkey Boiler Fee .. .	£ - : - : -	When received,	29.8.96
Travelling Expenses (if any)	£ - : 14 : 8		

James Barclay and *James Kerr*
 Engineer Surveyors to Lloyd's Register of British & Foreign Shipping.

Committee's Minute **FRI. 31 AUG 1906**
 Assigned *+ H.M.C. 8.06*

