

EFFECTIVE AREA OF STAYS		
DIAM.	6 THREADS.	9 THREADS.
3/4"	7.24"	
3/8"	6.66"	
3"	6.10"	
2 1/4"	3.26"	
2 3/8"		3.09"
1 7/8"		2.36"
1 3/4"		2.03"
1 5/8"		1.73"

TESTS OF MATERIAL	
SHELL PLATES	30 To 34 TONS
BUTT STRAPS	Do
COMP ⁵ PLATE	27 To 30 "
ALL COMB. PLATES	26 To 30 "
FLANGING PLATES	Do
NANHOLE DOORS	28 To 32 "
GIRDER BARS	Do
LONGIT. STAYS	Do

483-4

Date 2/2/10

Drawn by }
Checked by } J. Brown

ENGINES N^{os} 483-4.

MAIN BOILER.

3-OFF. for each ship.

$$\begin{array}{r} 31 \\ \hline 483-4 \end{array}$$

From BARCLAY, CURLE & CO., Ltd.,
STOBCROSS ENGINE WORKS,

Enclosure.

Lloyd's Surveyors

W1637-02782

Barclay Curle


N^o 483-4

215 lb per 0"

Please return drawing
for 484.

GLASGOW REPORT No. 29384.

1/8 "b hilka"
N^o 483.



RETAIN



© 2021

Lloyd's Register
Foundation

8270-6391