

Rpt. 12.

COPY.

# FREEBOARD VERIFICATION FORM FOR STEAMERS.

Port **Belfast.**

When received in London Office

Vessel's Name **"M O O L T A N"**

Official No. **145435**

No. in Reg. Book **27854**

Port of Registry (For Foreign Vessels) **Belfast.**

Iron or Steel **Steel** State whether Classed by Lloyd's Register **Contemp.**

Name of Owners Date of Verification **20. 9. 23.**

I have to report that the Freeboard from the centre of disc to the top of the statutory deck line, and the lines in connection therewith, as given below, assigned by the Committee to this vessel, have been correctly marked on the vessel's sides, in accordance with the printed instructions:—

From centre of disc to top of statutory deck line --- ft. --- ins.

From centre of disc to top of statutory deck line } **18** ft. **4½** ins.  
at ~~awning or part-awning~~ deck . . . }

Fresh Water line above centre of disc . . . **8½** ins.

Indian Summer line above centre of disc . . . **8½** ins.

Winter line below centre of disc . . . **9** ins.

Winter North Atlantic line below centre of disc --- ins.

Distance between the top of statutory deck line on vessel's side and the intersection of the continuation of upper side of } at main, spar or upper dk. --- ins.  
**2½** wood on steel deck with the vessel's side } **Upper Shelter**  
at ~~awning or pt. awning~~ dk. **½** ins.

NOTE.—It should be clearly shown whether the statutory deck line is set off from a wood or steel deck.

(Signed) **S.O. KENDALL.** Surveyor.

(To be filled up in London Office.)

Statement No. Date of Committee's Minute **15. 10. 23.**

Particulars for record in Register Book { Moulded Depth . . . **52** ft. **8** ins.  
Freeboard . . . **18** ft. **4½** ins.  
Corresponding Draught ft. ins.

Freeboards compared and found correct by Date

Is fee paid? Form for Certificate

Instructions Date

Certificate written Noted for posting

m, 11, 21.—T.

Spacing

27 9 24

27 9 24

Deck. Material and thickness **Steel 38 sheet**

Condition of class



© 2021

Lloyd's Register Foundation

W1650-0373