

GENERAL REMARKS—(continued).

Particulars of Watertight Bulkheads.

N^o 1 Collision B.H. Stiffs in F. Plank 5 1/2 x 2 1/2 x 35 O.A. spaced 30' apart. B.K.T. top & bottom. Stiffs in Chain Locker 8 x 3 x 9/20 B.A. and 3 Webs formed by centre division and sides of Chain Locker. B.K.T. on Stiffs top & bottom. Stiffs 2nd to upper 5th 5 x 3 x 35 O.A. spaced 30' apart. Plating of Bulkhead lower 9/20 upper 7/20.

N^o 2 Lower Stiffs 11 x 3 1/2 x 50 B.A. 27' apart. Twelve 5th same as lower, one on each side 12 x 4 x 4 x 55 Channel. Plating 40'.

N^o 3 Lower Stiffs 10 x 3 1/2 x 55, 30' apart at sides 27' in centre. 1/2nd Stiffs 5 x 3 x 30, 30' apart, all bracketed top and bottom. Plating 7/20.

N^o 4 Lower Stiffs 7 x 3 1/2 x 45 B.A. with transverse bars 3 1/2 x 3 1/2 x 50 spaced 27' B.K.T. top & bottom. 1/2nd Stiffeners 5 x 2 1/2 x 35 O.A. spaced 27' B.K.T. top & bottom.

N^o 5 Lower Stiffs 9 x 3 1/2 x 50 spaced 24' B.A. B.K.T. top & bottom. 1/2nd Stiffs 5 x 2 1/2 x 35 O.A., 24' apart. B.K.T. top & bottom. Plating 7/20 - 5/20.

N^o 6 Lower Stiffs 7 x 3 1/2 x 45 B.A., 24' apart. plating 7/20 B.K.T. top & bottom. 1/2nd Stiffeners 3 x 2 1/2 x 30 O.A. 24' 5th 5/20 - bottom.

The above stiffeners are fitted on both sides of bulkhead.

N^o 7 Lower Stiffs 8 x 3 x 45 B.A. spaced 24' plating 7/20 B.K.T. top & bottom. 1/2nd Stiffs 5 x 2 1/2 x 35 O.A. 24' 5th 5/20 5th bottom.

N^o 8 After Peak Stiffs 5 x 2 1/2 x 9/20 O.A. B.K.T. top. plating 35. B.K.T. at top.

Handwritten notes in reverse of page, mostly illegible due to bleed-through from the other side.

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 379.75 ft., Bridge 57.5 ft., Forecastle 57.5 ft. and Poop and Bridge combined.

(in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated.

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) 20th 57L

Official No. _____; Signal Letters _____ State if Machinery is fitted aft no

How are the surfaces preserved from oxidation? Inside Paint + Cement Outside Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors. Cellular

Where Fitted.	Length.	Water Capacity.	Where Fitted.	Length.	Water Capacity.
	Feet.	Tons.		Feet.	Tons.
Double bottom, aft,		633	Fore peak tank,		32
Double bottom, under Engines and Boilers,		188	After peak tank,		8
Double bottom, if under Engines only,		156	Deep tank, aft,		-
Double bottom, if under Boilers only,		466	Deep tank, forward,		-
Double bottom, forward,		1443	Other tanks, if fitted,		-
Total capacity of double bottom		2923	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks. State whether the above have been tested as required by the Rules. Yes, except 2

Order for Special Survey No. _____

Date 1921. June 7. 9. 10. 11. 13. 14. 16. 17. 20. 21. 22. 23. 24. 28. 29.

No. _____ in builder's yard.

DATES of Surveys held while building July 1st

Surveyor's Signature Matthew Blackwood

Total No. of Visits 17