

REPORT ON ELECTRIC LIGHTING INSTALLATION. No. 25955

Port of SUNDERLAND Date of First Survey 15 Dec Date of Last Survey 22 Dec 13 No. of Visits 3
 No. in Reg. Book on the Iron or Steel S.S. "Mottisfont" Port belonging to LONDON
 Built at SUNDERLAND By whom J. L. Thompson & Son When built 1913-12
 Owners Century Shipping Co. (Marine Insurance) Owners' Address _____
 Yard No. 501 Electric Light Installation fitted by Sunderland Forge & Eng. Co. Ltd. When fitted 1913

DESCRIPTION OF DYNAMO, ENGINE, ETC.

One Multipolar Compound wound dynamo coupled direct to open type engine.

Capacity of Dynamo 120 Amperes at 100 Volts, whether continuous or alternating current Continuous ✓
 Where is Dynamo fixed Starboard Side Bottom E.R. Whether single or double wire system is used Double ✓
 Position of Main Switch Board Close to plant having switches to groups Five of lights, &c., as below
 Positions of auxiliary switch boards and numbers of switches on each One in Chartroom controlling 2 side
2 mast, 1 stern and 1 compass.

If fuses are fitted on main switch board to the cables of main circuit Yes and on each auxiliary switch board to the cables of auxiliary circuits Yes and at each position where a cable is branched or reduced in size Yes and to each lamp circuit Yes
 If vessel is wired on the double wire system are fuses fitted to both flow and return wires or cables of all circuits including lamp circuits Yes
 Are the fuses of non-oxidisable metal Yes and constructed to fuse at an excess of 100% ✓ per cent over the normal current
 Are all fuses fitted in easily accessible positions Yes Are the fuses of standard dimensions No If wire fuses are used are permanent instructions fitted on or near each switch board giving particulars of proper size of fuse for each circuit Yes
 Are all switches and fuses constructed of incombustible materials and fitted on incombustible bases _____

Total number of lights provided for 163 arranged in the following groups:—

Group	Description	Wires	Current (Amperes)	Notes
A	60 lights each of 16 candle power	14	33.6	requiring a total current of 33.6 Amperes
B	13 lights each of 16 candle power	16	7.28	requiring a total current of 7.28 Amperes
C	19 lights each of 16 candle power	20	10.64	requiring a total current of 10.64 Amperes
D	32 lights each of 16 candle power	18	17.92	requiring a total current of 17.92 Amperes
E	39 lights each of 16 candle power	16	21.84	requiring a total current of 21.84 Amperes
2	Mast head light with 1 lamp each of 32 D.F.	1	1.12	requiring a total current of 1.12 Amperes
2	Side light with 1 lamp each of 32 D.F.	1	1.12	requiring a total current of 1.12 Amperes
6	Cargo lights of 5 x 32 candle power	16	incandescent	whether incandescent or arc lights

If arc lights, what protection is provided against fire, sparks, &c. _____

Where are the switches controlling the masthead and side lights placed in Chartroom.

DESCRIPTION OF CABLES.

Description	Current (Amperes)	Wires	Wires per Cable	S.W.G. diameter	Total sectional area (square inches)
Main cable carrying	91.28	19	14	.094	square inches total sectional area
Branch cables carrying	33.6	7	16	.022	square inches total sectional area
Branch cables carrying	17.92	7	20	.007	square inches total sectional area
Leads to lamps carrying	2.24	1	18	.0018	square inches total sectional area
Cargo light cables carrying	5.6	1	16	.0032	square inches total sectional area

DESCRIPTION OF INSULATION, PROTECTION, ETC.

In berths etc., Lead covered.
 In Engine room etc., Lead covered armoured.
 Mains V.I.R. Masts Lead covered armoured.

Joints in cables, how made, insulated, and protected

There are none

Are all the joints of cables thoroughly soldered, and the flux used not containing acids or other corrosive substances _____ Are all joints in accessible positions, none being made in bunkers, cargo spaces, or spaces which may at any time be used for carrying cargo, stores, or baggage _____

Are there any joints in or branches from the cable leading from dynamo to main switch board No.

How are the cables led through the ship, and how protected V.I.R. in iron pipe.



© 2019

Lloyd's Register Foundation

W200-0143

DESCRIPTION OF INSULATION, PROTECTION, ETC.—continued.

Are they in places always accessible Yes.

What special protection has been provided for the cables in open alleyways or where exposed to weather or moisture Lead covered armoured.

What special protection has been provided for the cables near galleys or oil lamps or other sources of heat Lead covered armoured.

What special protection has been provided for the cables near boiler casings Lead covered armoured.

What special protection has been provided for the cables in engine room Lead covered armoured.

How are cables carried through beams holes pushed fibre through bulkheads, &c. W.T. Glands.

How are cables carried through decks W.T. in deck tubes.

Are any cables run through coal bunkers Yes or cargo spaces Yes or spaces which may be used for carrying cargo, stores, or baggage Yes

If so, how are they protected V.I.R. in iron pipe.

Are any lamps fitted in coal bunkers or spaces which may at times be used for cargo, coals, or baggage No.

If so, how are the lamp fittings and cable terminals specially protected

Where are the main switches and fuses for these lights fitted

If in the spaces, how are they specially protected

Are any switches or fuses fitted in bunkers No.

Cargo light cables, whether portable or permanently fixed Portable How fixed

In vessels fitted on the single wire system, how is the dynamo terminal fixed to the hull of vessel

How are the returns from the lamps connected to the hull

Are all the joints with the hull in accessible positions

Is the installation supplied with a voltmeter Yes, and with an amperemeter Yes, fixed Switchboard

VESSELS BUILT FOR CARRYING PETROLEUM.

In vessels built for carrying petroleum, are all switches and fuses fitted in positions not liable to the accumulation of petroleum vapour or gas

Are any switches, fuses, or joints of cables fitted in the pump room or companion

How are the lamps specially protected in places liable to the accumulation of vapour or gas

The copper used is guaranteed to have a conductivity of not less than that of the Engineering Standards Committee's standard, and the wires are protected by tinning from the sulphur compounds present in the insulating material.

Insulation of cables is guaranteed to have a resistance of not less than 500 megohms per statute mile at 60° Fahrenheit after 24 hours' immersion in water, the test being made after one minute's electrification at not less than 500 volts and while the cable is still immersed.

The foregoing statements are a correct description of the Electric Light installation fitted by us on this vessel and we declare that it is at this date in good order and safe working condition.

P. PRO THE SUNDERLAND FORCE OF ENGINEERS Electrical Engineers Date 8/1/14.

COMPASSES.

Distance between dynamo or electric motors and standard compass Directly about 100 ft.

Distance between dynamo or electric motors and steering compass about 96 feet.

The nearest cables to the compasses are as follows:—

A cable carrying	<u>2.24</u>	Amperes	<u>4</u>	feet from standard compass	<u>led into</u>	feet from steering compass
A cable carrying	<u>2.24</u>	Amperes	<u>4</u>	feet from standard compass	<u>4</u>	feet from steering compass
A cable carrying		Amperes		feet from standard compass		feet from steering compass

Have the compasses been adjusted with and without the electric installation at work at full power yes

The maximum deviation due to electric currents, etc., was found to be no degrees on any course in the case of the standard compass and no degrees on any course in the case of the steering compass.

JOSEPH L. THOMPSON & SONS, Limited

M. J. Orr Builder's Signature. Date Jan 13 1914

GENERAL REMARKS.

Managing Director

This installation as far as could be seen has been fitted in accordance with the requirements of the Rules, it has been examined under working conditions & found satisfactory

It is submitted that this vessel is eligible for

THE RECORD, Elec. light.

J.W.D.

Surveyor to Lloyd's Register of British and Foreign Shipping.

Committee's Minute

THE SURVEYORS ARE REQUESTED NOT TO WRITE ACROSS THIS MARGIN.

Im. 9.12.—Transfer.



© 2019

Lloyd's Register Foundation