

ALL ANGLES ARE N.B.S

MASTS WINCHES WINDLASS STEERING GEAR & DECKHOUSES  
SUPPORTED TO SURVEYORS SATISFACTION.

for cantilever brackets  
in 4th. lower 11/1/39

SHELL AT BOW

SHEER 90°

FOUR SIDES 27

1/2 END 26  
50 2 3 29  
10 APPART

W.T. BOW 127

Stays & hatch angles slanted  
or welded

Angles & stays  
as per drawings

Dimensions 17.6 and 2

1/2 in or more as 1" if  
not butt welded  
with 2 in.

Stays & hatch angles  
slanted or welded

FOUR SIDES  
18 39  
7 3/4 RVS.

No SHELL CONNECTION  
TO STANCHIONS IN DECKS  
SHELL INCISED 1/2 in  
BELOW L.W.L.

25  
18 39  
7 3/4 RVS.

APPROVED  
LLOYD'S REGISTER OF SHIPPING


Lloyd's Register  
of Shipping



BURNT ISLAND S. B. Loy

N<sup>o</sup> 231-2

Profile & Decks Whit Section  
36

No. 231 n " bo marsh " 

Lth. Rpt. No. 19960.

No 232 s/s " Cornead "

Lth Rpt no 19948



© 2019

Lloyd's Register  
Foundation

W21-0277