

Rpt. 13.

No. 41353.

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

11 NOV 1930

Date of writing Report 10.11.1930 When handed in at Local Office 10 Nov. 1930 Port of HULL

No. in Survey held at HULL Date, First Survey 27 Oct. Last Survey 11 Nov. 1930

Reg. Book. 62205 on the STEAM TRAWLER "RYLSTON" Tons { Gross 380.11 Net 153.62

Built at Beverley By whom built Cook, Welton & Gemmill Ltd. Hard No. 556 When built 1930

Owners Henriksen & Co. Ltd. Port belonging to Hull

Electric Light Installation fitted by W. Broady & Son Contract No. - When fitted 1930

Is the Vessel fitted for carrying Petroleum in bulk No.

System of Distribution Two wire

Pressure of supply for Lighting 100 volts, Heating ✓ volts, Power ✓ volts.

Direct or Alternating Current, Lighting Direct current Power ✓

If alternating current system, state frequency of periods per second ✓

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off Yes

Generators, do they comply with the requirements regarding rating Yes, are they compound wound Yes

are they over compounded 5 per cent. Yes, if not compound wound state distance between each generator ✓

Where more than one generator is fitted are they arranged to run in parallel ✓, is an adjustable regulating resistance fitted in series with each shunt field Yes

Are all terminals accessible, clearly marked, and furnished with sockets Yes, are they so spaced or shielded that they cannot be accidentally earthed, short circuited, or touched Yes

Position of Generators Starboard side of engine room, Are the lubricating arrangements of the generators as per Rule Yes

is the ventilation in way of the generators satisfactory Yes, are they clear of all inflammable material Yes

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators ✓

and ✓, are the generators protected from mechanical injury and damage from water, steam or oil Yes

are their axes of rotation fore and aft Yes

Earthing, are the bedplates and frames of the generating plant efficiently earthed Yes, are the prime movers and their respective generators in metallic contact Yes - direct coupled.

Main Switch Boards, where placed Beside generator in engine room.

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard ✓

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes Yes

are they protected from mechanical injury and damage from water, steam or oil Yes, if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards ✓ and ✓

are they constructed wholly of durable, non-ignitable non-absorbent materials Yes, is all insulation of high dielectric strength and of permanently high insulation resistance Yes

if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework ✓

and is the frame effectively earthed Yes. Are the fittings as per Rule regarding: - spacing or shielding of live parts

Yes, accessibility of all parts Yes, absence of fuses on back of board Yes, proportion of omnibus bars Yes

Yes, individual fuses to voltmeter, pilot or earth lamp Yes, connections of switches Yes

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches S.P. linked

switch for generator. Outgoing circuits controlled by S.P. switches and protected by fuses on each pole.


Instruments on main switchboard One ammeters One voltmeters - synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

Earth lamps with separate switches

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules Yes

Point Boxes Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule Yes.



© 2020

Lloyd's Register Foundation

W221-0045 1/2

Cables: Single, twin, concentric, or multicore Twin are the cables insulated and protected as per Tables IV or V of the Rules Yes

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load 1 volt

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets Yes

Paper Insulated Cables, If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound None

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage Yes

Support and Protection of Cables, state how the cables are supported and protected Armoured cable with L.S. clips
L.C. cable with brass clips

If cables are run in wood casings, are the casings and caps secured by screws , are the cap screws of brass , are the cables run in separate grooves . If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII Yes

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements None

Joints in Cables, state if any, and how made, insulated, and protected No joints

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands Yes

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed Yes state the material of which the bushes are made Lead

Earthing Connections, state what earthing connections are fitted and their respective sectional areas through earth lamps

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule Yes, are their connections made as per Rule Yes

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven None

Navigation Lamps, are these separately wired Yes, controlled by separate switch and separate fuses Yes, are the fuses double pole Yes, are the switches and fuses grouped in a position accessible only to the officers on watch Yes

has each navigation lamp an automatic indicator as per Rule No

Secondary Batteries, are they constructed and fitted as per Rule

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight Yes, are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected None

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected None

how are the cables led None

where are the controlling switches situated None

Searchlight Lamps, No. of 1, whether fixed or portable , are their fittings as per Rule

Arc Lamps, other than searchlight lamps, No. of 0, are their live parts insulated from the frame or case , are their fittings as per Rule

Motors, are their working parts readily accessible , are the coils self-contained and readily removable for replacement

are the brushes, brush holders, terminals and lubricating arrangements as per Rule , are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material

are they protected from mechanical injury and damage from water, steam or oil , are their axes of rotation fore and aft

if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type

are they protected from mechanical injury and damage from water, steam or oil , if not of this type, state distance of the combustible material horizontally or vertically above the motors None and

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	<u>one</u>	<u>6</u>	<u>100</u>	<u>60</u>	<u>350</u>	<u>Steam engine</u>		
AUXILIARY								
EMERGENCY								
ROTARY TRANSFORMER								

GENERATOR, LIGHTING AND HEATING CONDUCTORS.

DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT AMPERES.		Approximate Length (Lead and Return) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Effective Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
MAIN GENERATOR	<u>2</u>	<u>0.064</u>	<u>19</u>	<u>60 mg.</u>	<u>60</u>	<u>1</u>	<u>24</u>	<u>P.I.R.</u>	
EQUALISER CONNECTIONS									
AUXILIARY GENERATOR									
EMERGENCY GENERATOR									
ROTARY TRANSFORMER MOTOR GENERATOR									
ENGINE ROOM	<u>2</u>	<u>0.0018</u>	<u>3</u>	<u>20"</u>	<u>3.5</u>	<u>1</u>	<u>20</u>	<u>"</u>	<u>L.C. armoured</u>
BOILER ROOM	<u>2</u>	<u>0.0018</u>	<u>3</u>	<u>20"</u>	<u>1.5</u>	<u>1</u>	<u>40</u>	<u>"</u>	<u>"</u>
AUXILIARY SWITCHBOARDS									
ACCOMMODATION	<u>2</u>	<u>0.012</u>	<u>7</u>	<u>18"</u>	<u>12</u>	<u>1</u>	<u>50</u>	<u>"</u>	<u>L.C.</u>
Navigation Main	<u>2</u>	<u>0.007</u>	<u>7</u>	<u>20"</u>	<u>5</u>	<u>1</u>	<u>150</u>	<u>"</u>	<u>L.C. armoured</u>
WIRELESS	<u>2</u>	<u>0.012</u>	<u>7</u>	<u>18"</u>	<u>10</u>	<u>1</u>	<u>150</u>	<u>"</u>	<u>"</u>
SEARCHLIGHT	<u>2</u>	<u>0.0018</u>	<u>3</u>	<u>20"</u>	<u>1</u>	<u>1</u>	<u>180</u>	<u>"</u>	<u>"</u>
MASTHEAD LIGHT	<u>2</u>	<u>0.0018</u>	<u>3</u>	<u>20"</u>	<u>1</u>	<u>1</u>	<u>30</u>	<u>"</u>	<u>L.C.</u>
SIDE LIGHTS	<u>2</u>	<u>0.0018</u>	<u>3</u>	<u>20"</u>	<u>1</u>	<u>1</u>	<u>30</u>	<u>"</u>	<u>"</u>
COMPASS LIGHTS									
POOP LIGHTS									
CARGO LIGHTS									
ARC LAMPS									
HEATERS									

MOTOR CONDUCTORS.

DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT AMPERES.		Approximate Length (Lead and Return) Feet.	Insulated with	HOW PROTECTED.
		No. per Pole.	Total Effective Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP										
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS										
AIR COMPRESSOR										
FRESH WATER PUMP										
ENGINE TURNING GEAR										
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS										
OIL FUEL TRANSFER PUMP										
WINDLASS										
WINCHES, FORWARD										
WINCHES, AFT										
STEERING GEAR—										
(a) MOTOR GENERATOR										
(b) MAIN MOTOR										
WORKSHOP MOTOR										
VENTILATING FANS										

All Conductors are of annealed copper conforming to British Standard Specification No. 7.

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

WM. BROADY & SONS
ENGLISH STREET,
WULF.

Electrical Engineers.

Date Nov. 11th 1930.

COMPASSES.

Distance between electric generators or motors and standard compass 68 ft.

Distance between electric generators or motors and steering compass

The nearest cables to the compasses are as follows:—

A cable carrying 0.5 Ampères To feet from standard compass ✓ feet from steering compass.

A cable carrying 0.5 Ampères To feet from standard compass ✓ feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted yes

The maximum deviation due to electric currents was found to be no degrees on any course in the case of the standard compass, and no degrees on any course in the case of the steering compass.

COOK, WELTON & GEMMELL LTD.

ad Campbell
CHIEF DRAFTSMAN.

Builder's Signature.

Date 6/11/30

Is this installation a duplicate of a previous case Yes If so, state name of vessel "Monimia"

General Remarks (State quality of workmanship, opinions as to class, &c. The electrical installation of this vessel has been fitted on board under special survey, the materials and workmanship being sound & good. It has been tried under full working conditions and found in good order and is eligible, in my opinion, to have record of "Electric Light"

It is submitted that this vessel is eligible for THE RECORD. Elec Light.

J. 13/11/30

Total Capacity of Generators 6 Kilowatts.

The amount of Fee ... E.L. £ 3 : 0 : 10 Nov 1930

Travelling Expenses (if any) £ : : 11.12.30

b. Moffatt.

Surveyor to Lloyd's Register of Shipping.

Committee's Minute TUE. 18 NOV 1930

Assigned Elec Lt

Im. 11.20.—Transfer. (The Surveyors are requested not to write on or below the space for Committee's Minute.)



© 2020

Lloyd's Register Foundation