

Q2662 ADV 100
FRI MAY 7 1960

State if Report is also sent on the Machinery of the Vessel **Yes**

No. 4928

Last Survey March 2nd.

1920

CLASS ~~100A1~~

FEET.

Master G. M. Frargopoulos

Year of appointment	(1) As Master in service of owner of present vessel:—18
	(2) As Master of this vessel:—18

Built at **Hong Kong**

When built 1920 Launched Dec. 16th. 1919

By whom built Hong Kong & Whampoa Dock Co. Ltd.

Owners Evangelos E. Ambatielos
ex The Shipping Controller

Managers

Residence Argostoli, Greece

Port belonging to Argostoli

Master Tonnage } 3307.43

Destined Voyage Karachi

If Surveyed while Building, Afloat, or in Dry Dock **Building & Afloat**

LENGTH on Deck as per Rule	Feet. 400	Inches. 0	BREADTH— Moulded	Feet. 52	Inches. 0	DEPTH, ACTUAL—Top of Floors to top of Upper Dk. Beams Do. do. do. do. Second Dk. Beams	Feet. 28	Inches. 6	No. of Decks with flat laid	TWO
									No. of Tiers of Beams	TWO

Dimensions of Ship per Register, Length 400.2' breadth 52.2' depth 28.5'

FRAMING.							PILLARS.						
	Inches in Ship.	Inches in Ship.	Inches in Ship.	Inches per Rule Or as	Inches per Rule Approved.		Inches Size in Ship.	Inches Spacing in Ship.	Inches per Rule Or as	Inches per Rule Approved.			
FRAME, Angles, or E or L Bars amidships	10	3 1/2	46	10	3 1/2	46	PILLARS In 'tween Deck, size and spacing	3 1/2 Dia	52"	3 1/2 Dia	52"		
Do. in peaks	8	3	38	8	3	38	" " Hold	5 1/2 Dia	52"	5 1/2 Dia	52"		
Do. in way of Double Bottoms at Solid Floors...	3 1/2	3 1/2	40	3 1/2	3 1/2	40	" Quarter 'tween Dks., as	2 Ls 6x3 1/2 x 50	2 Ls 6x3 1/2 x 50	2 Ls 6x3 1/2 x 50	2 Ls 6x3 1/2 x 50		
" " at intermdt. Bkts.	9	3 1/2	42	9	3 1/2	42	" in Hold Apprvd	4 Ls 6x6 x 60	4 Ls 6x6 x 60	4 Ls 6x6 x 60	4 Ls 6x6 x 60		
Spacing of Frames from centre to centre amidships	26"			26"			KEELSONS & STRINGERS.						
" " from 1/2 length to Collision bulkhead	26"			26"			CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercostal Plate						
" " in peaks..	24"			24"			Rider Plate.....						
REVERSED FRAME, Angles.....	-			-			Flat Plate Keel Angles						
Do. in way of Double Bottoms at Solid Floors...	3 1/2	3 1/2	40	3 1/2	3 1/2	40	Horizontal Plates on Floors.....						
" " at intermdt. Bkts.	8	3	46	8	3	46	Angles or Bulb Angles						
FRAMING, depth of girder	10"			10"			SIDE KEELSONS, Number						
FLOORS, depth and thickness of Floor Plate at mid-line for 1/2 length amidships...}							Angles or Bulb Angles						
" in way of Engine and Boiler Spaces							Plate above floors, for length...						
" thickness at the ends of vessel							Intercostal Plate, for length						
" depth at 1/2 the half breadth, as per Rule ...							Attached to outside Plating with Angle...						
" height extended at the Bilges							BILGE KEELSON, Angles						
FLOORS in Cell. Double Bottoms.....	42	38	Ends	50	BS	42	Intercostal Plate for length						
" state if flanged (top & bottom).....	No			No			Attached to outside Plating with Angle ...						
" every frame E.S. & S.L. }	78"			78"			SIDE STRINGERS, Number						
" forming of Solid Floors }	43x.50 (1/2 L)	40	Ends	60	BS		Angles						
CENTRE GIRDER, in Dbl. bottom, dpth. & thickness.	6	6	66	6	6	66	Intercostal Plate, for length ...						
" Angles, Top Single	6	6	66	6	6	66	Attached to outside plating with Angle.....						
" " Bottom Single	6	6	46	6	6	46	Upper Deck Stringer Plate, br'dth & thickness (clear of Bridge)						
" " to Floors	39"	42	38	39	42	38	" " " " br'dth & thickness (in way of Bridge)						
" Brackets at intermdt. frmng., wdth & thkns	One	42	38	One	42	38	" " " " Angle (clear of Bridge) ...						
SIDE GIRDERS, number on each side & thickness	Flanged top only						" " Tie Plate at sides of Hatchways.....						
" state if flanged (top and bottom)	3 1/2	3 1/2	40	3 1/2	3 1/2	40	Deck * Iron or Steel, for Whole lng.						
" Angles (top and bottom)	3 1/2	3 1/2	40	3 1/2	3 1/2	40	" Thickness (clear of Bridge)						
" " to Floors.....	3 1/2	3 1/2	40	3 1/2	3 1/2	40	" " (in way of Bridge)						
MARGIN PLATE, depth (exclusive of flange) and thickness.....}	40 1/2"	x	48	40 1/2"	x	48	Wood Deck. Material & thickness						
" Angle to Outside Plating.....	3 1/2	3 1/2	50	3 1/2	3 1/2	50	Second Deck Stringer Plate, br'dth & thickness						
" " Floors	3 1/2	3 1/2	40	3 1/2	3 1/2	40	Angles on ditto, No. Two						
" Brackets at intermdt. frmng., wdth & thkns	39"	42	38	39"	42	38	Tie Plates outside Hatchways						
" Height of Outside Brackets above at bilge	38"			38"			Deck * Iron or Steel, for Whole lng.						
INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake	43"x.50	40	43"x.50	40	Ends		Wood Deck. Material & thickness						
" " in Engine and Boiler space	48	ES	56	BS	48	ES	Hard Deck Stringer Plate, br'dth & thickness						
" " Remainder in Holds.....	42	38	Ends	42	38	Ends	Angles on ditto, No.						
BEAMS, Upper Deck, Single Angle, Bulb Angle, Plate, Tee Bulb, or Channel	9	3 1/2	52	9	3 1/2	52	Tie Plates, outside Hatchways.....						
" In way of Long Bridge	9	3 1/2	52	9	3 1/2	52	Deck * Material and thickness						
" Spacing	26"			26"			Fourth and Fifth Deck Stringer Plate, breadth & thickness}						
BEAMS, Second Deck, Single Angle, Bulb Angle, Plate, Tee Bulb, or Channel	10	3 1/2	56	10	3 1/2	56	Angles on ditto, No.						
" Spacing	26"			26"			Tie Plates outside Hatchways						
BEAMS, Third and Fourth Deck, Single Angle, Bulb Angle, Plate, Tee Bulb, or Channel							Deck. Material & thickness.						
" Angles on upper edge							Poop Deck Stringer Plate, breadth & thickness						
" Spacing							Angle on ditto						
BEAMS, Poop Deck, Angle, Bulb Angle, Plate, Tee Bulb, or Channel	8	3	38	8	3	38	Tie Plates						
" Angles on upper edge							Deck. Material and thickness.						
" Spacing	26"			26"			Bridge Deck Stringer Plate, br'dth & thickness						
BEAMS, Bridge Deck, Angle, Bulb Angle, Plate, Tee Bulb, or Channel	9	3 1/2	52	9	3 1/2	52	Angles on ditto.....						
" Angles on upper edge							Tie Plates.....						
" Spacing	26"			26"			Deck. Material and thickness						
BEAMS, Forecastle Deck, Angle, Bulb Angle, Plate, Tee Bulb, or Channel	9	3 1/2	46	9	3 1/2	46	Forecastle Deck Stringer Plate, b'dth & th'kns						
" Angles on upper edge							Angles on ditto.....						
" Spacing	26"			26"			Tie Plates						
" "													

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 49.25 ft., R.Q.D. - ft., Bridge 112.7 ft., Forecastle 39.75 ft.
(in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated No

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 2 Dks. (Stl)

Official No.; Signal Letters

State if Machinery is fitted aft Amidships

How are the surfaces preserved from oxidation? Inside Two coats paint and cemented

Outside Two coats red Oxide & one finishing

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cellular

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	<u>123.5</u>	<u>380</u>	Fore peak tank,	<u>21.4</u>	<u>123</u>
Double bottom, under Engines and Boilers,	<u>39</u>	<u>155</u>	After peak tank,	<u>25.5</u>	<u>175</u>
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,	<u>177.6</u>	<u>585</u>	Other tanks, if fitted,		
Total capacity of double bottom		<u>1120</u>	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules. Yes

Order for Special Survey No.

Date Oct. 29th. 1918

No. 570 in builder's yard.

DATES OF SURVEYS
held while building

1919 Feb. 13, May 6, Jun. 6, 27, 30, July 7, 17, 22, 26, 31 Aug. 6, 8, 15
18, 25, 28, 30 Sept. 3, 5, 9, 11, 15, 18, 23, 24, 29 Oct. 2, 7, 8, 11, 15
22, 24, 30 Nov. 4, 5, 7, 12, 17, 24, 26, 28. Dec. 1, 2, 3, 5, 13, 16, 29.
1920 Jan. 5, 8, 9, 15, 23, 26, 28, Feb. 11, 13, 14, 16, 18, 19, 23, 24, 27
Mar. 2.

Total No. of Visits 66

Surveyor's Signature

John S. Gardiner

Lloyd's Register
Foundation