

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office.....

Date of writing Report

19

When handed in at Local Office

22/11/1924

Port of

NEWCASTLE-ON-TYNE

No. in Survey held at

Newcastle.

Date, First Survey

18 July

Last Survey

2 October 1924

Reg. Book. Supp.

(Number of Visits.....)

90919 on the

S. S. Dalamba

Tons { Gross
Net

Built at

Newcastle.

By whom built

Hawthorn Leslie & Co. Ltd.

Yard No.

533.

When built

1924

Owners

British India Steam Nav. Co. Ltd.

Port belonging to

London.

Electric Light Installation fitted by

Hawthorn Leslie & Co. Ltd.

Contract No.

533. When fitted

1924

System of Distribution

Double wire system

Pressure of supply for Lighting

110

volts, Heating

110

volts, Power

110

volts.

Direct or Alternating Current, Lighting

Direct

Power

Direct

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off

Yes

Generators, do they comply with the requirements regarding overload

Yes

, are they compound wound

Yes

are they over compounded 5 per cent.

Yes

, if not compound wound state distance between each generator

Where more than one generator is fitted are they arranged to run in parallel

No

, is an adjustable regulating resistance fitted in

series with each shunt field

Yes

Are all terminals accessible and clearly marked

Yes

, are they so spaced or shielded that they cannot be accidentally earthed,

or short circuited

Yes

Are the lubricating arrangements of the generators as per Rule

Yes

Position of Generators

Engine Room Forward

is the ventilation in way of the generators satisfactory

Yes

, are they clear of all inflammable material

Yes

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

—

and

—

, are the generators protected from mechanical injury and damage from water, steam or oil

Yes

are their axis of rotation fore and aft

Yes

Earthing, are the bedplates and frames of the generating plant efficiently earthed

Yes

are the prime movers and

their respective generators in metallic contact

Yes

Main Switch Boards, where placed

Engine Room Forward

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes

Yes

are they protected from mechanical injury and damage from water, steam or oil

Yes

, if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards

—

and

—

are they constructed wholly of durable, incombustible non-absorbent materials

Yes

, is all insulation of high dielectric strength and of

permanently high insulation resistance

Yes

, if semi-insulating material is used, are all conducting parts connected to one pole

insulated from the slab with mica or micanite and the slab similarly insulated from its framework

Yes

, and is the

frame effectively earthed

Yes

Are the following fittings as per Rule, viz.:— spacing or shielding of live parts

Yes

, accessibility of all parts

Yes

, absence of fuses on back of board

Yes

, proportion of omnibus

bars

Yes

, individual fuses to voltmeter, pilot or earth lamp

Yes

, connections of switches

Yes

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

Main Switches are Double Pole linked with fuses, all outgoing circuits fitted with two way Single Pole Switches, & Double Pole Fuses.

Instruments on main switchboard

Two

ammeters

Two

voltmeters

—

synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

Earth lamps,


coupled to Earth through switches & fuses.

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules

Yes

Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule

Yes



© 2019

Lloyd's Register

W264-0231

Single
Insulation of Cables, state type of cables, single or twin and *Twins* are the cables insulated and protected as per Tables III or IV of the Rules *Yes*

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load *4 Volts*

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.007 square inch and above provided with soldering sockets *Yes*

Paper Insulated Cables, If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound *—*

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage *Yes*

Support and Protection of Cables, state how the cables are supported and protected *Cables run on metal trays, secured by Brass clips, with Brass screws & Nuts.*

If cables are run in wood casings, are the casings and caps secured by screws *—*, are the cap screws of brass *—*, are the cables run in separate grooves *—*. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VI *Yes*

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements *Yes*

Joints in Cables, state if any, and how made, insulated, and protected *None made.*

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands *Yes*

Bushes in Beams and Non-watertight Positions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed *Yes* state the material of which the bushes are made *Lead*

Earthing Connections, state what earthing connections are fitted and their respective sectional areas *None*
 , are their connections made as per Rule *—*

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule *Yes*

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven *Emergency Generator, fitted on Boat Deck (in Dummy Tunnel) Generator direct coupled to an "Aster" Paraffin Engine. Double pole, change over switch fitted, for Main Board or Emergency supply.*

Navigation Lamps, are these separately wired *Yes*, controlled by separate switch and separate fuses *Yes*
 are the fuses double pole *Yes*, are the switches and fuses grouped in a position accessible only to the officers on watch *Yes*
 has each navigation lamp an automatic indicator as per Rule *Yes*, are separate screens provided for the use of oil and electric side lights *Yes*
 are separate oil lanterns provided for the mast head lights and side lights *Yes*

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight *Yes*
 are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected *none fitted.*
 are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected *None fitted.*
 , how are the cables led *—*

where are the controlling switches situated *—*

Searchlight Lamps, No. of *—*, whether fixed or portable *—*, are their fittings as per Rule *—*

Arc Lamps, other than searchlight lamps, No. of *—*, are their live parts insulated from the frame or case *—*, are their fittings as per Rule *—*

Motors, are their working parts readily accessible *Yes*, are the coils self-contained and readily removable for replacement *Yes*
 are the brushes, brush holders, terminals and lubricating arrangements as per Rule *Yes*, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material *Yes*
 are they protected from mechanical injury and damage from water, steam or oil *Yes* are their axis of rotation fore and aft *Yes*
 if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type *Yes*, if not of this type, state distance of the combustible material horizontally or vertically above the motors *—* and *—*

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed as per Rule *Yes*

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule *—*

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings *—*

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office *—*

PARTICULARS OF GENERATING PLANT.									
DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY.	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.		
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.	
MAIN ...	2	70	110	636	450	Steam engine	—	—	
AUXILIARY ...	—	—	—	—	—	—	—	—	
EMERGENCY ...	1	16	110	145	1000	Petrol - Paraffin	Paraffin	—	
ROTARY TRANSFORMER	—	—	—	—	—	—	—	—	

LIGHTING AND HEATING CONDUCTORS.									
Ref. No.	DESCRIPTION.	No. of Conductors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Ampères.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
MAIN GENERATOR...	No. 1 (2 per pole)	4	0.49850	61	.103	600	54	V. F. R.	Lead covered.
MAIN GENERATOR...	No. 2 (2 per pole)	4	0.49850	61	.103	600	90	"	" "
EMERGENCY GENERATOR	2	2	0.30240	37	.103	145	30	"	" "
ROTARY TRANSFORMER...	—	—	—	—	—	—	—	—	—
AUXILIARY SWITCHBOARDS	—	—	—	—	—	—	—	—	—
ENGINE ROOM	2	2	0.03960	19	.052	45	40	"	Lead covered armoured & braided
BOILER ROOM	2	2	0.03960	19	.052	45	40	"	Lead covered.
1 st Class Officers Lighting	2	2	0.10090	19	.083	93	220	"	Lead covered.
2 nd Class Engineers Lighting	2	2	0.07592	19	.072	73	220	"	" "
Emigrants Lighting & Ventilating Fans	2	2	0.07592	19	.072	54.9	250	"	" "
Crew's Lighting	2	2	0.01462	7	.052	20.1	200	"	" "
Brine Pump & Saline Motor	2	2	0.02214	7	.064	25	200	"	" "
Emergency Lighting	2	2	0.01462	7	.052	15	80	"	Lead covered armoured & braided
Emergency Switchboard	2	2	0.01462	7	.052	16	200	"	Lead covered.
Navigation Lights } compasses etc.	2	2	0.02214	7	.064	8	320	"	" "
Motors for Hatch & Space Vent.	2	2	0.02214	7	.064	40	180	"	" "
WIRELESS	2	2	0.02214	7	.064	34	280	"	" "
SEARCHLIGHT	—	—	—	—	—	—	—	—	—
MASTHEAD LIGHT	2	2	0.00194	3	.029	1.2	600	"	Lead covered, & Lead covered
SIDE LIGHTS	2	2	0.00194	3	.029	1.2	90	"	Lead covered
COMPASS LIGHTS	2	2	0.00194	3	.029	1	30	"	armoured & braided
STERN LIGHT	2	2	0.00194	3	.029	1.2	600	"	Lead covered.
CARGO LIGHTS	2	2	0.02214	7	.064	27	200	"	" "
HEATERS A	2	2	0.03960	19	.052	41	250	"	Lead covered.
HEATERS B	2	2	0.14780	37	.072	145.5	320	"	" "
HEATERS C	2	2	0.03960	19	.052	54.5	180	"	" "
HEATERS	2	2	0.03960	19	.052	54.5	300	"	" "
HEATERS	2	2	0.10090	19	.083	109.00	220	"	" "

MOTOR CONDUCTORS.									
Ref. No.	DESCRIPTION.	No. of Motors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Ampères.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
—	BALLAST PUMP	—	—	—	—	—	—	—	—
—	MAIN BILGE LINE PUMPS	—	—	—	—	—	—	—	—
—	GENERAL SERVICE PUMP	—	—	—	—	—	—	—	—
—	EMERGENCY BILGE PUMP	1	0.07592	19	.072	90	240	V. F. R.	Lead covered.
—	SANITARY PUMP	—	—	—	—	—	—	—	—
—	CIRC. SEA WATER PUMPS	—	—	—	—	—	—	—	—
—	CIRC. FRESH WATER PUMPS	—	—	—	—	—	—	—	—
—	AIR COMPRESSOR	—	—	—	—	—	—	—	—
—	FRESH WATER PUMP	—	—	—	—	—	—	—	—
—	ENGINE TURNING GEAR	—	—	—	—	—	—	—	—
—	ENGINE REVERSING GEAR	—	—	—	—	—	—	—	—
—	LUBRICATING OIL PUMPS	—	—	—	—	—	—	—	—
—	OIL FUEL TRANSFER PUMP	—	—	—	—	—	—	—	—
—	WINDLASS	—	—	—	—	—	—	—	—
—	WINCHES, FORWARD	—	—	—	—	—	—	—	—
—	WINCHES, AFT	—	—	—	—	—	—	—	—
—	STEERING GEAR	—	—	—	—	—	—	—	—
—	WORKSHOP MOTOR	1	0.01046	7	.044	13.5	300	V. F. R.	Lead covered armoured & braided
—	VENTILATING FANS 2 H.P.	2	0.01046	7	.044	6	150	"	Lead covered
—	" " 3/4"	2	0.01046	7	.044	6	150	"	" "
—	" " 2 1/2"	2	0.01046	7	.044	20	50	"	" "
—	" " 1/2"	1	0.00299	3	.036	3	60	"	Lead covered armoured & braided
—	Brine Pump Motor	1	0.01046	7	.044	23.5	30	"	" "

All Conductors are of annealed copper conforming to British Standard Specification No. 7.
The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.
The foregoing is a correct description.

R. & W. HAWTHORN, LESLIE & CO LIMITED

John T. Galt
Electrical Engineers.

Date *19th Feb. 1924*

COMPASSES.

Distance between electric generators or motors and standard compass *Main Generators 145 ft. Wireless Motor 40 ft.*

Distance between electric generators or motors and steering compass *Main Generator 135 ft. Wireless Motor 35 ft.*

The nearest cables to the compasses are as follows:—

A cable carrying *1* Ampères *on the feet from* standard compass *8* feet from steering compass.

A cable carrying *1* Ampères *8* feet from standard compass *on the feet from* steering compass.

A cable carrying *8* Ampères *5* feet from standard compass *8* feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power. *Yes*

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted. *Yes*

The maximum deviation due to electric currents was found to be *Nil* degrees on *each* course in the case of the standard compass, and *Nil* degrees on *each* course in the case of the steering compass.

R. & W. HAWTHORN, LESLIE & CO LIMITED.

John T. Galt
Builder's Signature.

Date *19th Feb. 1924*

Is this installation a duplicate of a previous case *No* If so, state name of vessel _____

General Remarks (State quality of workmanship, opinions as to class, &c. _____)

The above installation is in accordance with the Society's Rules. The vessel is eligible in my opinion for notation elec. light, wireless

It is submitted that
this vessel is eligible for
THE RECORD.

elec. light

W.T. Badger
25/4/24

Total Capacity of Generators *156* Kilowatts

The amount of Fee ... *£ 34 : 6/-* : { When applied for, *15/10/1924*

Travelling Expenses (if any) £ : : { When received, *22/10/1924*

W.T. Badger

Surveyor to Lloyd's Register of Shipping.

Committee's Minute _____

Assigned _____