

F.E.

Received by Chief Ship Surveyor 12. 12. 14

Received from Chief Ship Surveyor \_\_\_\_\_

VESSEL'S NAME Steel S.S. 'Amouma' Rpt. Sld No. 26299

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92.)

Transverse No. 79.5Depth "d" 17.83Framing: Table No. 3 page 15.Description Butt AngleLongitudinal No. 28990.Proportions  $\frac{\text{Length}}{\text{Depth}} = 9.5$ Bridge Deck Sheerstrake as approved.

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed  $\star$  100A.1 (Steel) as recommended.

 $\star$  100A.1. (Steel)

2 Dks (Steel)

WB = Cee 2TB a 10x 4 1/2 x B 4 3/4 f 16 1/4 687L. APT 37L

FK. 684. "Cem" Llys a x CP. P 37. B 136. F 440.

M. 12. 14  
14

It is concluded the edges of the middle line  
 and strake of inner bottom plating are double riveted as required  
 but the Surveyors should state if this is so.