

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Date of writing Report *Mar 8th 1927* When handed in at Local Office *Mar 17th 1927* Port of *Liverpool* Received at London Office *13 MAR 1927*No. in Survey held at *Birkenhead* Date, First Survey *Dec 17th 1926* Last Survey *Mar 24th 1927*
Reg. Book. *87947* on the *S.S. "Andalucia"* (Number of Visits *15*)Tons { Gross *13880*
NetBuilt at *Birkenhead* By whom built *Cammell Laird & Co. L^{td}* Yard No. *920* When built *1927*Owners *Messrs Blue Star Line (1920) L^{td}* Port belonging to *London*Electric Light Installation fitted by *Sunderland Forge & Eng^g Co. L^{td}* Contract No. When fitted *1927*

System of Distribution

*Double Wire*Pressure of supply for Lighting *220* volts, Heating *220* volts, Power *220* volts.Direct or Alternating Current, Lighting *Direct* Power *Direct*If alternating current system, state frequency of periods per second *—*Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off *Yes*Generators, do they comply with the requirements regarding overload *Yes*, are they compound wound *Yes*are they over compounded 5 per cent. *Yes*, if not compound wound state distance between each generator *—*Where more than one generator is fitted are they arranged to run in parallel *Yes*, is an adjustable regulating resistance fitted in series with each shunt field *Yes*Are all terminals accessible and clearly marked *Yes*, are they so spaced or shielded that they cannot be accidentally earthed, or short circuited *Yes* Are the lubricating arrangements of the generators as per Rule *Yes*

Position of Generators

*Engine Room St^bd.*is the ventilation in way of the generators satisfactory *Yes*, are they clear of all inflammable material *Yes*if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators *—* and *—*, are the generators protected from mechanical injury and damage from water, steam or oil *Yes*are their axis of rotation fore and aft *Yes*Earthing, are the bedplates and frames of the generating plant efficiently earthed *Yes* are the prime movers and their respective generators in metallic contact *Yes*

Main Switch Boards, where placed

*Engine Room St^bd.*If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard *—*Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes *Yes*are they protected from mechanical injury and damage from water, steam or oil *Yes*, if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards *—* and *—*are they constructed wholly of durable, incombustible non-absorbent materials *Yes*, is all insulation of high dielectric strength and of permanently high insulation resistance *Yes*if semi-insulating material is used, are all conducting parts connected to one pole insulated from the slab with mica or micanite and the slab similarly insulated from its framework *Yes*, and is the frame effectively earthed *Yes*Are the following fittings as per Rule, viz.: — spacing or shielding of live parts *Yes*, accessibility of all parts *Yes*, absence of fuses on back of board *Yes*, proportion of omnibus bars *Yes*, individual fuses to voltmeter, pilot or earth lamp *Yes*, connections of switches *Yes*Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches *Triple Pole, O.L.R.C.*Circuit Breakers for Generators — *3rd Pole to act as equaliser, D.P.O.L.*Circuit Breakers & D.P. Switches & Fuses for Feeder circuits. *✓*Instruments on main switchboard *5* ammeters *2* voltmeters *—* synchronising device for paralleling purposes.Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system *Earth lamps, switches & fuses on each pole.*Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules *Yes*Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule *Yes*

© 2020

Lloyd's Register
Foundation

W3-0074

Insulation of Cables. state type of cables, single or twin Single & twin are the cables insulated and protected as per Tables III or IV of the Rules. Yes

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load 4.5 Volts

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.007 square inch and above provided with soldering sockets

Paper Insulated Cables. *If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound*

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage. Yes

Support and Protection of Cables, state how the cables are supported and protected *Main Cables - L.C. & B. secured with Galv. Iron Clips. Accommodation Cables - L.C. & B. secured with Brass Clips*

If cables are run in wood casings, are the casings and caps secured by screws —, are the cap screws of brass —, are the cables run in separate grooves —. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VI **Yes**

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements Yes

Joints in Cables, state if any, and how made, insulated, and protected.....None

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands

Yes

Bushes in Beams and Non-watertight Positions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed Yes state the material of which the bushes are made Lead

Earthing Connections, state what earthing connections are fitted and their respective sectional areas

...are their connections made as per Rule

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule..... **Yes**

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven **Petrol-Paraffin Generating Set & Switchboard in Emergency Dynamo Room.**

Navigation Lamps, are these separately wired Yes, controlled by separate switch and separate fuses Yes

are the fuses double pole Yes, are the switches and fuses grouped in a position accessible only to the officers on watch. Yes

has each navigation lamp an automatic indicator as per Rule Yes, are separate screens provided for the use of oil and electric side lights Yes

are separate oil lanterns provided for the mast head lights and side lights Yes

Fittings. *are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight*..... Yes

are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected.....

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected.....

... how are the cables lead

where are the controlling switches situated

Searchlight Lamps, No. of _____, whether fixed or portable _____, are their fittings as per Rule _____

Arc Lamps, other than searchlight lamps, No. of _____, are their live parts insulated from the frame or case _____, are their fittings as per Rule _____

Motors, are their working parts readily accessible. Yes, are the coils self-contained and readily removable for replacement. Yes

are the brushes, brush holders, terminals and lubricating arrangements as per Rule Yes, are the motors placed in well-ventilated compartments in which

inflammable gases cannot accumulate and clear of all inflammable material..... Yes

are they protected from mechanical injury and damage from water, steam or oil Yes are their axis of rotation fore and aft Yes

if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type

....., if not of this type, state distance of the combustible material horizontally or vertically above the motors and

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed as per Rule..... Yes

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule.....

Ships carrying Oil having a Flash Point less than 150° F. *Have the special requirements of the Rules been complied with regarding switches, joint boxes*

• section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office.....

PARTICULARS OF GENERATING PLANT

DESCRIPTION OF GENERATOR.	No of	RATED AT				DRIVEN BY.	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	2	200	220	910	375	Compound Steam Engine		
AUXILIARY								
EMERGENCY	1	25	220	114	800	Petrol-Paraffin Engine	Paraffin (Petrol Starting)	
ROTARY TRANSFORMER								

L I G H T I N G A N D H E A T I N G C O N D U C T O R S

[illegible]

MOTOR CONDUCTORS.

Ref. No.	DESCRIPTION.	No. of Motors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	BALLAST PUMP								
	MAIN BILGE LINE PUMPS ...								
	GENERAL SERVICE PUMP								
	EMERGENCY BILGE PUMP ...	1	.04	19	.052	56 ✓	340	V.I.R	L.C.B.
	SANITARY PUMP								
	CIRC. SEA WATER PUMPS ...								
	CIRC. FRESH WATER PUMPS								
	AIR COMPRESSOR								
	FRESH WATER PUMP								
	ENGINE TURNING GEAR ...								
	ENGINE REVERSING GEAR ...								
	LUBRICATING OIL PUMPS ...								
	OIL FUEL TRANSFER PUMP								
	WINDLASS								
	WINCHES, FORWARD ...								
	WINCHES, AFT								
	STEERING GEAR								
	WORKSHOP MOTOR	1	.007	7	.036	20 ✓	100	-do-	-do-
	VENTILATING FANS	14	.1	19	.083	106 ✓	230	-do-	-do-
	Oil Purifier	1	.0045	7	.029	8 ✓	50	-do-	-do-
	Refrig ² Aux ¹⁴	12	.3	37	.103	508* ✓	124	-do-	-do-
	Galley Gear	7	.1	19	.083	98.26 ✓	480	-do-	-do-
	Laundry Gear	4	.0235	7	.064	44 ✓	440	-do-	-do-
	Forced Draught Fans	2	.25ea	37	.093	208ea ✓	90	-do-	-do-

* "All on" load. Max. working load = 240 Amps

© 2020

Lloyd's Register
Foundation

All Conductors are of annealed copper conforming to British Standard Specification No. 7.
The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.
The foregoing is a correct description.

Sunderland Forge & Engineering Co. Ltd. Electrical Engineers. Date 4.3.27
AWight

COMPASSES.

Distance between electric generators or motors and standard compass 130 ft

Distance between electric generators or motors and steering compass 130 ft

The nearest cables to the compasses are as follows:—

A cable carrying 3.25 Ampères 12 feet from standard compass 12 feet from steering compass.

A cable carrying .1 Ampères 10 feet from standard compass led into feet from steering compass.

A cable carrying .1 Ampères led into feet from standard compass 10 feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power. Yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted. Yes

The maximum deviation due to electric currents was found to be Nil degrees on all courses in the case of the standard compass, and 2° W degrees on all courses N. to N.E. by E. course in the case of the steering compass.
and S.W. to N. by W.

J. W. L. Laird and Company Limited.

J. W. L. Laird Builder's Signature. Date 15/3/27
LOCAL SECRETARY.

Is this installation a duplicate of a previous case. Yes. If so, state name of vessel S.S. 'Almeda'

General Remarks (State quality of workmanship, opinions as to class, &c.)

This Installation has been fitted under special survey and is in accordance with the Rules requirements. It was found satisfactory under full working conditions, and in my opinion the vessel is eligible for notation 'Elec. light' in Register book.

It is submitted that
this should be eligible for
THE RECORD.

Dec. Light.

23/3/27

J. W. L. Laird

Total Capacity of Generators 425 Kilowatts

The amount of Fee ... £ 42 : 2 : 6

When applied for,
3/3/1927.

Travelling Expenses (if any) £ :

When received,
31.3.27

J. D. Melton

Surveyor to Lloyd's Register of Shipping.

Committee's Minute

LIVERPOOL 18 MAR. 1927

Assigned

Electric Light.

Im. 9. 2. — Transfer.
(The Surveyors are requested not to write on or below the space for Committee's Minute.)



© 2020

Lloyd's Register
Foundation