

# REPORT ON MACHINERY.

No. 6894

Received at London Office

JUN. 30 JUN 1908

Date of writing Report 29 June 1908 When handed in at Local Office 29 June 1908 Port of Southampton  
 No. in Survey held at Sosport Date, First Survey 24 June Last Survey 24 June 1908  
 Reg. Book. 2 on the Composite Auxiliary Schooner yacht Tampa (Motor) Tons {Gross 225 Net 225  
 Master \_\_\_\_\_ Built at Gosport By whom built Benson & Shillington When built 1908  
 Engines made at Copenhagen By whom made P. Jensen Bragegade 10 when made 1907  
 Boilers made at \_\_\_\_\_ By whom made \_\_\_\_\_ when made \_\_\_\_\_  
 Registered Horse Power 60 B.H.P. Owners M. A. de Amboise Port belonging to \_\_\_\_\_  
 Nom. Horse Power as per Section 28 \_\_\_\_\_ Is Refrigerating Machinery fitted for cargo purposes \_\_\_\_\_ Is Electric Light fitted Yes

ENGINES, &c.—Description of Engines Internal combustion paraffin engine No. of Cylinders 4 No. of Cranks 4  
 Dia. of Cylinders 310 mm Length of Stroke 314 mm Revs. per minute 300 Dia. of Screw shaft as per rule 100 mm Material of steel  
 Is the screw shaft fitted with a continuous liner the whole length of the stern tube no liner Is the after end of the liner made water tight  
 in the propeller boss Yes If the liner is in more than one length are the joints burned none If the liner does not fit tightly at the part  
 between the bearings in the stern tube, is the space charged with a plastic material insoluble in water and non-corrosive yes with grease If two  
 liners are fitted, is the shaft lapped or protected between the liners only with grease Length of stern bush 330 mm  
 Dia. of Tunnel shaft as per rule 160 mm Dia. of Crank shaft journals as per rule 100 mm Dia. of Crank pin 100 mm Size of Crank webs 130x80 mm Dia. of thrust shaft under  
 collars 80 mm Dia. of screw 56 mm Pitch of Screw adjustable No. of Blades 2 State whether moveable yes Total surface 578 sq"  
 No. of Feed pumps 2 Diameter of ditto 2 3/16" Stroke 3" Can one be overhauled while the other is at work yes  
 No. of Bilge pumps none Diameter of ditto \_\_\_\_\_ Stroke \_\_\_\_\_ Can one be overhauled while the other is at work \_\_\_\_\_  
 No. of Donkey Engines \_\_\_\_\_ Sizes of Pumps \_\_\_\_\_ No. and size of Suctions connected to both Bilge and Donkey pumps  
 In Engine Room \_\_\_\_\_ In Holds, &c. \_\_\_\_\_

No. of Bilge Injections \_\_\_\_\_ sizes \_\_\_\_\_ Connected to condenser, or to circulating pump \_\_\_\_\_ Is a separate Donkey Suction fitted in Engine room & size \_\_\_\_\_  
 Are all the bilge suction pipes fitted with roses \_\_\_\_\_ Are the roses in Engine room always accessible \_\_\_\_\_ Are the sluices on Engine room bulkheads always accessible \_\_\_\_\_  
 Are all connections with the sea direct on the skin of the ship \_\_\_\_\_ Are they Valves or Cocks \_\_\_\_\_  
 Are they fixed sufficiently high on the ship's side to be seen without lifting the stokehold plates \_\_\_\_\_ Are the Discharge Pipes above or below the deep water line \_\_\_\_\_  
 Are they each fitted with a Discharge Valve always accessible on the plating of the vessel \_\_\_\_\_ Are the Blow Off Cocks fitted with a spigot and brass covering plate \_\_\_\_\_  
 What pipes are carried through the bunkers \_\_\_\_\_ How are they protected \_\_\_\_\_  
 Are all Pipes, Cocks, Valves, and Pumps in connection with the machinery and all boiler mountings accessible at all times \_\_\_\_\_  
 Are the Bilge Suction Pipes, Cocks, and Valves arranged so as to prevent any communication between the sea and the bilges \_\_\_\_\_  
 Dates of examination of completion of fitting of Sea Connections \_\_\_\_\_ of Stern Tube \_\_\_\_\_ Screw shaft and Propeller \_\_\_\_\_  
 Is the Screw Shaft Tunnel watertight \_\_\_\_\_ Is it fitted with a watertight door \_\_\_\_\_ worked from \_\_\_\_\_

OILERS, &c.—(Letter for record \_\_\_\_\_) Manufacturers of Steel \_\_\_\_\_  
 Total Heating Surface of Boilers \_\_\_\_\_ Is Forced Draft fitted \_\_\_\_\_ No. and Description of Boilers \_\_\_\_\_  
 Working Pressure \_\_\_\_\_ Tested by hydraulic pressure to \_\_\_\_\_ Date of test \_\_\_\_\_ No. of Certificate \_\_\_\_\_  
 Can each boiler be worked separately \_\_\_\_\_ Area of fire grate in each boiler \_\_\_\_\_ No. and Description of Safety Valves to  
 each boiler \_\_\_\_\_ Area of each valve \_\_\_\_\_ Pressure to which they are adjusted \_\_\_\_\_ Are they fitted with easing gear \_\_\_\_\_  
 Smallest distance between boilers or uptakes and bunkers or woodwork \_\_\_\_\_ Mean dia. of boilers \_\_\_\_\_ Length \_\_\_\_\_ Material of shell plates \_\_\_\_\_  
 Thickness \_\_\_\_\_ Range of tensile strength \_\_\_\_\_ Are the shell plates welded or flanged \_\_\_\_\_ Descrip. of riveting: cir. seams \_\_\_\_\_  
 long. seams \_\_\_\_\_ Diameter of rivet holes in long. seams \_\_\_\_\_ Pitch of rivets \_\_\_\_\_ Lap of plates or width of butt straps \_\_\_\_\_  
 Per centages of strength of longitudinal joint \_\_\_\_\_ rivets \_\_\_\_\_ Working pressure of shell by rules \_\_\_\_\_ Size of manhole in shell \_\_\_\_\_  
 Size of compensating ring \_\_\_\_\_ No. and Description of Furnaces in each boiler \_\_\_\_\_ Material \_\_\_\_\_ Outside diameter \_\_\_\_\_  
 Length of plain part \_\_\_\_\_ Thickness of plates \_\_\_\_\_ crown \_\_\_\_\_ bottom \_\_\_\_\_ Description of longitudinal joint \_\_\_\_\_ No. of strengthening rings \_\_\_\_\_  
 Working pressure of furnace by the rules \_\_\_\_\_ Combustion chamber plates: Material \_\_\_\_\_ Thickness: Sides \_\_\_\_\_ Back \_\_\_\_\_ Top \_\_\_\_\_ Bottom \_\_\_\_\_  
 Pitch of stays to ditto: Sides \_\_\_\_\_ Back \_\_\_\_\_ Top \_\_\_\_\_ If stays are fitted with nuts or riveted heads \_\_\_\_\_ Working pressure by rules \_\_\_\_\_  
 Material of stays \_\_\_\_\_ Diameter at smallest part \_\_\_\_\_ Area supported by each stay \_\_\_\_\_ Working pressure by rules \_\_\_\_\_ End plates in steam space: \_\_\_\_\_  
 Material \_\_\_\_\_ Thickness \_\_\_\_\_ Pitch of stays \_\_\_\_\_ How are stays secured \_\_\_\_\_ Working pressure by rules \_\_\_\_\_ Material of stays \_\_\_\_\_  
 Diameter at smallest part \_\_\_\_\_ Area supported by each stay \_\_\_\_\_ Working pressure by rules \_\_\_\_\_ Material of Front plates at bottom \_\_\_\_\_  
 Thickness \_\_\_\_\_ Material of Lower back plate \_\_\_\_\_ Thickness \_\_\_\_\_ Greatest pitch of stays \_\_\_\_\_ Working pressure of plate by rules \_\_\_\_\_  
 Diameter of tubes \_\_\_\_\_ Pitch of tubes \_\_\_\_\_ Material of tube plates \_\_\_\_\_ Thickness: Front \_\_\_\_\_ Back \_\_\_\_\_ Mean pitch of stays \_\_\_\_\_  
 Pitch across wide water spaces \_\_\_\_\_ Working pressures by rules \_\_\_\_\_ Girders to Chamber tops: Material \_\_\_\_\_ Depth and \_\_\_\_\_  
 thickness of girder at centre \_\_\_\_\_ Length as per rule \_\_\_\_\_ Distance apart \_\_\_\_\_ Number and pitch of stays in each \_\_\_\_\_  
 Working pressure by rules \_\_\_\_\_ Superheater or Steam chest; how connected to boiler \_\_\_\_\_ Can the superheater be shut off and the boiler worked  
 separately \_\_\_\_\_ Diameter \_\_\_\_\_ Length \_\_\_\_\_ Thickness of shell plates \_\_\_\_\_ Material \_\_\_\_\_ Description of longitudinal joint \_\_\_\_\_ Diam. of rivet \_\_\_\_\_  
 Pitch of rivets \_\_\_\_\_ Working pressure of shell by rules \_\_\_\_\_ Diameter of flue \_\_\_\_\_ Material of flue plates \_\_\_\_\_ Thickness \_\_\_\_\_  
 If stiffened with rings \_\_\_\_\_ Distance between rings \_\_\_\_\_ Working pressure by rules \_\_\_\_\_ End plates: Thickness \_\_\_\_\_ How stayed \_\_\_\_\_  
 Working pressure of end plates \_\_\_\_\_ Area of safety valves to superheater \_\_\_\_\_ Are they fitted with easing gear \_\_\_\_\_

W315-0110



# VERTICAL DONKEY BOILER— Manufacturers of Steel

No. \_\_\_\_\_ Description \_\_\_\_\_  
 Made at \_\_\_\_\_ By whom made \_\_\_\_\_ When made \_\_\_\_\_ Where fixed \_\_\_\_\_  
 Working pressure tested by hydraulic pressure to \_\_\_\_\_ Date of test \_\_\_\_\_ No. of Certificate \_\_\_\_\_ Fire grate area \_\_\_\_\_ Description of Safety  
 Valves \_\_\_\_\_ No. of Safety Valves \_\_\_\_\_ Area of each \_\_\_\_\_ Pressure to which they are adjusted \_\_\_\_\_ Date of adjustment \_\_\_\_\_  
 If fitted with easing gear \_\_\_\_\_ If steam from main boilers can enter the donkey boiler \_\_\_\_\_ Dia. of donkey boiler \_\_\_\_\_ Length \_\_\_\_\_  
 Material of shell plates \_\_\_\_\_ Thickness \_\_\_\_\_ Range of tensile strength \_\_\_\_\_ Descrip. of riveting long. seams \_\_\_\_\_  
 Dia. of rivet holes \_\_\_\_\_ Whether punched or drilled \_\_\_\_\_ Pitch of rivets \_\_\_\_\_ Lap of plating \_\_\_\_\_ Per centage of strength of joint \_\_\_\_\_ Rivets \_\_\_\_\_  
 Working pressure of shell by rules \_\_\_\_\_ Thickness of shell crown plates \_\_\_\_\_ Radius of do. \_\_\_\_\_ No. of stays to do. \_\_\_\_\_ Dia. of stays \_\_\_\_\_  
 Diameter of furnace Top \_\_\_\_\_ Bottom \_\_\_\_\_ Length of furnace \_\_\_\_\_ Thickness of furnace plates \_\_\_\_\_ Description of joint \_\_\_\_\_  
 Working pressure of furnace by rules \_\_\_\_\_ Thickness of furnace crown plates \_\_\_\_\_ Stayed by \_\_\_\_\_  
 Diameter of uptake \_\_\_\_\_ Thickness of uptake plates \_\_\_\_\_ Thickness of water tubes \_\_\_\_\_ Dates of survey \_\_\_\_\_

SPARE GEAR. State the articles supplied:—

The foregoing is a correct description,

Manufacturer.



Dates of Survey while building  
 During progress of work in shops - -  
 During erection on board vessel - -  
 Total No. of visits

13

Is the approved plan of main boiler forwarded herewith

Dates of Examination of principal parts—Cylinders \_\_\_\_\_ Slides \_\_\_\_\_ Covers \_\_\_\_\_ Pistons \_\_\_\_\_ Rods \_\_\_\_\_  
 Connecting rods \_\_\_\_\_ Crank shaft \_\_\_\_\_ Thrust shaft \_\_\_\_\_ Tunnel shafts \_\_\_\_\_ Screw shaft \_\_\_\_\_ Propeller \_\_\_\_\_  
 Stern tube \_\_\_\_\_ Steam pipes tested \_\_\_\_\_ Engine and boiler seatings \_\_\_\_\_ Engines holding down bolts \_\_\_\_\_  
 Completion of pumping arrangements \_\_\_\_\_ Boilers fixed \_\_\_\_\_ Engines tried under steam \_\_\_\_\_  
 Main boiler safety valves adjusted \_\_\_\_\_ Thickness of adjusting washers \_\_\_\_\_  
 Material of Crank shaft \_\_\_\_\_ Identification Mark on Do. \_\_\_\_\_ Material of Thrust shaft \_\_\_\_\_ Identification Mark on Do. \_\_\_\_\_  
 Material of Tunnel shafts \_\_\_\_\_ Identification Marks on Do. \_\_\_\_\_ Material of Screw shafts \_\_\_\_\_ Identification Marks on Do. \_\_\_\_\_  
 Material of Steam Pipes \_\_\_\_\_ Test pressure \_\_\_\_\_

General Remarks (State quality of workmanship, opinions as to class, &c.)

This vessel has now been fitted with an internal combustion  
 paraffin motor. The machinery was tried under full  
 working conditions and found satisfactory.  
 I beg to recommend that no character be assigned the  
 machinery, but that her class be recorded experimental  
 in the Yacht Register Book.

It is submitted that the  
 notation of "Paraffin Motor"  
 might be recorded on the  
 Yacht Register.

The amount of Entry Fee. £ 3 : 3 : 0  
 Special £ 3 : 3 : 0  
 Donkey Boiler Fee £ 1 : 19 : 0  
 Travelling Expenses (if any) £

When applied for,

When received,

3.7.08

3.7.08

Engineer Surveyor to Lloyd's Register of British & Foreign Shipping.

Committee's Minute

Assigned

Paraffin Motor



© 2019

Lloyd's Register  
 Foundation