

Maximum pressure in cylinders 500 lb. Diameter of cylinders 28 3/4 Length of stroke 59 No. of cylinders 6
Span of bearings, adjacent to the Crank, measured from inner edge to inner edge 980 mm Is there a bearing between

2c.11.30.

1E

Received by Chief Engineer Surveyor

Received from Chief Engineer Surveyor

VESSEL'S NAME "ATHELFOAM"

Rpt. Liverpool No. 98861

The remarks of the Chief Engineer Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/6/92.)

Type of Engine OIL ENGINE 4 SC.S.A. 6 cy. 28 3/4" - 59"

NORTH EASTERN MAR. ENG. CO. LTD.
WALLSEND.

If Boilers fitted with forced draught ✓

Tail Shaft. If fitted with a continuous liner yes.

If fitted with an outside gland of
approved type ✓

This vessel's machinery appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed + L.M.C. 6.31.

C.L. 2 DB. 180 lb.

cm.
25/6/31.



© 2020

Lloyd's Register
Foundation

W336-0052

Is there a drain arrangement fitted at the lowest part of each receiver ✓

High Pressure Air Receivers No 2 ✓

Cubic capacity of each 18.5 cu. ft.

Internal diameter 15 3/4"